

Inductors

For Power Line

Radial

SL Series SL1215 Type

FEATURES

- This is a low R_{dc}, best for the power supply line.
- There is a series of many types from low inductance to high inductance in large current.

APPLICATIONS

Televisions, CRT displays, printers, and various types of electronic products.

SPECIFICATIONS

Operating temperature range	−40 to +85°C [Including self-temperature rise]
Storage temperature range	−40 to +85°C [Unit of products]
Terminal strength	9.8N min.*

* Only for lead type specification. Wire type's specification depends on the vibration test.

PRODUCT IDENTIFICATION

SL	1215	-	100	K	3R6
(1)	(2)		(3)	(4)	(5)

(1)Series name

(2)Dimensions

Type	Dimension	Lead pitch
1215	ø12×14.5mm	11mm (10 to 100μH for wire type) 7.5mm (150 to 5600μH for lead type)

(3)Inductance value

100	10μH
102	1000μH

(4)Inductance tolerance

K	±10%
---	------

(5)Rated current

3R6	3.6A
R20	0.2A

PACKAGING STYLE AND QUANTITIES

Packaging style	Quantity
Bulk	100 pieces/tray

Inductors


For Power Line

Radial


SL Series SL1215 Type

SHAPES AND DIMENSIONS

WIRE TYPE (10 to 100 μ H)



LEAD TYPE (150 to 5600 μ H)



Weight: 7g typ.
Dimensions in mm



ELECTRICAL CHARACTERISTICS

Inductance (μ H)	Inductance tolerance	DC resistance (Ω)max.	Rated current(A)*max.		Part No.	Lead wire style
			Based on inductance change	Based on temperature rise		
10	$\pm 10\%$	0.019	9.8	3.6	SL1215-100K3R6	Wire type
15	$\pm 10\%$	0.022	8.9	3.3	SL1215-150K3R3	Wire type
22	$\pm 10\%$	0.031	7.2	2.8	SL1215-220K2R8	Wire type
33	$\pm 10\%$	0.044	6	2.3	SL1215-330K2R3	Wire type
47	$\pm 10\%$	0.059	4.9	2	SL1215-470K2R0	Wire type
68	$\pm 10\%$	0.073	4.2	1.8	SL1215-680K1R8	Wire type
100	$\pm 10\%$	0.1	3.4	1.5	SL1215-101K1R5	Wire type
150	$\pm 10\%$	0.15	2.8	1.3	SL1215-151K1R3	Lead type
220	$\pm 10\%$	0.26	1.9	1	SL1215-221K1R0	Lead type
330	$\pm 10\%$	0.32	1.8	0.91	SL1215-331KR91	Lead type
470	$\pm 10\%$	0.48	1.6	0.72	SL1215-471KR72	Lead type
680	$\pm 10\%$	0.73	1.3	0.58	SL1215-681KR58	Lead type
1000	$\pm 10\%$	0.96	1.1	0.51	SL1215-102KR51	Lead type
1500	$\pm 10\%$	1.4	0.9	0.42	SL1215-152KR42	Lead type
2200	$\pm 10\%$	2.5	0.7	0.31	SL1215-222KR31	Lead type
3300	$\pm 10\%$	3.3	0.6	0.27	SL1215-332KR27	Lead type
5600	$\pm 10\%$	6.4	0.47	0.2	SL1215-562KR20	Lead type

* Rated current: Value obtained when current flows and self-temperature has risen to 25°C.

- Test equipment Inductance: LCR METER YHP4261A, or equivalent
Rdc: MILLIOHM METER VP-2941A MATSUSHITA, or equivalent

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE CHANGE vs. DC SUPERPOSITION CHARACTERISTICS

