



3.3V CMOS ONE-TO-FOUR ADDRESS/CLOCK DRIVER WITH 3-STATE OUTPUTS AND 5 VOLT TOLERANT I/O

IDT74LVC16344A

FEATURES:

- Typical $t_{SK(0)}$ (Output Skew) < 250ps
- ESD > 2000V per MIL-STD-883, Method 3015;
> 200V using machine model (C = 200pF, R = 0)
- 0.635mm pitch SSOP, 0.50mm pitch TSSOP
and 0.40mm pitch TVSOP packages
- Extended commercial range of -40°C to +85°C
- $V_{CC} = 3.3V \pm 0.3V$, Normal Range
- $V_{CC} = 2.7V$ to 3.6V, Extended Range
- CMOS power levels (0.4μW typ. static)
- All inputs, outputs and I/O are 5 Volt tolerant
- Supports hot insertion

Drive Features for LVC16344A:

- High Output Drivers: $\pm 24mA$
- Reduced system switching noise

APPLICATIONS:

- 5V and 3.3V mixed voltage systems
- Data communication and telecommunication systems


DESCRIPTION:

The LVC16344A is a 1:4 address/clock driver built using advanced dual metal CMOS technology. This high speed, low power device provides the ability to fanout to memory arrays. Eight banks, each with a fanout of 4, and 3-state control provide efficient address distribution. One or more banks may be used for clock distribution.

All pins of this address line driver can be driven from either 3.3V or 5V devices. This feature allows the use of this device as a translator in a mixed 3.3V/5V supply system.

The LVC16344A has been designed with a $\pm 24mA$ output driver. This driver is capable of driving a moderate to heavy load while maintaining speed performance.


Functional Block Diagram



EXTENDED COMMERCIAL TEMPERATURE RANGE

MARCH 1999

PIN CONFIGURATION



ABSOLUTE MAXIMUM RATINGS (1)

Symbol	Description	Max.	Unit
V _{TERM} (2)	Terminal Voltage with Respect to GND	− 0.5 to +6.5	V
V _{TERM} (3)	Terminal Voltage with Respect to GND	− 0.5 to +6.5	V
T _{STG}	Storage Temperature	− 65 to +150	°C
I _{OUT}	DC Output Current	− 50 to +50	mA
I _{IK} I _{OK}	Continuous Clamp Current, V _I < 0 or V _O < 0	− 50	mA
I _{CC} I _{SS}	Continuous Current through each V _{CC} or GND	±100	mA

LVC Link

NOTES:

- Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
- V_{CC} terminals.
- All terminals except V_{CC}.

CAPACITANCE (T_A = +25°C, f = 1.0MHz)

Symbol	Parameter(1)	Conditions	Typ.	Max.	Unit
C _{IN}	Input Capacitance	V _{IN} = 0V	4.5	6	pF
C _{OUT}	Output Capacitance	V _{OUT} = 0V	6.5	8	pF
C _{I/O}	I/O Port Capacitance	V _{IN} = 0V	6.5	8	pF

LVC Link

NOTE:

- As applicable to the device type.

PIN DESCRIPTION

Pin Names	Description
$\overline{OE}x$	3-State Output Enable Inputs (Active LOW)
A _x	Data Inputs
B _{xx}	3-State Outputs

FUNCTION TABLE

Inputs		Outputs
$\overline{OE}x$	A _x	B _{xx}
L	L	L
L	H	H
H	X	Z

NOTE:

- H = HIGH Voltage Level
L = LOW Voltage Level
X = Don't Care
Z = High-Impedance

DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE

Following Conditions Apply Unless Otherwise Specified:

Operating Condition: $T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$

Symbol	Parameter	Test Conditions		Min.	Typ. ⁽¹⁾	Max.	Unit
V_{IH}	Input HIGH Voltage Level	$V_{CC} = 2.3\text{V to } 2.7\text{V}$		1.7	—	—	V
		$V_{CC} = 2.7\text{V to } 3.6\text{V}$		2	—	—	
V_{IL}	Input LOW Voltage Level	$V_{CC} = 2.3\text{V to } 2.7\text{V}$		—	—	0.7	V
		$V_{CC} = 2.7\text{V to } 3.6\text{V}$		—	—	0.8	
I_{IH} I_{IL}	Input Leakage Current	$V_{CC} = 3.6\text{V}$	$V_I = 0 \text{ to } 5.5\text{V}$	—	—	± 5	μA
I_{OZH} I_{OZL}	High Impedance Output Current (3-State Output pins)	$V_{CC} = 3.6\text{V}$	$V_O = 0 \text{ to } 5.5\text{V}$	—	—	± 10	μA
I_{OFF}	Input/Output Power Off Leakage	$V_{CC} = 0\text{V}$, V_{IN} or $V_O \leq 5.5\text{V}$		—	—	± 50	μA
V_{IK}	Clamp Diode Voltage	$V_{CC} = 2.3\text{V}$, $I_{IN} = -18\text{mA}$		—	-0.7	-1.2	V
V_H	Input Hysteresis	$V_{CC} = 3.3\text{V}$		—	100	—	mV
I_{CCL} I_{CCH} I_{CCZ}	Quiescent Power Supply Current	$V_{CC} = 3.6\text{V}$	$V_{IN} = \text{GND or } V_{CC}$	—	—	10	μA
			$3.6 \leq V_{IN} \leq 5.5\text{V}^{(2)}$	—	—	10	
ΔI_{CC}	Quiescent Power Supply Current Variation	One input at $V_{CC} - 0.6\text{V}$ other inputs at V_{CC} or GND		—	—	500	μA

LVC Link

NOTES:

- Typical values are at $V_{CC} = 3.3\text{V}$, $+25^{\circ}\text{C}$ ambient.
- This applies in the disabled state only.

OUTPUT DRIVE CHARACTERISTICS

Symbol	Parameter	Test Conditions ⁽¹⁾		Min.	Max.	Unit
V_{OH}	Output HIGH Voltage	$V_{CC} = 2.3\text{V to } 3.6\text{V}$	$I_{OH} = -0.1\text{mA}$	$V_{CC} - 0.2$	—	V
		$V_{CC} = 2.3\text{V}$	$I_{OH} = -6\text{mA}$	2	—	
		$V_{CC} = 2.3\text{V}$	$I_{OH} = -12\text{mA}$	1.7	—	
		$V_{CC} = 2.7\text{V}$		2.2	—	
		$V_{CC} = 3.0\text{V}$		2.4	—	
		$V_{CC} = 3.0\text{V}$	$I_{OH} = -24\text{mA}$	2.2	—	
V_{OL}	Output LOW Voltage	$V_{CC} = 2.3\text{V to } 3.6\text{V}$	$I_{OL} = 0.1\text{mA}$	—	0.2	V
		$V_{CC} = 2.3\text{V}$	$I_{OL} = 6\text{mA}$	—	0.4	
			$I_{OL} = 12\text{mA}$	—	0.7	
		$V_{CC} = 2.7\text{V}$	$I_{OL} = 12\text{mA}$	—	0.4	
		$V_{CC} = 3.0\text{V}$	$I_{OL} = 24\text{mA}$	—	0.55	

LVC Link

NOTE:

- V_{IH} and V_{IL} must be within the min. or max. range shown in the DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE table for the appropriate V_{CC} range. $T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$.

OPERATING CHARACTERISTICS, $V_{CC} = 3.3V \pm 0.3V$, $T_A = 25^\circ C$

Symbol	Parameter	Test Conditions	Typical	Unit
CPD	Power Dissipation Capacitance per buffer/driver Outputs enabled	$C_L = 0pF$, $f = 10MHz$		pF
CPD	Power Dissipation Capacitance per buffer/driver Outputs disabled			pF

SWITCHING CHARACTERISTICS (1)

Symbol	Parameter	$V_{CC} = 2.7V$		$V_{CC} = 3.3V \pm 0.3V$		Unit
		Min.	Max.	Min.	Max.	
tPLH tPHL	Propagation Delay Ax to Bxx			1.5	4.3	ns
tpZH tpZL	Output Enable Time $\overline{OE}_x$ to Bxx			1.5	5.8	ns
tPHZ tPLZ	Output Disable Time $\overline{OE}_x$ to Bxx			1.5	5.2	ns
tsk(b)	Skew between outputs of same bank and same package (same transition)			—	350	ps
tsk(o)	Skew between outputs of all banks of same package (A1 thru A8 tied together) (2)			—	500	ps

NOTES:

1. See test circuits and waveforms. $T_A = -40^\circ C$ to $+85^\circ C$.
2. Skew between any two outputs of the same package and switching in the same direction.


TEST CIRCUITS AND WAVEFORMS

TEST CONDITIONS

Symbol	V _{CC} (1) = 3.3V ±0.3V	V _{CC} (1) = 2.7V	V _{CC} (2) = 2.5V ±0.2V	Unit
V _{LOAD}	6	6	2 x V _{CC}	V
V _{IH}	2.7	2.7	V _{CC}	V
V _T	1.5	1.5	V _{CC} / 2	V
V _{LZ}	300	300	150	mV
V _{HZ}	300	300	150	mV
C _L	50	50	30	pF

LVC Link

TEST CIRCUITS FOR ALL OUTPUTS



LVC Link

DEFINITIONS:

C_L = Load capacitance: includes jig and probe capacitance.

R_T = Termination resistance: should be equal to Z_{OUT} of the Pulse Generator.

NOTE:


1. Pulse Generator for All Pulses: Rate ≤ 10MHz; t_F ≤ 2.5ns; t_R ≤ 2.5ns.
2. Pulse Generator for All Pulses: Rate ≤ 10MHz; t_F ≤ 2ns; t_R ≤ 2ns.

SWITCH POSITION

Test	Switch
Open Drain Disable Low Enable Low	V _{LOAD}
Disable High Enable High	GND
All Other tests	Open

LVC Link

OUTPUT SKEW - t_{SK}(x)




$$t_{SK}(x) = |t_{PLH2} - t_{PLH1}| \text{ or } |t_{PHL2} - t_{PHL1}|$$

LVC Link

NOTES:


1. For t_{SK}(o) OUTPUT1 and OUTPUT2 are any two outputs.
2. For t_{SK}(b) OUTPUT1 and OUTPUT2 are in the same bank.

PROPAGATION DELAY



LVC Link

ENABLE AND DISABLE TIMES




LVC Link

NOTE:


1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH.

SET-UP, HOLD, AND RELEASE TIMES



LVC Link

PULSE WIDTH



LVC Link

ORDERING INFORMATION

IDT	XX	LVC	X	XX	XXXX	XX	
Temp. Range	Bus-Hold		Family	Device Type	Package		
						PV	Shrink Small Outline Package (SO56-1)
						PA	Thin Shrink Small Outline Package (SO56-2)
						PF	Thin Very Small Outline Package (SO56-3)
				344A			One-to-Four Address/Clock Driver
			16				Double-Density with Resistors, $\pm 24\text{mA}$
		Blank					No Bus-hold
74							-40 °C to +85 °C



CORPORATE HEADQUARTERS

2975 Stender Way
 Santa Clara, CA 95054

for SALES:






800-345-7015 or 408-727-6116
 fax: 408-492-8674
www.idt.com*

*To search for sales office near you, please click the sales button found on our home page or dial the 800# above and press 2.
 The IDT logo is a registered trademark of Integrated Device Technology, Inc.

PACKAGE DIAGRAM OUTLINES

SSOP

REVISIONS				
DCN	REV	DESCRIPTION	DATE	APPROVED
17893	00	INITIAL RELEASE	07/15/90	A. FUNCELL
22377	01	REMOVE CHAMFER FROM PACKAGE	04/15/92	T. VU
27492	02	REDRAW TO JEDEC FORMAT	02/01/95	



TOLERANCES UNLESS SPECIFIED		Integrated Device Technology, Inc.	
DECIMAL	ANGULAR	2075 Slender Way, Santa Clara, CA 95054	
XXX	±	PHONE: (408) 727-8118	
XXX		FAX: (408) 482-8874	
XXX		TWC: 910-338-2070	
APPROVALS	DATE	TITLE	REV
DRAWN	08/15/90	PV PACKAGE OUTLINE	02
CHECKED		.300" BODY WIDTH SSOP	
		.025" PITCH	
		SIZE	
		C	
		DRAWING No.	
		PSC-4029	
DO NOT SCALE DRAWING			

PACKAGE DIAGRAM OUTLINES SSOP (Continued)


REVISIONS				
DCN	REV	DESCRIPTION	DATE	APPROVED
17893	00	INITIAL RELEASE	07/15/90	A. FUNCELL
22377	01	REMOVE CHAMFER FROM PACKAGE	04/15/92	T. WJ
27492	02	REDRAW TO JEDEC FORMAT	02/01/95	

DWG #		S048-1				DWG #		S056-1			
SYMBOL	JEDEC VARIATION				NOTE	JEDEC VARIATION				NOTE	
	AA			AB							
	MIN	NOM	MAX	MIN		NOM	MAX				
A	.095	.102	.110		.095	.102	.110				
A1	.008	.012	.016		.008	.012	.016				
A2	.088	.090	.092		.088	.090	.092				
D	.620	.625	.630	4,5	.720	.725	.730	4,5			
E	.395	.405	.420	3	.395	.405	.420	3			
E1	.291	.295	.299	4,6	.291	.295	.299	4,6			
N	48				56						

NOTES:

- ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
- DATUMS **-A-** AND **-B-** TO BE DETERMINED AT DATUM PLANE **-H-**
- DIMENSION E TO BE DETERMINED AT SEATING PLANE **-C-**
- DIMENSIONS D AND E1 ARE TO BE DETERMINED AT DATUM PLANE **-H-**
- DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS AND GATE BURRS SHALL NOT EXCEED .006 PER SIDE
- DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSIONS. INTERLEAD FLASH OR PROTRUSIONS SHALL NOT EXCEED .015 PER SIDE
- THESE DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN .005 AND .010 FROM LEAD TIP
- LEAD WIDTH DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION IS .004 IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT
- THE CHAMFER ON THE PACKAGE BODY IS OPTIONAL. IF IT IS NOT PRESENT, A VISUAL INDEX FEATURE MUST BE LOCATED WITHIN THE ZONE INDICATED
- ALL DIMENSIONS ARE IN INCHES
- THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MO-118, VARIATION AA & AB

LAND PATTERN DIMENSIONS








	MIN	MAX	MIN	MAX
P	.450	.458	.450	.458
P1	.282	.290	.282	.290
P2	.575 BSC		.675 BSC	
X	.010	.018	.010	.018
e	.025 BSC		.025 BSC	
N	48		56	

TOLERANCES UNLESS SPECIFIED		Integrated Device Technology, Inc.	
DECIMAL	ANGULAR	2075 Stoner Way, Santa Clara, CA 95054	
X.XX	±	PHONE: (408) 727-8116	
X.XXX	±	FAX: (408) 482-8874	
X.XXX	±	TW: 810-338-2070	
APPROVALS	DATE	TITLE	REV
DRN	06/15/90	PV PACKAGE OUTLINE	
CHECKED		.300" BODY WIDTH SSOP	
		.025" PITCH	
		SIZE	REV
		C	02
		DRAWING No.	
		PSC-4029	
		DO NOT SCALE DRAWING	

PACKAGE DIAGRAM OUTLINES

TSSOP

REVISIONS				
DCN	REV	DESCRIPTION	DATE	APPROVED
23757	00	INITIAL RELEASE	02/15/93	T. VU
26315	01	CHANGE DIMS A1 & A2	05/18/94	DG
26490	02	CHANGE DIM A1	07/21/94	T. VU
27494	03	REDRAW TO JEDEC FORMAT	03/08/95	



TOLERANCES UNLESS SPECIFIED		INTEGRATED DEVICE TECHNOLOGY, Inc.	
DECIMAL	ANGULAR	2975 Slender Way, Santa Clara, CA 95054	PHONE: (408) 727-8118
XXX.X	±	FAX: (408) 492-8674	TW: 910-336-2070
XXXX.X			
APPROVALS	DATE	TITLE	PA PACKAGE OUTLINE
DRAWN	01/15/93	6.10 mm BODY WIDTH TSSOP	
CHECKED		.50 mm PITCH	
SIZE	DRAWING No.	PSC-4039	REV 03
C			
DO NOT SCALE DRAWING			

PACKAGE DIAGRAM OUTLINES TSSOP (Continued)


SYMBOL	DWG #			S048-2		NOTE	DWG #			S056-2		NOTE		
	JEDEC VARIATION						JEDEC VARIATION							
	ED						EE							
	MIN	NOM	MAX					MIN	NOM	MAX				
A	-	-	1.10				-	-	1.10					
A1	.05	-	.15				.05	-	.15					
A2	.85	1.00	1.05				.85	1.00	1.05					
D	12.40	12.50	12.60	4,5			13.90	14.00	14.10	4,5				
E	7.95	8.10	8.25	3			7.95	8.10	8.25	3				
E1	6.00	6.10	6.20	4,6			6.00	6.10	6.20	4,6				
N	48						56							

NOTES:

- ALL DIMENSIONING AND TOLERANCING CONFORM TO ANSI Y14.5M-1982
- DATUMS $\square$ -A- and $\square$ -B- TO BE DETERMINED AT DATUM PLANE $\square$ -H-
- DIMENSION E TO BE DETERMINED AT SEATING PLANE $\square$ -C-
- DIMENSIONS D AND E1 ARE TO BE DETERMINED AT DATUM PLANE $\square$ -H-
- DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED .15 mm PER SIDE
- DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSIONS. INTERLEAD FLASH OR PROTRUSIONS SHALL NOT EXCEED .25 mm PER SIDE
- DETAIL OF PIN 1 IDENTIFIER IS OPTIONAL BUT MUST BE LOCATED WITHIN THE ZONE INDICATED
- LEAD WIDTH DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION IS .08 mm IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT
- THESE DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN .10 AND .25 mm FROM THE LEAD TIP
- ALL DIMENSIONS ARE IN MILLIMETERS
- THIS OUTLINE CONFORMS TO JEDEC PUBLICATION 95 REGISTRATION MQ-153, VARIATION ED & EE

REVISIONS				
DCN	REV	DESCRIPTION	DATE	APPROVED
23757	00	INITIAL RELEASE	02/15/93	T. VU
26315	01	CHANGE DIMS A1 & A2	05/18/94	DG
26490	02	CHANGE DIM A1	07/21/94	T. VU
27494	03	REDRAW TO JEDEC FORMAT	03/08/95	

LAND PATTERN DIMENSIONS




	MIN	MAX	MIN	MAX
P	8.90	9.10	8.90	9.10
P1	5.90	6.10	5.90	6.10
P2	11.50	BSC	13.50	BSC
X	.30	.40	.30	.40
e	.50	BSC	.50	BSC
N	48		56	

TOLERANCES UNLESS SPECIFIED		Integrated Device Technology, Inc. 2975 Slender Way, Santa Clara, CA 95054 PHONE: (408) 727-8118 FAX: (408) 482-8874 TWC: 910-338-2070	
DECIMAL	ANGULAR		
XXX.X	±		
XXX.XX			
XXX.XXX			
APPROVALS	DATE	TITLE PA PACKAGE OUTLINE	
DRAWN <i>AA</i>	01/19/93	6.10 mm BODY WIDTH TSSOP	
CHECKED		.50 mm PITCH	
		SIZE	DRAWING No.
		C	PSC-4039
			REV 03
DO NOT SCALE DRAWING			



TVSOP

The Most Compact Double Density Package




TVSOP Package	Typical Dimensions (in mm)				Area (mm ²)
	A	B	C	E	
48 Pin	9.80	4.40	6.40	0.40	63.00
56 Pin	11.30	4.40	6.40	0.40	72.30
80 Pin	17.00	6.10	8.10	0.40	137.80
100 Pin	20.80	6.10	8.10	0.40	168.50



Double Density Packaging

48-Pin



16.0 x 10.3 x 2.6 mm
pin pitch = 0.635 mm
Area = 164.8 mm²




12.5 x 8.1 x 1.1 mm
pin-pitch = 0.5 mm
Area = 101.3 mm²



9.8 x 6.4 x 1.1 mm
pin-pitch = 0.4 mm
Area = 62.7 mm²

56-Pin



18.4 x 10.3 x 2.6 mm
pin-pitch = 0.635 mm
Area = 189.5 mm²



14.0 x 8.1 x 1.1 mm
pin-pitch = 0.5 mm
Area = 113.4 mm²



11.3 x 6.4 x 1.1 mm
pin-pitch = 0.4 mm
Area = 72.3 mm²

TVSOP	Area (mm ²)	%Smaller Than SSOP	%Smaller Than TSSOP
48 pin	63.00	61.9	38.0
56 pin	72.30	62.2	36.0