
HM51W4265C Series

262,144-word $\times$ 16-bit Dynamic Random Access Memory

HITACHI

ADE-203-477B (Z)

Rev. 2.0

Jul. 10, 1997

Description

The Hitachi HM51W4265C Series is a CMOS dynamic RAM organized as 262,144-word $\times$ 16-bit. HM51W4265C Series has realized higher density, higher performance and various functions by employing 0.8 μ m CMOS process technology and some new CMOS circuit design technologies. The HM51W4265C Series offers Extended Data Out (EDO) Page Mode as a high speed access mode. It is packaged in standard 44-pin plastic TSOPII.


Features

- Single 3.3 V supply: 3.3 V $\pm$ 0.15 V (HM51W4265C-6R)
- 3.3 V $\pm$ 0.3 V (HM51W4265C-6R)
- Access time: 60 ns/70 ns/80 ns (max)
- Power dissipation
 - Active mode: 576 mW/552 mW/468 mW/396 mW (max)
 - Standby mode: 6.9 mW (max) (HM51W4265C-6R)
 - 7.2 mW (max) (HM51W4265C-6/7/8)
 - 0.69 mW (max)(L-version) (HM51W4265CL-6R)
 - 0.72 mW (max) (L-version) (HM51W4265CL-6/7/8)
- EDO page mode capability
- Refresh cycles
 - 512 refresh cycles: 8 ms
 - 128 ms (L-version)
- 3 variations of refresh
 - $\overline{\text{RAS}}$ -only refresh
 - $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh
 - Self refresh
- $2\overline{\text{CAS}}$ -byte control
- Battery backup operation (L-version)

HM51W4265C Series

Ordering Information


Type No.	Access time	Package
HM51W4265CTT-6	60 ns	400-mil 44-pin plastic TSOPII (TTP-44/40DB)
HM51W4265CTT-6R	60 ns	
HM51W4265CTT-7	70 ns	
HM51W4265CTT-8	80 ns	
HM51W4265CLTT-6	60 ns	
HM51W4265CLTT-6R	60 ns	
HM51W4265CLTT-7	70 ns	
HM51W4265CLTT-8	80 ns	

Pin Arrangement

Pin Description

Pin name	Function
A0 to A8	Address input – Row address A0 to A8 – Column address A0 to A8 – Refresh address A0 to A8
I/O0 to I/O15	Data input/output
$\overline{\text{RAS}}$	Row address strobe
$\overline{\text{UCAS}}, \overline{\text{LCAS}}$	Column address strobe
$\overline{\text{WE}}$	Read/write enable
$\overline{\text{OE}}$	Output enable
V _{CC}	Power supply
V _{SS}	Ground
NC	No connection

HM51W4265C Series

Block Diagram



Operation Table

The HM51W4265C series has the following 11 operation modes.

1. Read cycle
2. Early write cycle
3. Delayed write cycle
4. Read-modify-write cycle
5. $\overline{\text{RAS}}$ -only refresh cycle
6. $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle
7. Self refresh cycle
8. EDO page mode read cycle
9. EDO page mode early write cycle
10. EDO page mode delayed write cycle
11. EDO page mode read-modify-write cycle

Inputs

RAS	LCAS	UCAS	WE	OE	Output	Operation
H	H	H	D	D	Open	Standby
H	L	L	H	L	Valid	Standby
L	L	L	H	L	Valid	Read cycle
L	L	L	L^{*2}	D	Open	Early write cycle
L	L	L	L^{*2}	H	Undefined	Delayed write cycle
L	L	L	H to L	L to H	Valid	Read-modify-write cycle
L	H	H	D	D	Open	$\overline{\text{RAS}}$ -only refresh cycle
H to L	H	L	D	D	Open	$\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle
	L	H				Self refresh cycle
	L	L				
L	H to L	H to L	H	L	Valid	EDO page mode read cycle
L	H to L	H to L	L^{*2}	D	Open	EDO page mode early write cycle
L	H to L	H to L	L^{*2}	H	Undefined	EDO page mode delayed write cycle
L	H to L	H to L	H to L	L to H	Valid	EDO page mode read-modify-write cycle
L	L	L	H	H	Open	Read cycle (Output disabled)

Notes: 1. H: High(inactive) L: Low(active) D: H or L (H: $V_{IH}(\min) \leq V_{IN} \leq V_{IH}(\max)$, L: $V_{IL}(\min) \leq V_{IN} \leq V_{IL}(\max)$)

2. $t_{WCS} \geq 0$ ns: Early write cycle
 $t_{WCS} < 0$ ns: Delayed write cycle

3. Mode is determined by the OR function of the $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$. (Mode is set by the earliest of $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$ active edge and reset by the latest of $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$ inactive edge.) However write operation and output High-Z control are done independently by each $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$.

ex. if $\overline{\text{RAS}} = \text{H to L}$, $\overline{\text{LCAS}} = \text{L}$, $\overline{\text{UCAS}} = \text{H}$, then $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle is selected.

HM51W4265C Series

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Voltage on any pin relative to V_{SS}	V_T	−0.5 to +4.6	V
Supply voltage relative to V_{SS}	V_{CC}	−0.5 to +4.6	V
Short circuit output current	I_{out}	50	mA
Power dissipation	P_T	1.0	W
Operating temperature	T_{opr}	0 to +70	°C
Storage temperature	T_{stg}	−55 to +125	°C

Recommended DC Operating Conditions ($T_a = 0$ to +70°C)

Parameter	Symbol	Min	Typ	Max	Unit	Notes
Supply voltage	V_{SS}	0	0	0	V	2
	V_{CC} (HM51W4265C-6R)	3.15	3.3	3.45	V	1, 2
	V_{CC} (HM51W4265C-6/7/8)	3.0	3.3	3.6	V	1, 2
Input high voltage	V_{IH}	2.0	—	$V_{CC} + 0.3$	V	1
Input low voltage	V_{IL}	−0.3	—	0.8	V	1

Notes: 1. All voltage referred to V_{SS} .
 2. The supply voltage with all V_{CC} pins must be on the same level.
 The supply voltage with all V_{SS} pins must be on the same level.

HM51W4265C Series

DC Characteristics

(Ta = 0 to +70°C, V_{CC} = 3.3 V ±0.15 V, V_{SS} = 0 V) (HM51W4265C-6R)*⁵

(Ta = 0 to +70°C, V_{CC} = 3.3 V ±0.3 V, V_{SS} = 0 V) (HM51W4265C-6/7/8) *⁵

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Test conditions
Operating current* ^{1, *2}	I _{CC1}	—	120	—	110	—	95	mA	$\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ cycling t _{RC} = min
Standby current	I _{CC2}	—	2	—	2	—	2	mA	TTL interface $\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ = V _{IH} Dout = High-Z
		—	1	—	1	—	1	mA	CMOS interface $\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$, $\overline{\text{WE}}$, OE ≥ V _{CC} – 0.2 V Dout = High-Z
Standby current (L-version)	I _{CC2}	—	200	—	200	—	200	μA	CMOS interface $\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$, $\overline{\text{WE}}$, OE ≥ V _{CC} – 0.2 V Dout = High-Z
$\overline{\text{RAS}}$ -only refresh current* ²	I _{CC3}	—	120	—	105	—	92	mA	t _{RC} = min
Standby current* ¹	I _{CC5}	—	5	—	5	—	5	mA	$\overline{\text{RAS}}$ = V _{IH} , $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ = V _{IL} Dout = enable
$\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh current* ²	I _{CC6}	—	120	—	105	—	92	mA	t _{RC} = min
EDO page mode current* ^{1, *3}	I _{CC4}	—	160	—	130	—	110	mA	t _{HPC} = min
Battery backup current* ⁴ (Standby with CBR refresh) (L-version)	I _{CC10}	—	200	—	200	—	200	μA	Standby: CMOS interface Dout = High-Z CBR refresh: t _{RC} = 250 μs t _{RAS} ≤ 1 μs, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ = V _{IL} $\overline{\text{WE}}$, OE = V _{IH}
Self-refresh mode current	I _{CC11}	—	1	—	1	—	1	mA	CMOS interface $\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ ≤ 0.2 V Dout = High-Z
Self-refresh mode current (L-version)	I _{CC11}	—	200	—	200	—	200	μA	CMOS interface $\overline{\text{RAS}}$, $\overline{\text{UCAS}}$, $\overline{\text{LCAS}}$ ≤ 0.2 V Dout = High-Z
Input leakage current	I _{LI}	–10	10	–10	10	–10	10	μA	0 V ≤ Vin ≤ 4.6 V
Output leakage current	I _{LO}	–10	10	–10	10	–10	10	μA	0 V ≤ Vout ≤ 4.6 V Dout = disable
Output high voltage	V _{OH}	2.4	V _{CC}	2.4	V _{CC}	2.4	V _{CC}	V	High Iout = –2 mA
Output low voltage	V _{OL}	0	0.4	0	0.4	0	0.4	V	Low Iout = 2 mA

Notes: 1. I_{CC} depends on output load condition when the device is selected. I_{CC} max is specified at the output open condition.

HM51W4265C Series

2. Address can be changed once or less while $\overline{RAS} = V_{IL}$.
3. Address can be changed once or less within one EDO page cycle.
4. $V_{IH} \geq V_{CC} - 0.2 \text{ V}$, $0 \leq V_{IL} \leq 0.2 \text{ V}$, Address can be changed once or less while $\overline{RAS} = V_{IL}$.
5. All the V_{CC} pins should be supplied with the same voltage. And all the V_{SS} pins should be supplied with the same voltage.

Capacitance

($T_a = +25^\circ\text{C}$, $V_{CC} = 3.3 \text{ V} \pm 0.15 \text{ V}$) (HM51W4265C-6R)

($T_a = +25^\circ\text{C}$, $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$) (HM51W4265C-6/7/8)

Parameter	Symbol	Typ	Max	Unit	Notes
Input capacitance (Address)	C_{I1}	—	5	pF	1
Input capacitance (Clocks)	C_{I2}	—	7	pF	1
Output capacitance (Data-in, Data-out)	$C_{I/O}$	—	10	pF	1, 2

Notes: 1. Capacitance measured with Boonton Meter or effective capacitance measuring method.
 2. $\overline{UCAS}$ and $\overline{LCAS} = V_{IH}$ to disable Dout.

AC Characteristics

($T_a = 0 \text{ to } +70^\circ\text{C}$, $V_{CC} = 3.3 \text{ V} \pm 0.15 \text{ V}$, $V_{SS} = 0 \text{ V}$) (HM51W4265C-6R)*1, *14, *15, *17, *18

($T_a = 0 \text{ to } +70^\circ\text{C}$, $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$, $V_{SS} = 0 \text{ V}$) (HM51W4265C-6/7/8)*1, *14, *15, *17, *18

Test Conditions

- Input rise and fall time: 2 ns
- Input levels: $V_{IL} = 0 \text{ V}$, $V_{IH} = 3.0 \text{ V}$
- Input timing reference levels: 0.8 V, 2.0 V
- Output timing reference levels: 0.8 V, 2.0 V
- Output load: 1 TTL gate + C_L (50 pF) (Including scope and jig)

HM51W4265C Series

Read, Write, Read-Modify-Write and Refresh Cycles (Common parameters)

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Random read or write cycle time	t _{RC}	104	—	124	—	144	—	ns	
RAS precharge time	t _{RP}	40	—	50	—	60	—	ns	
RAS pulse width	t _{RAS}	60	10000	70	10000	80	10000	ns	27
CAS pulse width	t _{CAS}	10	10000	13	10000	15	10000	ns	28
Row address setup time	t _{ASR}	0	—	0	—	0	—	ns	
Row address hold time	t _{RAH}	10	—	10	—	10	—	ns	
Column address setup time	t _{ASC}	0	—	0	—	0	—	ns	19
Column address hold time	t _{CAH}	10	—	13	—	15	—	ns	19
RAS to CAS delay time	t _{RCD}	20	45	20	50	20	60	ns	8
RAS to column address delay time	t _{RAD}	15	30	15	35	15	40	ns	9
RAS hold time	t _{RSH}	15	—	18	—	20	—	ns	
CAS hold time	t _{CSH}	48	—	58	—	68	—	ns	29
CAS to RAS precharge time	t _{CRP}	10	—	10	—	10	—	ns	20
OE to Din delay time	t _{ODD}	15	—	18	—	20	—	ns	
OE delay time from Din	t _{DZO}	0	—	0	—	0	—	ns	
CAS setup time from Din	t _{DZC}	0	—	0	—	0	—	ns	
Transition time (rise and fall)	t _T	2	50	2	50	2	50	ns	7
Refresh period	t _{REF}	—	8	—	8	—	8	ms	
Refresh period (L-version)	t _{REF}	—	128	—	128	—	128	ms	

HM51W4265C Series

Read Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Access time from $\overline{\text{RAS}}$	t_{RAC}	—	60	—	70	—	80	ns	2, 3
Access time from $\overline{\text{CAS}}$	t_{CAC}	—	15	—	20	—	20	ns	3, 4, 13
Access time from address	t_{AA}	—	30	—	35	—	40	ns	3, 5, 13
Access time from $\overline{\text{OE}}$	t_{OAC}	—	15	—	20	—	20	ns	3, 23
Read command setup time	t_{RCS}	0	—	0	—	0	—	ns	19
Read command hold time to $\overline{\text{CAS}}$	t_{RCH}	0	—	0	—	0	—	ns	16, 20
Read command hold time to $\overline{\text{RAS}}$	t_{RRH}	0	—	0	—	0	—	ns	16
Column address to $\overline{\text{RAS}}$ lead time	t_{RAL}	30	—	35	—	40	—	ns	
Column address to $\overline{\text{CAS}}$ lead time	t_{CAL}	18	—	23	—	28	—	ns	
Output buffer turn-off time	t_{OFF1}	—	15	—	15	—	15	ns	6, 25
Output buffer turn-off time to $\overline{\text{OE}}$	t_{OFF2}	—	15	—	15	—	15	ns	6
$\overline{\text{CAS}}$ to Din delay time	t_{CDD}	15	—	18	—	20	—	ns	
$\overline{\text{RAS}}$ to Din delay time	t_{RDD}	15	—	18	—	20	—	ns	
$\overline{\text{WE}}$ to Din delay time	t_{WDD}	15	—	18	—	20	—	ns	
$\overline{\text{OE}}$ pulse width	t_{OEP}	15	—	20	—	20	—	ns	23
Turn-off to $\overline{\text{RAS}}$	t_{OFR}	—	15	—	15	—	15	ns	6, 25
Turn-off to $\overline{\text{WE}}$	t_{WEZ}	—	15	—	15	—	15	ns	6
Output data hold time	t_{OH}	5	—	5	—	5	—	ns	25
Output data hold time from $\overline{\text{RAS}}$	t_{OHR}	5	—	5	—	5	—	ns	25
Read command hold time from $\overline{\text{RAS}}$	t_{RCHR}	60	—	70	—	80	—	ns	
Read command hold time from $\overline{\text{CAS}}$	t_{RCHC}	15	—	18	—	20	—	ns	
Read command hold time from column address	t_{RCHA}	30	—	35	—	40	—	ns	

HM51W4265C Series

Write Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Write command setup time	t_{WCS}	0	—	0	—	0	—	ns	10, 19
Write command hold time	t_{WCH}	10	—	13	—	15	—	ns	19
Write command pulse width	t_{WP}	10	—	10	—	10	—	ns	
Write command to $\overline{RAS}$ lead time	t_{RWL}	10	—	13	—	15	—	ns	
Write command to $\overline{CAS}$ lead time	t_{CWL}	10	—	13	—	15	—	ns	21
Data-in setup time	t_{DS}	0	—	0	—	0	—	ns	11, 21
Data-in hold time	t_{DH}	10	—	13	—	15	—	ns	11, 21

Read-Modify-Write Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Read-modify-write cycle time	t_{RWC}	133	—	159	—	183	—	ns	
$\overline{RAS}$ to $\overline{WE}$ delay time	t_{RWD}	77	—	90	—	102	—	ns	10
$\overline{CAS}$ to $\overline{WE}$ delay time	t_{CWD}	32	—	38	—	42	—	ns	10
Column address to $\overline{WE}$ delay time	t_{AWD}	47	—	55	—	62	—	ns	10
$\overline{OE}$ hold time from $\overline{WE}$	t_{OEH}	15	—	18	—	20	—	ns	

Refresh Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
$\overline{CAS}$ setup time (CBR refresh cycle)	t_{CSR}	10	—	10	—	10	—	ns	19
$\overline{CAS}$ hold time (CBR refresh cycle)	t_{CHR}	10	—	10	—	10	—	ns	20
$\overline{RAS}$ precharge to $\overline{CAS}$ hold time	t_{RPC}	10	—	10	—	10	—	ns	19
$\overline{CAS}$ precharge time in normal mode	t_{CPN}	10	—	13	—	15	—	ns	22

HM51W4265C Series

EDO Page Mode Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
EDO page mode cycle time	t _{HPC}	25	—	30	—	35	—	ns	24
EDO page mode $\overline{\text{CAS}}$ precharge time	t _{CP}	10	—	13	—	15	—	ns	22
EDO page mode $\overline{\text{RAS}}$ pulse width	t _{RASC}	—	100000	—	100000	—	100000	ns	12
Access time from $\overline{\text{CAS}}$ precharge	t _{ACP}	—	35	—	40	—	45	ns	3, 13, 20
$\overline{\text{RAS}}$ hold time from $\overline{\text{CAS}}$ precharge	t _{RHCP}	35	—	40	—	45	—	ns	
Output data hold time from $\overline{\text{CAS}}$ low	t _{DOH}	3	—	3	—	3	—	ns	26
$\overline{\text{CAS}}$ hold time referred $\overline{\text{OE}}$	t _{COL}	10	—	13	—	20	—	ns	
$\overline{\text{CAS}}$ to $\overline{\text{OE}}$ setup time	t _{COP}	5	—	5	—	5	—	ns	
Read command hold time from $\overline{\text{CAS}}$ precharge	t _{RCHP}	35	—	40	—	45	—	ns	

EDO Page Mode Read-Modify-Write Cycle

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
EDO page mode read-modify-write cycle time	t _{HPCM}	66	—	77	—	86	—	ns	
EDO page mode read-modify-write cycle CAS precharge to WE delay time	t _{CPW}	52	—	60	—	67	—	ns	10, 20

Self Refresh Mode

		HM51W4265C							
		-6/6R		-7		-8			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
$\overline{\text{RAS}}$ pulse width (self refresh)	t_{RASS}	100	—	100	—	100	—	μs	30, 31, 32, 33
$\overline{\text{RAS}}$ precharge time (self refresh)	t_{RPS}	110	—	130	—	150	—	ns	
$\overline{\text{CAS}}$ hold time (self refresh)	t_{CHS}	−50	—	−50	—	−50	—	ns	21

- Notes:
1. AC measurements assume $t_r = 2 \text{ ns}$.
 2. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}}(\text{max})$ and $t_{\text{RAD}} \leq t_{\text{RAD}}(\text{max})$. If t_{RCD} or t_{RAD} is greater than the maximum recommended value shown in this table, t_{RAC} exceeds the value shown.
 3. Measured with a load circuit equivalent to 1 TTL loads and 50 pF. ($V_{\text{OH}} = 2.0 \text{ V}$, $V_{\text{OL}} = 0.8 \text{ V}$)
 4. Assumes that $t_{\text{RCD}} \geq t_{\text{RCD}}(\text{max})$ and $t_{\text{RAD}} \leq t_{\text{RAD}}(\text{max})$.
 5. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}}(\text{max})$ and $t_{\text{RAD}} \geq t_{\text{RAD}}(\text{max})$.
 6. $t_{\text{OFF1}}(\text{max})$, $t_{\text{OFF2}}(\text{max})$, $t_{\text{OFR}}(\text{max})$ and $t_{\text{WEZ}}(\text{max})$ define the time at which the output achieves the open circuit condition and is not referred to output voltage levels.
 7. $V_{\text{IH}}(\text{min})$ and $V_{\text{IL}}(\text{max})$ are reference levels for measuring timing of input signals. Also, transition times are measured between V_{IH} and V_{IL} .
 8. Operation with the $t_{\text{RCD}}(\text{max})$ limit insures that $t_{\text{RAC}}(\text{max})$ can be met, $t_{\text{RCD}}(\text{max})$ is specified as a reference point only, if t_{RCD} is greater than the specified $t_{\text{RCD}}(\text{max})$ limit, then access time is controlled exclusively by t_{CAC} .
 9. Operation with the $t_{\text{RAD}}(\text{max})$ limit insures that $t_{\text{RAC}}(\text{max})$ can be met, $t_{\text{RAD}}(\text{max})$ is specified as a reference point only, if t_{RAD} is greater than the specified $t_{\text{RAD}}(\text{max})$ limit, then access time is controlled exclusively by t_{AA} .
 10. t_{WCS} , t_{RWD} , t_{CWD} and t_{AWD} are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only: if $t_{\text{WCS}} \geq t_{\text{WCS}}(\text{min})$, the cycle is an early write cycle and the data out pin will remain open circuit (high impedance) throughout the entire cycle; if $t_{\text{RWD}} \geq t_{\text{RWD}}(\text{min})$, $t_{\text{CWD}} \geq t_{\text{CWD}}(\text{min})$, $t_{\text{AWD}} \geq t_{\text{AWD}}(\text{min})$ and $t_{\text{CPW}} \geq t_{\text{CPW}}(\text{min})$, the cycle is a read-modify-write and the data output will contain data read from the selected cell; if neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminate.
 11. These parameters are referred to $\overline{\text{CAS}}$ leading edge in an early write cycle and to $\overline{\text{WE}}$ leading edge in a delayed write or a read-modify-write cycle.
 12. t_{RASC} defines $\overline{\text{RAS}}$ pulse width in EDO mode cycles.
 13. Access time is determined by the longest among t_{AA} , t_{CAC} and t_{ACP} .
 14. An initial pause of 100 μs is required after power up followed by a minimum of eight initialization cycles (RAS-only refresh cycle or $\overline{\text{CAS}}$ -before-RAS refresh cycle). If the internal refresh counter is used, a minimum of eight $\overline{\text{CAS}}$ -before-RAS refresh cycles is required.
 15. In delayed write or read-modify-write cycles, $\overline{\text{OE}}$ must disable output buffer prior to applying data to the device.
 16. Either t_{RCH} or t_{RRH} must be satisfied for a read cycle.
 17. When both $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$ go low at the same time, all 16-bit data are written into the device. $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$ cannot be staggered within the same write/read cycles.
 18. All the V_{CC} and V_{SS} pins shall be supplied with the same voltages.
 19. t_{ASC} , t_{CAH} , t_{RCS} , t_{WCS} , t_{WCH} , t_{CSR} and t_{RPC} are determined by the earlier falling edge of $\overline{\text{UCAS}}$ or $\overline{\text{LCAS}}$.
 20. t_{CRP} , t_{CHR} , t_{ACP} , t_{CPW} and t_{RCH} are determined by the later rising edge of $\overline{\text{UCAS}}$ or $\overline{\text{LCAS}}$.
 21. t_{CWL} , t_{DH} , t_{DS} and t_{CHS} should be satisfied by both $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$.
 22. t_{CPN} and t_{CP} are determined by the time that both $\overline{\text{UCAS}}$ and $\overline{\text{LCAS}}$ are high.


HM51W4265C Series

23. When output buffers are enabled once, sustain the low impedance state until valid data is obtained. When output buffer is turned on and off within a very short time, generally it causes large V_{CC}/V_{SS} line noise, which causes to degrade V_{IH} min/ V_{IL} max level.
24. t_{HPC} (min) can be achieved during a series of EDO page mode early write cycles or EDO page mode read cycles. If both write and read operation are mixed in a EDO page mode $\overline{RAS}$ cycle (EDO page mode mix cycle (1), (2)), minimum value of $\overline{CAS}$ cycle t_{HPC} ($t_{CAS} + t_{CP} + 2t_T$) becomes greater than the specified t_{HPC} (min) value.
25. Data output turns off and becomes high impedance from later rising edge of $\overline{RAS}$ and $\overline{CAS}$. Hold time and turn off time are specified by the timing specifications of later rising edge of $\overline{RAS}$ and $\overline{CAS}$ between t_{OHR} and t_{OH1} , and between t_{OFR} and t_{OFF1} .
26. t_{DOH} defines the time at which the output level satisfied the output timing reference levels. Measured with the test conditions.
27. t_{RAS} (min) = t_{RWD} (min) + t_{RWL} (min) + t_T in read-modify-write cycle.
28. t_{CAS} (min) = t_{CWD} (min) + t_{CWL} (min) + t_T in read-modify-write cycle.
29. t_{CSH} (min) can be achieved when $t_{RCD} \leq t_{CSH}$ (min) - t_{CAS} (min).
30. Please do not use t_{RASS} timing, $10 \mu s \leq t_{RASS} \leq 100 \mu s$. During this period, the device is in transition state from normal operation mode to self refresh mode. If $t_{RASS} \geq 100 \mu s$, then $\overline{RAS}$ precharge time should use t_{RPS} instead of t_{RP} .
31. If you use distributed CBR refresh mode with $15.6 \mu s$ interval in normal read/write cycle, CBR refresh should be executed within $15.6 \mu s$ immediately after exiting from and before entering into self refresh mode.
32. If you use $\overline{RAS}$ only refresh or CBR burst refresh mode in normal read/write cycle, 512 cycles of distributed CBR refresh with $15.6 \mu s$ interval should be executed within 8 ms immediately after exiting from and before entering into the self refresh mode.
33. Repetitive self refresh mode without refreshing all memory is not allowed. Once you exit from self refresh mode, all memory cells need to be refreshed before re-entering the self refresh mode again.
34. XXX: H or L (H: V_{IH} (min) $\leq V_{IN} \leq V_{IH}$ (max), L: V_{IL} (min) $\leq V_{IN} \leq V_{IL}$ (max))
////////: Invalid Dout
When the address, clock and input pins are not described on timing waveforms, their pins must be applied V_{IH} or V_{IL} .


Notes concerning $\overline{2CAS}$ control

Please do not separate the $\overline{UCAS}/\overline{LCAS}$ operation timing intentionally. However skew between $\overline{UCAS}/\overline{LCAS}$ are allowed under the following conditions.

1. Each of the $\overline{UCAS}/\overline{LCAS}$ should satisfy the timing specifications individually.
2. Different operation mode for upper/lower byte is not allowed; such as following.



3. Closely separated upper/lower byte control is not allowed. However when the condition ($t_{CP} \leq t_{UL}$) is satisfied, EDO page mode can be performed.




4. Byte control operation by remaining $\overline{UCAS}$ or $\overline{LCAS}$ high is guaranteed.


HM51W4265C Series

Timing Waveforms*34

Read Cycle




Early Write Cycle




HM51W4265C Series

Delayed Write Cycle




Read-Modify-Write Cycle




HM51W4265C Series

$\overline{\text{RAS}}$ -Only Refresh Cycle




$\overline{\text{CAS}}$ -Before- $\overline{\text{RAS}}$ Refresh Cycle




HM51W4265C Series

EDO Page Mode Read Cycle (t_{HPC} minimum cycle operation)




EDO Page Mode Read Cycle (High-Z control by $\overline{WE}$ and $\overline{OE}$)




HM51W4265C Series

EDO Page Mode Early Write Cycle (t_{HPC} minimum cycle operation)




EDO Page Mode Delayed Write Cycle




HM51W4265C Series


EDO Page Mode Read-Modify-Write Cycle



EDO Page Mode Mix Cycle (1)*24



Self Refresh Cycle*30, 31, 32, 33




HM51W4265C Series

Package Dimensions

HM51W4265CTT/CLTT Series (TTP-44/40DB)

Unit: mm



When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.¹
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. **MEDICAL APPLICATIONS:** Hitachi's products are not authorized for use in MEDICAL APPLICATIONS without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in MEDICAL APPLICATIONS.

HITACHI

Hitachi, Ltd.

Semiconductor & IC Div.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100, Japan
Tel: Tokyo (03) 3270-2111
Fax: (03) 3270-5109

For further information write to:

Hitachi America, Ltd.
Semiconductor & IC Div.
2000 Sierra Point Parkway
Brisbane, CA. 94005-1835
U S A
Tel: 415-589-8300
Fax: 415-583-4207

Hitachi Europe GmbH
Electronic Components Group
Continental Europe
Dornacher Straße 3
D-85622 Feldkirchen
München
Tel: 089-9 91 80-0
Fax: 089-9 29 30 00

Hitachi Europe Ltd.
Electronic Components Div.
Northern Europe Headquarters
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA
United Kingdom
Tel: 0628-585000
Fax: 0628-778322

Hitachi Asia Pte. Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 0104
Tel: 535-2100
Fax: 535-1533

Hitachi Asia (Hong Kong) Ltd.
Unit 706, North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon
Hong Kong
Tel: 27359218
Fax: 27306071

Copyright © Hitachi, Ltd., 1997. All rights reserved. Printed in Japan.

HM51W4265C Series

Revision Record

Rev.	Date	Contents of Modification	Drawn by	Approved by
0.0	Dec. 1, 1995	Initial issue	T. Oono	S. Suzuki
1.0	Jul. 31, 1996	Addition of HM51W4265C-6 Series AC Characteristics Change of note 25, 34 Addition of note 30 Notes concerning $2\overline{\text{CAS}}$ control Addition of note 4 Timing waveforms Deletion of notes about undefined pins. Early write cycle. EDO pagemode early write cycle. $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle. $\overline{\text{RAS}}$ - only refresh cycle. Self refresh cycle.	M. Tsunozaki	S. Suzuki
2.0	Jul. 10, 1997	Correct errors DC Characteristics Test conditions of I_{CC1} , I_{CC5} : $\overline{\text{UCAS}}$ or ... to $\overline{\text{UCAS}}$, ... Addition of note 5 AC Characteristics Correct numbers on tables t_{RPS} max: 130/130/130 ns to 110/130/150 ns Notes concerning $2\overline{\text{CAS}}$ control Addition of description Timing waveforms Change order of waveforms $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle Read-modify-write cycle		