
HD74LVC125

Quad. Bus Buffer Gates with 3-state Outputs

HITACHI

ADE-205-108(Z)

Rev.0

October 1995

Description

The HD74LVC125 has four bus buffer gates in a 14 pin package. The device require the three state control input C to be taken high to put the output into the high impedance condition, whereas the device requires the control input to be low to put the output into high impedance. Low voltage and high speed operation is suitable at the battery drive product (note type personal computer) and low power consumption extends the life of a battery for long time operation.

Features

- $V_{cc} = 2.0 \text{ V to } 5.5 \text{ V}$
- All inputs $V_{ih} (\text{Max.}) = 5.5 \text{ V} (@V_{cc} = 0 \text{ V to } 5.5 \text{ V})$
- Typical V_{ol} ground bounce $< 0.8 \text{ V} (@V_{cc} = 3.3 \text{ V}, T_a = 25^\circ\text{C})$
- Typical V_{oh} undershoot $> 2.0 \text{ V} (@V_{cc} = 3.3 \text{ V}, T_a = 25^\circ\text{C})$
- High output current $\pm 24 \text{ mA} (@V_{cc} = 3.0 \text{ V to } 5.5 \text{ V})$

Function Table

Inputs		Outputs Y
C	A	
H	X	Z
L	L	L
L	H	H

H : High level


L : Low level

X : Immaterial

Z : High impedance

HD74LVC125

Pin Arrangement



Absolute Maximum Ratings

Item	Symbol	Ratings	Unit	Conditions
Supply voltage	V_{CC}	-0.5 to 6.0	V	
Input diode current	I_{IK}	-50	mA	$V_I = -0.5\text{ V}$
Input voltage	V_I	-0.5 to 6.0	V	
Output diode current	I_{OK}	-50	mA	$V_O = -0.5\text{ V}$
		50	mA	$V_O = V_{CC} + 0.5\text{ V}$
Output voltage	V_O	-0.5 to $V_{CC} + 0.5$	V	Output "H" or "L"
Output current	I_O	± 50	mA	
V_{CC} , GND current / pin	I_{CC} or I_{GND}	100	mA	
Storage temperature	T_{stg}	-65 to +150	$^{\circ}\text{C}$	

Note: The absolute maximum ratings are values which must not individually be exceeded, and furthermore, no two of which may be realized at the same time.

Recommended Operating Conditions

Item	Symbol	Ratings	Unit	Conditions
Supply voltage	V_{CC}	1.5 to 5.5	V	Data retention
		2.0 to 5.5	V	At operation
Input / output voltage	V_I	0 to 5.5	V	C, A
	V_O	0 to V_{CC}	V	Output "H" or "L"
Operating temperature	T_a	-40 to 85	°C	
Output current	I_{OH}	-12	mA	$V_{CC} = 2.7\text{ V}$
		-24 ²	mA	$V_{CC} = 3.0\text{ V to }5.5\text{ V}$
	I_{OL}	12	mA	$V_{CC} = 2.7\text{ V}$
		24 ²	mA	$V_{CC} = 3.0\text{ V to }5.5\text{ V}$
Input rise / fall time ^{*1}	t_r, t_f	10	ns/V	

Notes: 1. This item guarantees maximum limit when one input switches.

Waveform : Refer to test circuit of switching characteristics.

2. duty cycle $\leq 50\%$

HD74LVC125


Electrical Characteristics

Item	Symbol	V_{CC} (V)	Ta = -40 to 85°C		Unit	Test Conditions
			Min	Max		
Input voltage	V_{IH}	2.7 to 3.6	2.0	—	V	
		4.5 to 5.5	$V_{CC} \times 0.7$	—	V	
	V_{IL}	2.7 to 3.6	—	0.8	V	
		4.5 to 5.5	—	$V_{CC} \times 0.3$	V	
Output voltage	V_{OH}	2.7 to 5.5	$V_{CC} - 0.2$	—	V	$I_{OH} = -100 \mu A$
		2.7	2.2	—	V	$I_{OH} = -12 \text{ mA}$
		3.0	2.4	—	V	
		3.0	2.0	—	V	$I_{OH} = -24 \text{ mA}$
		4.5	3.8	—	V	
	V_{OL}	2.7 to 5.5	—	0.2	V	$I_{OL} = 100 \mu A$
		2.7	—	0.4	V	$I_{OL} = 12 \text{ mA}$
		3.0	—	0.55	V	$I_{OL} = 24 \text{ mA}$
		4.5	—	0.55	V	
Input current	I_{IN}	0 to 5.5	—	± 5.0	μA	$V_{IN} = 5.5 V_{CC} \text{ GND}$
Quiescent supply current	I_{CC}	2.7 to 5.5	—	10	μA	$V_{IN} = V_{CC} \text{ or GND}$
	ΔI_{CC}	3.0 to 3.6	—	500	μA	$V_{IN} = \text{one input at } (V_{CC} - 0.6)V, \text{ other inputs at } V_{CC} \text{ or GND}$
Off state output current	I_{OZ}	5.5	—	± 10	μA	$V_{IN} = V_{CC}, \text{ GND}$ $V_{OUT} = V_{CC} \text{ or GND}$
Quiescent supply current	I_{CC}	5.5	—	20	μA	$V_{IN} = V_{CC} \text{ or GND}$

Switching Characteristics


Item	Symbol	V_{CC} (V)	$T_a = -40 \text{ to } 85^\circ\text{C}$				Unit	From (Input)	To (Output)
			Min	Typ	Max				
Propagation delay time	t_{PLH}	2.7	—	5.0	7.0	ns	A	Y	
	t_{PHL}	3.3 ± 0.3	1.5	4.0	6.5	ns			
		5.0 ± 0.5	—	3.0	5.0	ns			
Output enable time	t_{ZH}	2.7	—	5.5	8.0	ns	C	Y	
	t_{ZL}	3.3 ± 0.3	1.5	4.0	7.0	ns			
		5.0 ± 0.5	—	3.0	5.5	ns			
Output disable time	t_{HZ}	2.7	—	3.5	6.5	ns	C	Y	
	t_{LZ}	3.3 ± 0.3	1.5	3.0	5.5	ns			
		5.0 ± 0.5	—	2.5	4.5	ns			
Input capacitance	C_{IN}	2.7	—	3.0	—	pF			
Output capacitance	C_O	2.7	—	15.0	—	pF			

Test Circuit



HD74LVC125

Waveforms – 1



Waveforms – 2

