



HD74LS390 • Dual Decade Counters

This circuit contains eight master-slave flip-flops and additional gating to implement two individual four-bit counters. The HD74LS390 incorporates dual divide-by-two and divide-by-five counters, which can be used to implement cycle lengths equal to any whole and/or cumulative multiples of 2 and/or 5 up to divide-by-100. When connected as a bi-quinary counter, the separate divide-by-two circuit can be used to provide symmetry (a square wave) at the final output stage.

PIN ARRANGEMENT



BLOCK DIAGRAM (1/2)



RECOMMENDED OPERATING CONDITIONS

Item	Symbol	min	typ	max	Unit
Output current	I_{OH}	—	—	-400	μA
Output current	I_{OL}	—	—	8	mA
Count frequency	Input A	f_{count}	0	—	25
	Input B		0	—	20
Pulse width	Input A	t_w	20	—	—
	Input B		25	—	—
	Clear		20	—	—
Setup time	t_{su}	25	↓	—	ns

↓: The arrow indicates that the falling edge of the clock pulse is used for reference.

FUNCTION TABLE

BCD Count Sequence (Notes 1)

Count	Outputs			
	Q _D	Q _C	Q _B	Q _A
0	L	L	L	L
1	L	L	L	H
2	L	L	H	L
3	L	L	H	H
4	L	H	L	L
5	L	H	L	H
6	L	H	H	L
7	L	H	H	H
8	H	L	L	L
9	H	L	L	H

Bi-Quinary (Notes 2)

Count	Outputs			
	Q _A	Q _D	Q _C	Q _B
0	L	L	L	L
1	L	L	L	H
2	L	L	H	L
3	L	L	H	H
4	L	H	L	L
5	H	L	L	L
6	H	L	L	H
7	H	L	H	L
8	H	L	H	H
9	H	H	L	L

Notes

- Output Q_A is connected to input B for BCD count.
- Output Q_D is connected to input A for bi-quinary count.
- H: high level, L: low level, X: irrelevant

ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Ratings	Unit
Supply voltage	V_{CC}	7	V
Input voltage	Clear	7	V
	A, B	5.5	V
Operating temperature range	T_{op}	-20 ~ +75	°C
Storage temperature range	T_{stg}	-65 ~ +150	°C

■ ELECTRICAL CHARACTERISTICS ($T_a = -20 \sim +75^\circ\text{C}$)

Item		Symbol	Test Conditions	min	typ*	max	Unit
Input voltage		V_{IH}		2.0	—	—	V
		V_{IL}		—	—	0.8	V
Output voltage		V_{OH}	$V_{CC} = 4.75\text{V}$, $V_{IH} = 2\text{V}$, $V_{IL} = 0.8\text{V}$, $I_{OH} = -400\mu\text{A}$	2.7	—	—	V
		V_{OL}	$V_{CC} = 4.75\text{V}$, $V_{IH} = 2\text{V}$, $V_{IL} = 0.8\text{V}$	$I_{OL} = 4\text{mA}$	—	0.4	V
				$I_{OL} = 8\text{mA}$	—	0.5	
Input current	Clear	I_I	$V_{CC} = 5.25\text{V}$	$V_I = 7\text{V}$	—	0.1	mA
	Input A			$V_I = 5.5\text{V}$	—	0.2	
	Input B				—	0.4	
	Clear	I_{IH}	$V_{CC} = 5.25\text{V}$, $V_I = 2.7\text{V}$		—	20	μA
	Input A				—	100	
	Input B				—	200	
	Clear	I_{IL}	$V_{CC} = 5.25\text{V}$, $V_I = 0.4\text{V}$		—	-0.4	mA
	Input A				—	-1.6	
	Input B				—	-2.4	
Short-circuit output current		I_{OS}	$V_{CC} = 5.25\text{V}$	-20	—	-100	mA
Supply current		I_{CC}^{**}	$V_{CC} = 5.25\text{V}$	—	15	26	mA
Input clamp voltage		V_{IK}	$V_{CC} = 4.75\text{V}$, $I_{IN} = -18\text{mA}$	—	—	-1.5	V

* $V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$

** I_{CC} is measured with all outputs open, both clear inputs grounded following momentary connection to 4.5V, and all other inputs grounded.

■ SWITCHING CHARACTERISTICS ($V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$)


Item	Symbol	Inputs	Outputs	Test Conditions	min	typ	max	Unit
Maximum count frequency	f_{max}	A	Q_A	$C_L=15\text{pF}$, $R_L=2\text{k}\Omega$	25	35	—	MHz
		B	Q_B		20	30	—	
Propagation delay time	t_{PLH}	A	Q_A		—	12	20	ns
	t_{PHL}				—	13	20	
	t_{PLH}	A	Q_C		—	37	60	
	t_{PHL}				—	39	60	
	t_{PLH}	B	Q_B		—	13	21	
	t_{PHL}				—	14	21	
	t_{PLH}	B	Q_C		—	24	39	
	t_{PHL}				—	26	39	
	t_{PLH}	B	Q_D		—	13	21	
	t_{PHL}				—	14	21	
	t_{PLH}	Clear	Any		—	24	39	
	t_{PHL}				—	24	39	

PACKAGING INFORMATION

T-90-20


Factory orders for circuits described in this databook should include a three-part type number as explained in the following example.

HD 74LS00 P




■ Plastic DIP


● 14 Pin




● 16 Pin



● 20 Pin



● 24 Pin




Hitachi America Ltd. • 2210 O'Toole Ave. • San Jose, CA 95131 • (408) 435-8300

T-90-20


PACKAGING INFORMATION

■Cerdip


●14 Pin



●16 Pin



●20 Pin



●24 Pin

