
HD74HC4052/HD74HC4053

Dual 4-channel Analog Multiplexers/Demultiplexers
Triple 2-channel Analog Multiplexers/Demultiplexers

HITACHI

ADE-205-536 (Z)
1st. Edition
Sep. 2000

Description

HD74HC4052: This device connects together the outputs of 4 switches in two sets, thus achieving a pair of 4 channel multiplexers. The binary code placed on the A, and B select lines determine which switch in each 4 channel section is “on”, connecting one of the four inputs in each section to its common output. This enables the implementation of a 4 channel differential multiplexer.

HD74HC4053: This device contains 6 switches whose outputs are connected together in pairs, thus implementing a triple 2 channel multiplexer, or the equivalent of 3 single-pole-double throw configuration. Each of the A, B, or C select lines independently controls one pair of switches, selecting one of the two switches to be “on”.

Features

- High Speed Operation
- Wide Operating Voltage
- Low Quiescent Supply Current

HD74HC4052/HD74HC4053

Function Table


Control Inputs

Inhibit	Select			ON Switch				
	C* ¹	B	A	HD74HC4052		HD74HC4053		
L	L	L	L	Y ₀	X ₀	Z ₀	Y ₀	X ₀
L	L	L	H	Y ₁	X ₁	Z ₀	Y ₀	X ₁
L	L	H	L	Y ₂	X ₂	Z ₀	Y ₁	X ₀
L	L	H	H	Y ₃	X ₃	Z ₀	Y ₁	X ₁
L	H	L	L			Z ₁	Y ₀	X ₀
L	H	L	H			Z ₁	Y ₀	X ₁
L	H	H	L			Z ₁	Y ₁	X ₀
L	H	H	H			Z ₁	Y ₁	X ₁
H	X	X	X	—		—		

Note: 1. Not applicable for HD74HC4052
X = Don't Care


Pin Arrangement

HD74HC4052




(Top view)

HD74HC4053




Block Diagram

HD74HC4052



HD74HC4053



Absolute Maximum Ratings

Item	Symbol	Rating	Unit
Supply voltage	V_{CC}	-0.5 to +7.0	V
	$V_{CC} - V_{EE}$	-0.5 to +7.0	V
Control input voltage	V_{IN}	GND - 0.5 to $V_{CC} + 0.5$	V
Switch I/O voltage	$V_{I/O}$	$V_{EE} - 0.5$ to $V_{CC} + 0.5$	V
Supply current	(V_{CC}) I_{CC}	+50	mA
	(GND) I_{GND}	-50	mA
Switch I/O current (per pin)	$I_{I/O}$	±25	mA
Control input diode current	I_{IK}	±20	mA
Switch I/O diode current	I_{IOK}	±20	mA
Power dissipation	P_T	500	mW
Storage temperature range	Tstg	-65 to +150	°C

Recommended Operating Range

Item		Symbol	Min	Typ	Max	Unit
Supply voltage		$V_{CC} - V_{EE}$	2	—	6	V
		$GND - V_{EE}$	−4	—	0	V
Control input voltage		V_{IN}	0	—	V_{CC}	V
Switch I/O voltage		$V_{I/O}$	V_{EE}	—	V_{CC}	V
Operating temperature		T_{opr}	−40	—	+85	°C
Input rise/fall time	$V_{CC} = 2.0\text{ V}$	t_r, t_f	0	—	1000	ns
	$V_{CC} = 4.5\text{ V}$		0	—	500	ns
	$V_{CC} = 6.0\text{ V}$		0	—	400	ns

HD74HC4052/HD74HC4053

DC Characteristics (V_{EE} = GND)

Item	Symbol	V _{CC} (V)	Ta = 25°C			Ta = −40 to +85°C		Unit	Test Conditions
			Min	Typ	Max	Min	Max		
Control input voltage	V _{IH}	2.0	1.5	—	—	1.5	—	V	
		4.5	3.15	—	—	3.15	—		
		6.0	4.2	—	—	4.2	—		
	V _{IL}	2.0	—	—	0.5	—	0.5	V	
		4.5	—	—	1.35	—	1.35		
		6.0	—	—	1.8	—	1.8		
ON resistance	R _{ON}	2.0	—	2000	5000	—	6250	Ω	V _{INH} = V _{IL}
		4.5	—	120	180	—	225		V _{I/O} = V _{CC} to V _{EE}
		6.0	—	100	170	—	210		I _{I/O} ≤ 2 mA
		2.0	—	200	800	—	1000	Ω	V _{INH} = V _{IL}
		4.5	—	80	150	—	190		V _{I/O} = V _{CC} to V _{EE}
		6.0	—	70	140	—	175		V _{I/O} ≤ 2 mA
ΔON resistance between any two channels	ΔR _{ON}	2.0	—	50	—	—	—	Ω	V _{INH} = V _{IL}
		4.5	—	13	40	—	50		V _{I/O} = V _{CC} to V _{EE}
		6.0	—	10	20	—	25		I _{I/O} ≤ 2 mA
OFF channel leakage current (switch off)	I _{S (OFF)}	6.0	—	—	±0.1	—	±1.0	μA	V _{INH} = V _{IL}
OFF channel leakage current (switch on)	I _{S (ON)}	6.0	—	—	±0.1	—	±1.0	μA	V _{INH} = V _{IL}
Control input current	I _{in}	6.0	—	—	±0.1	—	±1.0	μA	V _{in} = V _{CC} or GND
Quiescent supply current	I _{CC}	6.0	—	—	4.0	—	40	μA	V _{in} = V _{CC} or GND

AC Characteristics ($C_L = 50 \text{ pF}$, Input $t_r = t_f = 6 \text{ ns}$, $V_{EE} = \text{GND}$)


Item	Symbol	$V_{CC} \text{ (V)}$	$T_a = 25^\circ\text{C}$			$T_a = -40 \text{ to } +85^\circ\text{C}$		Unit	Test Conditions
			Min	Typ	Max	Min	Max		
Propagation delay time	t_{PLH}	2.0	—	25	60	—	75	ns	$R_L = 10 \text{ k}\Omega$
		4.5	—	6	12	—	15		Switch input to
		6.0	—	5	10	—	13		switch output
	t_{PHL}	2.0	—	25	60	—	75	ns	
		4.5	—	6	12	—	15		
		6.0	—	5	10	—	13		
Propagation delay time	t_{PLH}	2.0	—	50	153	—	191	ns	$R_L = 10 \text{ k}\Omega$
		4.5	—	16	30	—	38		Control input to
		6.0	—	14	26	—	33		switch output
	t_{PHL}	2.0	—	50	153	—	191	ns	
		4.5	—	16	30	—	38		
		6.0	—	14	26	—	33		
Output enable time	t_{ZH}	2.0	—	50	153	—	191	ns	$R_L = 1 \text{ k}\Omega$
		4.5	—	14	30	—	38		
		6.0	—	12	26	—	33		
	t_{ZL}	2.0	—	50	153	—	191	ns	
		4.5	—	14	30	—	38		
		6.0	—	12	26	—	33		
Output disable time	t_{HZ}	2.0	—	40	153	—	191	ns	$R_L = 1 \text{ k}\Omega$
		4.5	—	17	30	—	38		
		6.0	—	14	26	—	33		
	t_{LZ}	2.0	—	40	153	—	191	ns	
		4.5	—	17	30	—	38		
		6.0	—	14	26	—	33		
Control input capacitance	C_{in}	—	—	5	10	—	10	pF	
Switch input capacitance	C_{in}	5.0	—	5	—	—	—	pF	
Output capacitance (Common pin)	C_{out}	5.0	—	12	—	—	—	pF	HD74HC4052
		5.0	—	6	—	—	—		HD74HC4053
Feed through capacitance	C_{in-out}	5.0	—	0.6	—	—	—	pF	HD74HC4052
		5.0	—	0.5	—	—	—		HD74HC4053

AC Characteristics (C_L = 50 pF, Input t_r = t_f = 6 ns, V_{EE} = GND) (cont)


Item	Symbol	V _{CC} (V)	Ta = 25°C			Ta = -40 to +85°C		Unit	Test Conditions
			Min	Typ	Max	Min	Max		
Power dissipation	C _{PD}	5.0	—	32.0	—	—	—	pF	HD74HC4052
capacitance		5.0	—	17.0	—	—	—		HD74HC4053
Sine wave distortion		4.5	—	0.1	—	—	—	%	f _{in} = 1 kHz, V _{in} = 4 V _{P-P} R _L = 10 kΩ, C _L = 50 pF
Frequency response channel “ON” (Sine wave input)		4.5	—	95	—	—	—	MHz	f _{in} = 1 MHz, 20 log ₁₀ V _{OS} /V _{IS} = -3 dB R _L = 50 Ω, C _L = 10 pF
Feed through attenuation		4.5	—	-50	—	—	—	dB	R _L = 600 Ω, C _L = 50 pF, f _{in} = 1 MHz
Cross talk between control input and switch I/O		2.0	—	25	—	—	—	mV	R _L = 600 Ω, C _L = 15 pF, f _{in} = 1 MHz
		4.5	—	50	—	—	—		
		6.0	—	75	—	—	—		
Cross talk between any two switches		4.5	—	-50	—	—	—	dB	R _L = 600 Ω, C _L = 50 pF, f _{in} = 1 MHz
Maximum control frequency		2.0	—	20	—	—	—	MHz	R _L = 1 kΩ, C _L = 15 pF V _{out} = 1/2 (V _{CC})
		4.5	—	30	—	—	—		
		6.0	—	30	—	—	—		

AC Characteristics Test Circuit


Maximum Control Frequency




Cross talk (Between Any Two Switches)




Cross talk (Control Input to Switch Output)




Feed through Attenuation




Sine Wave Distortion




Cin, Cout, Cin-out (Input, Output and Feed through Capacitance)




Frequency Response Channel ON




R_{ON} : ON Resistance



I_s (OFF): OFF Channel Leakage Current (Switch OFF)




I_s (ON): OFF Channel Leakage Current (Switch ON)




HD74HC4052/HD74HC4053


t_{PLH} , t_{PHL} : Propagation Delay Time (Switch Input to Switch Output)



t_{PLH} , t_{PHL} : Propagation Delay Time (Control Input to Switch Output)




t_{ZH} , t_{ZL}/t_{HZ} , t_{LZ} : Output Enable and Disable Time




Package Dimensions

Unit: mm



Hitachi Code	DP-16
JEDEC	Conforms
EIAJ	Conforms
Mass (reference value)	1.07 g


Unit: mm



Hitachi Code	FP-16DA
JEDEC	—
EIAJ	Conforms
Mass (reference value)	0.24 g

*Dimension including the plating thickness
Base material dimension

Unit: mm



*Dimension including the plating thickness
Base material dimension

Hitachi Code	FP-16DN
JEDEC	Conforms
EIAJ	Conforms
Mass (reference value)	0.15 g

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohite-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL	North America	: http://semiconductor.hitachi.com/
	Europe	: http://www.hitachi-eu.com/hel/ecg
	Asia	: http://sicapac.hitachi-asia.com
	Japan	: http://www.hitachi.co.jp/Sicd/indx.htm

For further information write to:

Hitachi Semiconductor (America) Inc. 179 East Tasman Drive, San Jose, CA 95134 Tel: <1> (408) 433-1990 Fax: <1> (408) 433-0223	Hitachi Europe GmbH Electronic Components Group Dornacher Straße 3 D-85622 Feldkirchen, Munich Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00
	Hitachi Europe Ltd. Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 585160

Hitachi Asia Ltd. Hitachi Tower 16 Collyer Quay #20-00, Singapore 049318 Tel: <65>-538-6533/538-8577 Fax: <65>-538-6933/538-3877 URL: http://www.hitachi.com.sg	Hitachi Asia Ltd. (Taipei Branch Office) 4/F, No. 167, Tun Hwa North Road, Hung-Kuo Building, Taipei (105), Taiwan Tel: <886>-(2)-2718-3666 Fax: <886>-(2)-2718-8180 Telex: 23222 HAS-TP URL: http://www.hitachi.com.tw
---	---

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower,
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon,
Hong Kong
Tel: <852>-(2)-735-9218
Fax: <852>-(2)-730-0281
URL: <http://www.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 2.0

HITACHI