

# HD74AC166/HD74ACT166

## 8-bit Shift Register

# HITACHI

ADE-205-375 (Z)  
1st. Edition  
Sep. 2000


### Description

The HD74AC166/HD74ACT166 is an 8-bit, serial or parallel-in, serial-out shift register using edge triggered D-type flip-flops. Serial and parallel entry are synchronous, with state changes initiated by the rising edge of the clock. An asynchronous Master Reset overrides other inputs and clears all flip-flops. The circuit can be clocked from two sources or one CP input can be used to trigger the other.


### Features

- Outputs Source/Sink 24 mA
- HD74ACT166 has TTL-Compatible Inputs

### Pin Arrangement



Logic Symbol



Pin Names

- CP<sub>1</sub>, CP<sub>2</sub> Clock Pulse Inputs (Active Rising Edge)
- D<sub>s</sub> Serial Data Input
- $\overline{PE}$  Parallel Enable Input (Active Low)
- P<sub>0</sub> to P<sub>7</sub> Parallel Data Inputs
- $\overline{MR}$  Asynchronous Master Reset Input (Active Low)
- Q<sub>7</sub> Last Stage Output

Functional Description


Operation is synchronous (except for Master Reset) and state changes are initiated by the rising edge of either clock input if the other clock input is Low. When one of the clock inputs is used as an active High clock inhibit, it should attain the High state while the other clock is still in the High state following the previous operation. When the Parallel Enable ( $\overline{PE}$ ) input is Low, data is loaded into the register from the Parallel Data (P<sub>0</sub> to P<sub>7</sub>) inputs on the next rising edge of the clock. When  $\overline{PE}$  is High, information is shifted from the Serial Data (D<sub>s</sub>) input to Q<sub>0</sub> and all data in the register is shifted one bit position (i.e., Q<sub>0</sub> → Q<sub>1</sub>, Q<sub>1</sub> → Q<sub>2</sub>, etc.) on the rising edge of the clock.

Truth Table

| Inputs          |                 |        |          |       | Parallel       | Internal Outputs |          | Output   |
|-----------------|-----------------|--------|----------|-------|----------------|------------------|----------|----------|
| $\overline{MR}$ | $\overline{PE}$ | $CP_2$ | $CP_1$   | $D_S$ | $P_0$ to $P_7$ | $Q_0$            | $Q_6$    | $Q_7$    |
| L               | X               | X      | X        | X     | X              | L                | L        | L        |
| H               | X               | L      | L        | X     | X              | $Q_{A0}$         | $Q_{B0}$ | $Q_{H0}$ |
| H               | L               | L      | $\lceil$ | X     | $a \cdots h$   | $a$              | $b$      | $h$      |
| H               | H               | L      | $\lceil$ | H     | X              | H                | $Q_{An}$ | $Q_{Gn}$ |
| H               | H               | L      | $\lceil$ | L     | X              | L                | $Q_{An}$ | $Q_{Gn}$ |
| H               | X               | H      | $\lceil$ | X     | X              | $Q_{A0}$         | $Q_{B0}$ | $Q_{H0}$ |

H : High Voltage Level  
L : Low Voltage Level  
X : Immaterial  
 $\lceil$  : Low-to-High Clock Transition

Logic Diagram



HD74AC166/HD74ACT166

DC Characteristics (unless otherwise specified)

| Item                                                   | Symbol           | Max | Unit | Condition                                                                             |
|--------------------------------------------------------|------------------|-----|------|---------------------------------------------------------------------------------------|
| Maximum quiescent supply current                       | I <sub>CC</sub>  | 80  | μA   | V <sub>IN</sub> = V <sub>CC</sub> or ground, V <sub>CC</sub> = 5.5 V, Ta = Worst case |
| Maximum quiescent supply current                       | I <sub>CC</sub>  | 8.0 | μA   | V <sub>IN</sub> = V <sub>CC</sub> or ground, V <sub>CC</sub> = 5.5 V, Ta = 25°C       |
| Maximum additional I <sub>CC</sub> /input (HD74ACT166) | I <sub>CCT</sub> | 1.5 | mA   | V <sub>IN</sub> = V <sub>CC</sub> – 2.1 V, V <sub>CC</sub> = 5.5 V, Ta = Worst case   |

AC Characteristics: HD74AC166

| Item                                                                   | Symbol           | V <sub>CC</sub> (V)*1 | Ta = +25°C<br>C <sub>L</sub> = 50 pF |      |      | Ta = –40°C to +85°C<br>C <sub>L</sub> = 50 pF |      | Unit |
|------------------------------------------------------------------------|------------------|-----------------------|--------------------------------------|------|------|-----------------------------------------------|------|------|
|                                                                        |                  |                       | Min                                  | Typ  | Max  | Min                                           | Max  |      |
| Maximum clock frequency                                                | f <sub>max</sub> | 3.3                   | 75                                   | —    | —    | 65                                            | —    | MHz  |
|                                                                        |                  | 5.0                   | 100                                  | —    | —    | 80                                            | —    |      |
| Propagation delay CP <sub>1</sub> or CP <sub>2</sub> to Q <sub>7</sub> | t <sub>PLH</sub> | 3.3                   | 1.0                                  | 11.0 | 14.5 | 1.0                                           | 15.5 | ns   |
|                                                                        |                  | 5.0                   | 1.0                                  | 9.5  | 11.5 | 1.0                                           | 12.5 |      |
| Propagation delay CP <sub>1</sub> or CP <sub>2</sub> to Q <sub>7</sub> | t <sub>PHL</sub> | 3.3                   | 1.0                                  | 10.5 | 14.0 | 1.0                                           | 15.0 |      |
|                                                                        |                  | 5.0                   | 1.0                                  | 9.0  | 11.0 | 1.0                                           | 12.0 |      |
| Propagation delay $\overline{MR}$ to Q <sub>7</sub>                    | t <sub>PHL</sub> | 3.3                   | 1.0                                  | 9.5  | 12.0 | 1.0                                           | 13.0 |      |
|                                                                        |                  | 5.0                   | 1.0                                  | 6.5  | 9.0  | 1.0                                           | 10.0 |      |

Note: 1. Voltage Range 3.3 is 3.3 V ± 0.3 V  
Voltage Range 5.0 is 5.0 V ± 0.5 V

## AC Operating Requirements: HD74AC166

| Item                                                                   | Symbol           | $V_{CC}$ (V)* <sup>1</sup> | Ta = +25°C<br>C <sub>L</sub> = 50 pF |                    | Ta = -40°C to +85°C<br>C <sub>L</sub> = 50 pF |  | Unit |
|------------------------------------------------------------------------|------------------|----------------------------|--------------------------------------|--------------------|-----------------------------------------------|--|------|
|                                                                        |                  |                            | Typ                                  | Guaranteed Minimum |                                               |  |      |
| Setup time                                                             | t <sub>su</sub>  | 3.3                        | 3.0                                  | 5.5                | 6.0                                           |  | ns   |
| $\overline{PE}$ or P <sub>n</sub> or D <sub>S</sub> to CP <sub>n</sub> |                  | 5.0                        | 2.0                                  | 4.0                | 4.5                                           |  |      |
| Hold time                                                              | t <sub>h</sub>   | 3.3                        | -1.5                                 | 3.0                | 3.0                                           |  |      |
| CP <sub>n</sub> to $\overline{PE}$ or P <sub>n</sub> or D <sub>S</sub> |                  | 5.0                        | -0.5                                 | 3.0                | 3.0                                           |  |      |
| Pulse width                                                            | t <sub>w</sub>   | 3.3                        | 2.0                                  | 5.5                | 7.0                                           |  |      |
| CP <sub>n</sub> or $\overline{MR}$                                     |                  | 5.0                        | 2.0                                  | 4.5                | 5.0                                           |  |      |
| Recovery time                                                          | t <sub>rec</sub> | 3.3                        | -2.5                                 | 0.0                | 0.0                                           |  |      |
| $\overline{MR}$ to CP <sub>n</sub>                                     |                  | 5.0                        | -1.5                                 | 0.0                | 0.0                                           |  |      |

Note: 1. Voltage Range 3.3 is 3.3 V ± 0.3 V  
Voltage Range 5.0 is 5.0 V ± 0.5 V

## AC Characteristics: HD74ACT166

| Item                                                   | Symbol           | $V_{CC}$ (V)* <sup>1</sup> | Ta = +25°C<br>C <sub>L</sub> = 50 pF |      |      | Ta = -40°C to +85°C<br>C <sub>L</sub> = 50 pF |      | Unit |
|--------------------------------------------------------|------------------|----------------------------|--------------------------------------|------|------|-----------------------------------------------|------|------|
|                                                        |                  |                            | Min                                  | Typ  | Max  | Min                                           | Max  |      |
| Maximum clock frequency                                | f <sub>max</sub> | 5.0                        | 100                                  | —    | —    | 80                                            | —    | MHz  |
| Propagation delay<br>CP <sub>n</sub> to Q <sub>7</sub> | t <sub>PLH</sub> | 5.0                        | 1.0                                  | 10.0 | 12.5 | 1.0                                           | 13.5 | ns   |
| Propagation delay<br>CP <sub>n</sub> to Q <sub>7</sub> | t <sub>PHL</sub> | 5.0                        | 1.0                                  | 9.5  | 12.0 | 1.0                                           | 13.0 |      |
| Propagation delay<br>$\overline{MR}$ to Q <sub>7</sub> | t <sub>PHL</sub> | 5.0                        | 1.0                                  | 8.5  | 11.0 | 1.0                                           | 12.0 |      |

Note: 1. Voltage Range 5.0 is 5.0 V ± 0.5 V

AC Operating Requirements: HD74ACT166

| Item                                                                    | Symbol           | V <sub>CC</sub> (V)*1 | Ta = +25°C             | Ta = −40°C |                        | Unit |
|-------------------------------------------------------------------------|------------------|-----------------------|------------------------|------------|------------------------|------|
|                                                                         |                  |                       | C <sub>L</sub> = 50 pF | to +85°C   | C <sub>L</sub> = 50 pF |      |
| Setup time<br>PE or P <sub>n</sub> or D <sub>S</sub> to CP <sub>n</sub> | t <sub>su</sub>  | 5.0                   | 2.5                    | 7.0        | 8.0                    | ns   |
| Hold time<br>CP <sub>n</sub> to PE or P <sub>n</sub> or D <sub>S</sub>  | t <sub>h</sub>   | 5.0                   | 0.0                    | 1.5        | 1.5                    |      |
| Pulse width CP <sub>n</sub> or MR                                       | t <sub>w</sub>   | 5.0                   | 4.5                    | 7.0        | 8.0                    |      |
| Recovery time MR to CP <sub>n</sub>                                     | t <sub>rec</sub> | 5.0                   | −2.5                   | 0.5        | 0.5                    |      |


Note: 1. Voltage Range 5.0 is 5.0 V ± 0.5 V

Capacitance

| Item                          | Symbol          | Typ  | Unit | Condition               |
|-------------------------------|-----------------|------|------|-------------------------|
| Input capacitance             | C <sub>IN</sub> | 4.5  | pF   | V <sub>CC</sub> = 5.5 V |
| Power dissipation capacitance | C <sub>PD</sub> | 35.0 | pF   | V <sub>CC</sub> = 5.0 V |


Package Dimensions

Unit: mm



|                        |          |
|------------------------|----------|
| Hitachi Code           | DP-16    |
| JEDEC                  | Conforms |
| EIAJ                   | Conforms |
| Mass (reference value) | 1.07 g   |


Unit: mm



\*Dimension including the plating thickness  
Base material dimension

|                        |          |
|------------------------|----------|
| Hitachi Code           | FP-16DA  |
| JEDEC                  | —        |
| EIAJ                   | Conforms |
| Mass (reference value) | 0.24 g   |


Unit: mm



\*Dimension including the plating thickness  
Base material dimension

|                        |          |
|------------------------|----------|
| Hitachi Code           | FP-16DN  |
| JEDEC                  | Conforms |
| EIAJ                   | Conforms |
| Mass (reference value) | 0.15 g   |

Unit: mm



\*Dimension including the plating thickness  
Base material dimension

|                        |          |
|------------------------|----------|
| Hitachi Code           | TTP-16DA |
| JEDEC                  | —        |
| EIAJ                   | —        |
| Mass (reference value) | 0.05 g   |

## Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

# HITACHI

## Hitachi, Ltd.

Semiconductor & Integrated Circuits.  
Nippon Bldg., 2-6-2, Ohite-machi, Chiyoda-ku, Tokyo 100-0004, Japan  
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

|     |               |   |                                                                                             |
|-----|---------------|---|---------------------------------------------------------------------------------------------|
| URL | North America | : | <a href="http://semiconductor.hitachi.com/">http://semiconductor.hitachi.com/</a>           |
|     | Europe        | : | <a href="http://www.hitachi-eu.com/hel/ecg">http://www.hitachi-eu.com/hel/ecg</a>           |
|     | Asia          | : | <a href="http://sicapac.hitachi-asia.com">http://sicapac.hitachi-asia.com</a>               |
|     | Japan         | : | <a href="http://www.hitachi.co.jp/Sicd/indx.htm">http://www.hitachi.co.jp/Sicd/indx.htm</a> |

### For further information write to:

|                                                                                                                                            |                                                                                                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hitachi Semiconductor (America) Inc.<br>179 East Tasman Drive,<br>San Jose, CA 95134<br>Tel: <1> (408) 433-1990<br>Fax: <1> (408) 433-0223 | Hitachi Europe GmbH<br>Electronic Components Group<br>Dornacher Straße 3<br>D-85622 Feldkirchen, Munich<br>Germany<br>Tel: <49> (89) 9 9180-0<br>Fax: <49> (89) 9 29 30 00                            |
|                                                                                                                                            | Hitachi Europe Ltd.<br>Electronic Components Group.<br>Whitebrook Park<br>Lower Cookham Road<br>Maidenhead<br>Berkshire SL6 8YA, United Kingdom<br>Tel: <44> (1628) 585000<br>Fax: <44> (1628) 585160 |

|                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hitachi Asia Ltd.<br>Hitachi Tower<br>16 Collyer Quay #20-00,<br>Singapore 049318<br>Tel: <65>-538-6533/538-8577<br>Fax: <65>-538-6933/538-3877<br>URL: <a href="http://www.hitachi.com.sg">http://www.hitachi.com.sg</a> | Hitachi Asia Ltd.<br>(Taipei Branch Office)<br>4/F, No. 167, Tun Hwa North Road,<br>Hung-Kuo Building,<br>Taipei (105), Taiwan<br>Tel: <886>-(2)-2718-3666<br>Fax: <886>-(2)-2718-8180<br>Telex: 23222 HAS-TP<br>URL: <a href="http://www.hitachi.com.tw">http://www.hitachi.com.tw</a> |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Hitachi Asia (Hong Kong) Ltd.  
Group III (Electronic Components)  
7/F., North Tower,  
World Finance Centre,  
Harbour City, Canton Road  
Tsim Sha Tsui, Kowloon,  
Hong Kong  
Tel: <852>-(2)-735-9218  
Fax: <852>-(2)-730-0281  
URL: <http://www.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.  
Colophon 2.0

## HITACHI