

Thyristor triggers - SIDAC.

The plastic material carries U/L recognition 94 V-O.

TYPE	Repetitive Peak Off-State Voltage	Breakover Voltage (60 Hz Sine Wave)		On-State RMS Current Conduction Angle of 360°	Peak Surge (Non-Repetitive) On-State Current One-cycle @ 60 Hz	Repetitive Peak Off-State Current @ 60 Hz, V=V _{DRM}	Dynamic Holding Current R=0.1KΩ, 60Hz	Breakover Current 60 Hz Sine Wave
	V _{DRM}	V _{BO(Min.)}	V _{BO(Max.)}	I _{T(RMS)}	I _{TSM}	I _{DRM}	I _{HO}	I _{BO}
	Volt	Volt	Volt	Amp.	Amp.	μA	mA	μA

G105 Series. SIDAC. Case: DO-41. Outline: 2

G105	± 90	95	113	1.0	20	10	100	200
G120	± 90	110	125	1.0	20	10	100	200
G130	± 90	120	135	1.0	20	10	100	200
G220	± 180	205	230	1.0	20	10	100	200
G240	± 180	220	250	1.0	20	10	100	200
G260	± 180	240	270	1.0	20	10	100	200
G270	± 180	250	280	1.0	20	10	100	200