

Hex 2-input NAND drivers

74F804/1804

FEATURES

- High capacitive drive capability
- Choice of configuration
Corner V_{CC} and GND – 74F804
Center V_{CC} and GND – 74F1804
- Typical propagation delay of 2.5ns

TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT (TOTAL)
74F804	2.5ns	9mA
74F1804	2.5ns	9mA

ORDERING INFORMATION


DESCRIPTION	ORDER CODE
	COMMERCIAL RANGE $V_{CC} = 5V \pm 10\%$, $T_{amb} = 0^\circ C$ to $+70^\circ C$
20-pin plastic DIP	N74F804N, N74F1804N
20-pin plastic SOL	N74F804D, N74F1804D

INPUT AND OUTPUT LOADING AND FAN OUT TABLE


PINS	DESCRIPTION	74F (U.L.) HIGH/LOW	LOAD VALUE HIGH/LOW
D _{na} – D _{nb}	Data inputs	1.0/0.033	20 μ A/20 μ A
Q ₀ – Q ₅	Data outputs	2400/80	48mA/48mA

NOTE: One (1.0) FAST unit load is defined as: 20 μ A in the high state and 0.6mA in the low state.


PIN CONFIGURATION




LOGIC SYMBOL




IEC/IEEE SYMBOL




PIN CONFIGURATION



LOGIC SYMBOL




IEC/IEEE SYMBOL



Hex 2-input NAND drivers

74F804/1804

LOGIC DIAGRAM



FUNCTION TABLE

INPUTS		OUTPUT
D_a	D_b	Q̄
H	H	L
L	X	H
X	L	H

NOTES:

2. H = High voltage level
 3. L = Low voltage level
 4. X = Don't care

ABSOLUTE MAXIMUM RATINGS

(Operation beyond the limit set forth in this table may impair the useful life of the device. Unless otherwise noted these limits are over the operating free air temperature range.)

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	-0.5 to +7.0	V
V_{IN}	Input voltage	-0.5 to +7.0	V
I_{IN}	Input current	-30 to +5	mA
V_{OUT}	Voltage applied to output in high output state	-0.5 to V_{CC}	V
I_{OUT}	Current applied to output in low output state	96	mA
T_{amb}	Operating free-air temperature range	0 to +70	°C
T_{stg}	Storage temperature range	-65 to +150	°C

RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5.0	5.5	V
V_{IH}	High-level input voltage	2.0			V
V_{IL}	Low-level input voltage			0.8	V
I_{ik}	Input clamp current			-18	mA
I_{OH}	High-level output current			-48	mA
I_{OL}	Low-level output current			48	mA
T_{amb}	Operating free air temperature range	0		+70	°C

Hex 2-input NAND drivers

74F804/1804

DC ELECTRICAL CHARACTERISTICS

(Over recommended operating free-air temperature range unless otherwise noted.)

SYMBOL	PARAMETER	TEST CONDITIONS ¹	LIMITS			UNIT
			MIN	TYP ²	MAX	
V_{OH}	High-level output voltage	$V_{CC} = \text{MIN}, V_L = \text{MAX}$	$\pm 10\%V_{CC}$	2.0		V
		$V_{IH} = \text{MIN}, I_{OH} = \text{MAX}$	$\pm 5\%V_{CC}$	2.0		
V_{OL}	Low-level output voltage	$V_{CC} = \text{MIN}, V_L = \text{MAX}$	$\pm 10\%V_{CC}$	0.38	0.55	V
		$V_{IH} = \text{MIN}, I_{OL} = \text{MAX}$	$\pm 5\%V_{CC}$	0.38	0.55	
V_{IK}	Input clamp voltage	$V_{CC} = \text{MIN}, I_I = I_{IK}$		-0.73	-1.2	V
I_I	Input current at maximum input voltage	$V_{CC} = \text{MAX}, V_I = 7.0V$			100	μA
I_{IH}	High-level input current	$V_{CC} = \text{MAX}, V_I = 2.7V$			20	μA
I_{IL}	Low-level input current	$V_{CC} = \text{MAX}, V_I = 0.5V$			-20	μA
I_O	Output current ³	$V_{CC} = \text{MAX}$		-60		-160 mA
I_{CC}	Supply current (total)	I_{CCH}	$V_{CC} = \text{MAX}$	$V_{IN} = \text{GND}$	2.0	3.0 mA
		I_{CCL}	$V_{CC} = \text{MAX}$	$V_{IN} = 4.5V$	15	20 mA

NOTES:

1. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
2. All typical values are at $V_{CC} = 5V$, $T_{amb} = 25^\circ C$.
3. The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

AC ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER	TEST CONDITION	LIMITS						UNIT	
			$T_{amb} = +25^\circ C$			$T_{amb} = 0^\circ C \text{ to } +70^\circ C$				
			$V_{CC} = +5.0V$	$C_L = 50pF$	$R_L = 500\Omega$	$V_{CC} = +5.0V \pm 10\%$	$C_L = 50pF$	$R_L = 500\Omega$		
t_{PLH}	Propagation delay $D_{nA}, D_{nb} \text{ to } Q_n$	Waveform 1	1.0 1.0	2.0 3.0	4.0 4.5	1.0 1.0	4.0 5.0	ns		
t_{PHL}										
$t_{sk(o)}$	Output skew ^{1,2}	Waveform 2			1.5		1.5	ns		


NOTES:

1. [t_{PN} actual – t_{PM} actual] for any output compared to any other output where N and M are either LH or HL.
2. Skew times are valid only under same test conditions (temperature, V_{CC} , loading, etc.).


Hex 2-input NAND drivers

74F804/1804

AC WAVEFORMS




Waveform 1. Propagation delay for inverting outputs




Waveform 2. Output skew

NOTE: For all waveforms, V_M = 1.5V.

TEST CIRCUIT AND WAVEFORMS



Test circuit for totem-pole outputs



Input pulse definition

family	INPUT PULSE REQUIREMENTS					
	amplitude	V _M	rep. rate	t _w	t _{TLH}	t _{THL}
74F	3.0V	1.5V	1MHz	500ns	2.5ns	2.5ns

DEFINITIONS:

R_L = Load resistor;

see AC electrical characteristics for value.

C_L = Load capacitance includes jig and probe capacitance;
see AC electrical characteristics for value.R_T = Termination resistance should be equal to Z_{OUT} of
pulse generators.