

FS6M07652RT

Fairchild Power Switch(SPS)

Features

- Fixed frequency
- Internal Burst mode Controller for Stand-by mode
- Pulse by pulse over current limiting
- Over current protection(Auto restart mode)
- Over voltage protection (Auto restart mode)
- Over load protection(Auto restart mode)
- Internal thermal shutdown function(Latch mode)
- Under voltage lockout
- Internal high voltage sense FET
- Soft start


Description

The Fairchild Power Switch(SPS) product family is specially designed for an off-line SMPS with minimal external components. The Fairchild Power Switch(SPS) consist of high voltage power SenseFET and current mode PWM IC. Included PWM controller features integrated fixed oscillator, under voltage lock out, leading edge blanking, optimized gate turn-on/turn-off driver, thermal shut down protection, over voltage protection, and temperature compensated precision current sources for loop compensation and fault protection circuitry. Compared to discrete MOSFET and controller or RCC switching converter solution, a Fairchild Power Switch(SPS) can reduce total component count, design size, and weight and at the same time increase efficiency, productivity, and system reliability. It has a basic platform well suited for cost effective LCD monitor power supply.

TO-220F-5L



Internal Block Diagram



Rev.1.0.0

Absolute Maximum Ratings

(Ta=25°C, unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-source(GND) voltage ⁽¹⁾	V _{DSS}	650	V
Drain-Gate Voltage (R _{GS} =1MΩ)	V _{DGR}	650	V
Gate-source (GND) Voltage	V _{GS}	±30	V
Drain current pulsed ⁽²⁾	I _{DM}	14.4	ADC
Single pulsed avalanche energy ⁽³⁾	E _{AS}	570	mJ
Single Pulsed Avalanche current ⁽⁴⁾	I _{AS}	17	A
Continuous drain current (T _C = 25°C)	I _D	3.6	ADC
Continuous drain current (T _C =100°C)	I _D	2.28	ADC
Supply voltage	V _{CC}	40	V
Input Voltage Range	V _{FB}	−0.3 to V _{CC}	V
	V _{S_S}	−0.3 to 10	V
Total Power Dissipation	P _D (Watt H/S)	TO-220F;46	W
	Derating	TO-220F;0.37	W/°C
Operating junction temperature	T _j	+160	°C
Operating Ambient Temperature	T _A	−25 to +85	°C
Storage Temperature range	T _{STG}	−55 to +150	°C

Notes:

1. T_j=25°C to 150°C
2. Repetitive rating: Pulse width limited by maximum junction temperature
3. L=81mH, starting T_j=25°C
4. L=13uH, starting T_j=25°C

Electrical Characteristics (SFET part)

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	650	-	-	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =650V, V _{GS} =0V	-	-	25	μA
		V _{DS} =520V V _{GS} =0V, T _C =125°C	-	-	300	μA
Static drain-source on resistance ^(note)	R _{DS(ON)}	V _{GS} =10V, I _D =1.8A	-	1.3	1.6	Ω
Forward transconductance ^(note)	g _{fs}	V _{DS} =50V, I _D =1.8A	-	3.3	-	S
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V, f = 1MHz	-	1200	1560	pF
Output capacitance	C _{oss}		-	125	160	
Reverse transfer capacitance	C _{rss}		-	23	30	
Turn on delay time	t _{d(on)}	V _{DD} =325V, I _D =6.5A (MOSFET switching time are essentially independent of operating temperature)	-	22	55	nS
Rise time	t _r		-	70	150	
Turn off delay time	t _{d(off)}		-	105	220	
Fall time	t _f		-	65	140	
Total gate charge (gate-source+gate-drain)	Q _g	V _{GS} =10V, I _D =6.5A, V _{DS} =520V (MOSFET Switching time are Essentially independent of Operating temperature)	-	40	52	nC
Gate-source charge	Q _{gs}		-	6.5	-	
Gate-drain (Miller) charge	Q _{gd}		-	18	-	

Note:

Pulse test : Pulse width ≤ 300μS, duty 2%

$$S = \frac{1}{R}$$

Electrical Characteristics

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
UVLO SECTION						
Start threshold voltage	VSTART	VFB=GND	14	15	16	V
Stop threshold voltage	VSTOP	VFB=GND	8	9	10	V
SENSEFET SECTION						
Drain to PKG Breakdown voltage	BVpkg	60HZ AC, Ta=25°C	3500	-	-	V
Drain to Source Breakdown voltage	BVDSS	Vdrain = 650V, Ta=25°C	650	-	-	V
Drain to Source Leakage current	Idss	Vdrain = 650V, Ta=25°C	-	-	300	uA
OSCILLATOR SECTION						
Initial Frequency	FOSC	-	63	70	77	KHz
Voltage Stability	FSTABLE	12V ≤ Vcc ≤ 23V	0	1	3	%
Temperature Stability (note4)	ΔFOSC	-25°C ≤ Ta ≤ 85°C	0	±5	±10	%
Maximum duty cycle	DMAX	-	75	80	85	%
Minimum Duty Cycle	DMIN	-	-	-	0	%
FEEDBACK SECTION						
Feedback source current	IFB	VFB=GND	0.7	0.9	1.1	mA
Shutdown Feedback voltage	VSD	Vfb ≥ 6.9V	6.9	7.5	8.1	V
Shutdown delay current	Idelay	VFB=5V	3.2	4.0	4.8	μA
PROTECTION SECTION						
Over Voltage Protection	VOVP	Vsync ≥ 11V	27	30	33	V
Over Current Latch Voltage (Note2)	VOCL	-	0.9	1.0	1.1	V
Thermal Shutdown Temp.(Note4)	TSD	-	140	160	-	°C
SOFTSTART SECTION						
Softstart Vortage	VSS	Vfb=2	4.7	5.0	5.3	V
Softstart Current	ISS	Vss=V	0.8	1.0	1.2	mA
BURST MODE SECTION						
Burst mode Low Threshold Voltage	VBURL	Vfb=0V	10.4	11.0	11.6	V
Burst mode High Threshold Voltage	VBURH	Vfb=0V	11.4	12.0	12.6	V
Burst mode Enable Feedback Voltage(Note4)	VBEN	Vcc=10.5V	0.7	1.0	1.3	V
Burst mode Peak Current Limit(Note3)	lBU_PK	Vcc=10.5V	0.38	0.5	0.62	V
Burst mode Frequency	FBUR	Vcc=10.5V, Vfb=0V	63	70	77	KHz
CURRENT LIMIT(SELF-PROTECTION)SECTION						
Peak Current Limit(Note3)	lOVER	-	1.76	2.0	2.24	A
TOTAL DEVICE SECTION						
Start Up current	lSTART	Vfb=GND, VCC=14V	-	0.1	0.2	mA
Operating supply current (Note1)	lOP	Vfb=GND, VCC=16V	-	10	15	mA
	lOP(MIN)	Vfb=GND, VCC=10V				
	lOP(MAX)	Vfb=GND, VCC=28V				

Notes:

- (1) These parameters is the current flowing in the Control IC.
- (2) These parameters, although guaranteed, are tested in EDS(wafer test) process.
- (3) These parameters indicate Inductor Current.
- (4) These parameters, although guranteed at the design, are not tested in massing production.

Typical Performance Characteristics




Figure 1. Start Up Current vs. Temp




Figure 2. Operating Current vs. Temp




Figure 3. Start Threshold Voltage vs. Temp




Figure 4. Stop Threshold Voltage vs. Temp




Figure 5. Initial Frequency vs. Temp




Figure 6. Maximum Duty vs. Temp

Typical Performance Characteristics (Continued)




Figure 7. Feedback Offset Voltage vs. Temp




Figure 8. Feedback Source Current vs. Temp




Figure 9. ShutDown Delay Current vs. Temp




Figure 10 . ShutDown Feedback Voltage vs. Temp




Figure 11 . Softstart Voltage vs. Temp




Figure 12 . Over Voltage Protection vs. Temp

Typical Performance Characteristics (Continued)




Figure 13 . Burst Mode Low Voltage vs. Temp




Figure 14 . Burst Mode High Voltage vs. Temp




Figure 15 . Burst Mode Peak Current vs. Temp




Figure 16 . Over Current Limit vs. Temp

Ordering Information

Product Number	Package	Operating Temperature
FS6M07652RT	TO-220F-5L	-25°C to +85°C

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.