

N.E.P.

NEW ENGLAND PHOTOCONDUCTOR

SERIES - AM, BM, CM, FM

HERMETICALLY SEALED PLATE CELL

PbS

Electrical

Type - Rm, Temp 25°C

D* (Pk., 750, 1) x 10¹⁰

Wavelength Cut-off Microns

Time Constant μ Secs.

Resistance Megohms

Mechanical Code

AM

4-7

3.0

≤ 100

.2-2.0

1-10

BM

5-10

3.2

100-300

.2-2.0

1-10

CM

5-10

2.6

≥ 300

.2-10

1-10

PbSe

Type - Rm, Temp. 25°C

D* (Pk., 1000, 1) x 10⁹

Wavelength Cut-off

Resistance Megohms

Time Constant μ Secs.

Mechanical Code

FM

1-3

4.7

.1-2

1-5

2, 4, 6-10

**Code
Number**

1

2

3

4

5

6

7

8

9

10

Mechanical

Active Area

Inches²

MM²

.005 x .005

.125 TO-5

.010 x .010

.25 TO-5

.020 x .020

.5 TO-5

.040 x .040

1 TO-5

.060 x .060

1.5 TO-5

.080 x .080

2 TO-5

.120 x .120

3 TO-5

.160 x .160


4 TO-8

.200 x .200


5 TO-8

.400 x .400


10 TO-3



TO-5 PLATE CELL



TO-8 PLATE CELL



TO-3 PLATE CELL

HOW TO ORDER:

Select the proper electrical type (AM, BM, CM, or FM) and match it with the proper mechanical code number. Example: AM1, BM4, FM4. The active areas listed above are considered standard sizes. Special sizes are available on request.

253 Mansfield Ave. • Box M • Norton, MA 02766 U.S.A.
Tel. (508) 285-5561 • Fax. (508) 285-6480 • Tlx. 294116 BOSTLX