

E-Series Plug-In Mixer

0.5 - 500 MHz

EMS-1H

V3.00

Features

- LO Power: +17 dBm
- Up to +10 dBm RF

Specifications @ 25°C

Frequency Range		
RF		0.5 - 500 MHz
LO		0.5 - 500 MHz
IF		DC - 500 MHz
Conversion Loss (dB)		
1 - 250 MHz	Typical	Maximum
	5.5	7.5
.5 - 500 MHz	6.5	8.5
Isolation (dB)		
LO to RF	Typical	Minimum
0.5 - 5 MHz	55	45
5 - 250 MHz	45	30
250 - 500 MHz	35	25
LO to IF		
0.5 - 5 MHz	45	35
5 - 250 MHz	40	30
250 - 500 MHz	30	20

Operating Characteristics

Impedance	50 Ohms Nominal
RF input for 1dB Compression	+ 10 dBm


Ordering Information

Part No.	Packaging
EMS-1H	Tube
EMS-1HTR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	200 mW
Peak IF Current	40 mA
Storage Temperature	-55°C to 100°C
Operating Temperature	-55°C to 100°C
Pin Temperature (10 Seconds)	260°C

R-1



Dimensions in () are in mm.

Unless Otherwise Noted: .x = ±0.04 (1.00)

.xx = ±0.02 (0.50)

.xxx = ±0.010 (0.250)

WEIGHT (APPROX.): 0.16 OUNCES 4.4 GRAMS

Pin Configuration

Function	Pin No.
LO	8
RF	1
IF*	3,4
Ground	2,5,6,7
Case Ground	2

* IF pins must be connected together externally.

S 0089 B