

ECL DIGITAL DELAY LINES

SERIES E10 - ECL 10K INTERFACED

SERIES E100 - ECL 100K INTERFACED

- Industry's widest selection!
- Economical cost, prompt delivery
- Fast 2nSec rise time typical
- Standard 16 pin DIP on ECL 10K, 24 pin DIP on ECL 100K
- Surface Mount design available
- High-Speed CMOS design available

NEW
PRODUCT

TEST CONDITIONS @25°C

Pulse width: $2 \times$ Total Delay
Pulse Spacing: $5 \times$ Total Delay
Pulse Amplitude: -1.0V provided by open emitter ECL 10K gate
Supply Voltage (VEE): 5.2VDC ECL 10K, -4.5 VDC ECL 100K
Ground (VCC): 0V

ECL 10K outputs connected to external pull down 100Ω resistor to -2V
ECL 100K outputs connected to external pull down 50Ω resistor to -2V
Total Delay and Tap tolerance: $\pm 5\%$ or $\pm 1\text{nS}$ whichever is greater

TYPE E105 - ECL10K 5 TAP

Total Delay (nS)	Tap Delay (nS)	SCHEMATIC
10	2	
15	3	
20	4	
25	5	
30	6	
40	8	
50	10	
60	12	
80	16	
100	20	

TYPE E1008 - ECL100K 8 TAP

Total Delay (nS)	Tap Delay (nS)	SCHEMATIC
8	1	
16	2	
24	3	
32	4	
40	5	
48	6	
56	7	
64	8	
72	9	
80	10	
160	20	
200	25	

TYPE E101 - ECL10K SINGLE OUTPUT

Delay (nS)	SCHEMATIC
5	
10	
15	
20	
25	
50	
75	
100	

TYPE E1001 - ECL100K SINGLE OUTPUT

Delay (nS)	SCHEMATIC
5	
10	
15	
20	
25	
50	
75	
100	
150	
200	

TYPE E103 - ECL10K 3 INDEPENDENT DELAYS *

Delay (nS)	SCHEMATIC
5	
10	
15	
20	
25	
50	


* Also available in a double delay output

TYPE E1004 - ECL100K 4 INDEPENDENT DELAYS

Delay (nS)	SCHEMATIC
5	
10	
15	
20	
25	
50	
75	
100	


10K ECL DIMENSIONS

(unused pins are removed)



100K ECL DIMENSIONS

(unused pins are removed)



RCD Components, Inc., 520 East Industrial Park Dr., Manchester, NH USA 03109-1824

Tel: (603) 669-0054

Fax: (603) 669-5455