

DALLAS

SEMICONDUCTOR

DS80C323

Low-Power Micro

FEATURES

- 80C32-Compatible
 - Pin-compatible
 - Standard 8051 instruction set
 - Four 8-bit I/O ports
 - Three 16-bit timer/counters
 - 256 bytes scratchpad RAM
 - Multiplexed address/data bus
 - Addresses 64KB ROM and 64KB RAM
- Operates between 2.7V and 5.5V
- High-speed architecture
 - 4 clocks/machine cycle (8032=12)
 - Wasted cycles removed
 - Runs DC to 20 MHz clock rate @ 2.7V
 - Single-cycle instruction in 200 ns
 - Uses less power for equivalent work
 - Dual data pointer
 - Optional variable length MOVX to access fast/slow RAM /peripherals
- High integration controller includes:
 - Power-fail reset
 - Programmable Watchdog timer
 - Early-warning power-fail interrupt
- Two full-duplex hardware serial ports
- 13 total interrupt sources with six external
- Available in 40-pin DIP, 44-pin PLCC and TQFP

DESCRIPTION

The DS80C323 is a fast 80C31/80C32-compatible microcontroller. Wasted clock and memory cycles have been removed using a redesigned processor core. As a result, every 8051 instruction is executed between 1.5 and 3 times faster than the original for the same crystal speed. Typical applications will see a speed improvement of 2.5 times using the same code and same crystal. At 2.7V, the DS80C323 offers a maximum crystal rate of 20 MHz, resulting in apparent execution speeds of 50 MHz (approximately 2.5X).

PIN ASSIGNMENT

