


July 1998

The **LT<sup>®</sup>1780/LT1781** data sheet has been modified to include the operating temperature range of  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ . The electrical characteristics are the same as the commercial temperature versions. The order numbers are shown below in **bold**. For complete specifications, typical performance curves and applications information, please see the **LT1780/LT1781** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.



## ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range

Commercial .....  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$

**Industrial** .....  **$-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$**

## PACKAGE/ORDER INFORMATION

<div> <p>TOP VIEW</p>  <p>N PACKAGE 18-LEAD PDIP</p> <p>SW PACKAGE 18-LEAD PLASTIC SO</p> </div>	<div> <p>ORDER PART NUMBER</p> <p>LT1780CN LT1780CSW <b>LT17801IN</b> <b>LT1780SW</b></p> </div>	<div> <p>TOP VIEW</p>  <p>N PACKAGE 16-LEAD PDIP</p> <p>S PACKAGE 16-LEAD PLASTIC SO</p> <p>SW PACKAGE 16-LEAD PLASTIC SO</p> </div>	<div> <p>ORDER PART NUMBER</p> <p>LT1781CN LT1781CS LT1781CSW <b>LT1781IN</b> <b>LT1781IS</b> <b>LT1781SW</b></p> </div>
---	--	--	--

For further information regarding this specification notice contact:

Linear Technology Corporation  
 1630 McCarthy Blvd.  
 Milpitas, California 95035-7417  
 Attn: Product Marketing Manager  
 Phone: (408) 432-1900