


SIEMENS

RED LR 5480
SUPER-RED LS 5480
YELLOW LY 5480
GREEN LG 5480

T1 3/4 (5 mm) LED LAMP




FEATURES

- Diffused Lens
- Wide Viewing Angle 80°
- Without Standoffs
- T1 3/4 (5 mm) Package Size
- 1≤ Lead Length
- IC Compatible

DESCRIPTION

The LR 5480 series is a standard red gallium arsenide phosphide (GaAsP) LED lamp. The LS 5480 super-red and LY 5480 yellow are premium high efficiency light emitting diode lamps fabricated with TSN (transparent substrate nitrogen) technology. The LG 5480 green is a gallium phosphide (GaP) lamp. All have a diffused plastic lens, which emits a full flooded intense light.

Package Dimensions in Inches (mm)



Maximum Ratings

Storage Temperature Range (T_{STG})	-55°C to +100°C
Junction Temperature (T_J)	100°C
Reverse Voltage (V_R)	5 V
Forward Current (I_F)	40 mA
Surge Current ($t \leq 10 \mu s$) (I_{FS})	0.5 A
Total Power Dissipation (P_{TOT}) ($T_A=25^\circ C$)	140 mW
Thermal Resistance Junction to Air (R_{THJA})	400 K/W

Characteristics ($T_A=25^\circ C$) All values typical unless otherwise noted

Parameter	Sym	LR 5480 Red	LS 5480 Super-Red	LY 5480 Yellow	LG 5480 Green	Unit
Wavelength at Peak Emission	λ_{PEAK}	660	635	586	565	nm
Dominant Wavelength	λ_{DOM}	645	628	590	570	nm
Spectral Bandwidth (50% I_{RELMAX} , $I_F=20$ mA) $\Delta\lambda$		35	45	45	25	nm
Viewing Angle (Limits for 50% of Luminous Intensity I_V)	ϕ	80	80	80	80	Deg.
Forward Voltage ($I_F=10$ mA)	V_F	1.6(≤2.0)	2.0(≤2.6)	2.0(≤2.6)	2.0(≤2.6)	V
Reverse Current ($V_R=5$ V)	I_R	0.01(≤10)	0.01(≤10)	0.01(≤10)	0.01(≤10)	μA
Capacitance ($V_R=0$ V, $f=1$ MHz)	C_0	25	12	10	15	pF
Rise Time	t_R	120	300	300	450	ns
Fall Time	t_F	50	150	150	200	ns
Luminous Intensity (mcd)*						

Part Number	Min.	Max.	Condition	Part Number	Min.	Max.	Condition
LR 5480-CF	0.25	2	10 mA	LY 5480-GK	1.6	12.5	10 mA
LR 5480-DG	0.4	3.2	10 mA	LY 5480-L	10	20	10 mA
LR 5480-E	0.63	1.25	10 mA	LY 5480-JM	4	32	10 mA
LR 5480-F	1	2	10 mA	LY 5480-K	6.3	12.5	10 mA
LS 5480-GK	1.6	12.5	10 mA	LG 5480-GK	1.6	12.5	10 mA
LS 5480-J	4	8	10 mA	LG 5480-H	2.5	5	10 mA
LS 5480-JM	4	32	10 mA	LG 5480-J	4	8	10 mA
LS 5480-K	6.3	12.5	10 mA	LG 5480-JM	4	32	10 mA
				LG 5480-K	6.3	12.5	10 mA

See graph numbers 1, 2R, 3A, 4A, 5A, 6A, 7A, 8A, 9A, 10A in the back of this section.

* Luminous intensity ratio of I_V of one packaging unit $I_{VMAX}/I_{VMIN} \leq 2$.