

SONY CXK58257ATM/AYM -70L/85L/10L/12L -70LL/85LL/10LL/12LL

32768-word × 8-bit High Speed CMOS Static RAM

SONY CORP/COMPONENT PRODS

Description

CXK58257ATM/AYM is a 256K bits, 32,768 words by 8 bits, CMOS static RAM.

It is suitable for portable and battery back-up systems which require extremely small package and low stand-by current.

Features

- Thin Small-outline package :
CXK58257ATM : 8mm × 13.4mm 28 pin TSOP
CXK58257AYM : 8mm × 13.4mm 28 pin TSOP (Mirror image pinout)
- Low stand-by current :
L-Version :
25 μ A (Max.) @ $V_{CC} = 5.5V$, $T_a = 0$ to $70^\circ C$
LL-Version :
5 μ A (Max.) @ $V_{CC} = 5.5V$, $T_a = 0$ to $70^\circ C$
- Low voltage data retention : 2.0V (Min.)
- Fast access time : (Access time)
CXK58257ATM/AYM-70L, -70LL 70ns (Max.)
CXK58257ATM/AYM-85L, -85LL 85ns (Max.)
CXK58257ATM/AYM-10L, -10LL 100ns (Max.)
CXK58257ATM/AYM-12L, -12LL 120ns (Max.)
- Single +5V Supply : $5V \pm 10\%$


Function

32768-word × 8-bit static RAM

Structure

Silicon gate CMOS IC

Block Diagram




CXK58257ATM 28 pin TSOP (Plastic) CXK58257AYM 28 pin TSOP (Plastic)



Pin Description

Symbol	Description
A0 to A14	Address input
I/O1 to I/O8	Data input/output
CE	Chip enable input
WE	Write enable input
OE	Output enable input
VCC	+5V power supply
GND	Ground

Pin Configuration (Top View)



E90448 - ST

SONY

SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM

T-46-23-13

Absolute Maximum Ratings

(Ta = 25°C, GND = 0V)

Item	Symbol	Rating	Unit
Supply voltage	V _{CC}	-0.5 to +7.0	V
Input voltage	V _{IN}	-0.5* to V _{CC} +0.5	V
Input and output voltage	V _{I/O}	-0.5* to V _{CC} +0.5	V
Allowable power dissipation	P _D	0.7	W
Operating temperature	T _{opr}	0 to +70	°C
Storage temperature	T _{stg}	-55 to +150	°C
Soldering temperature	T _{solder}	235 ± 10	°C · sec

* V_{IN}, V_{I/O} = -3.0V Min. for pulse width less than 50ns.

Truth Table

$\overline{CE}$	$\overline{OE}$	$\overline{WE}$	Mode	I/O1 to I/O8	V _{CC} Current
H	x	x	Not selected	High Z	I _{sB1} , I _{sB2}
L	H	H	Not selected	High Z	I _{CC1} , I _{CC2}
L	L	H	Read	Data out	I _{CC1} , I _{CC2}
L	x	L	Write	Data in	I _{CC1} , I _{CC2}

x : "H" or "L"

DC Recommended Operating Conditions (Ta = 0 to +70°C, GND = 0V)

Item	Symbol	Min.	Typ.	Max.	Unit
Supply voltage	V _{CC}	4.5	5.0	5.5	V
Input high voltage	V _{IH}	2.2	—	V _{CC} + 0.3	V
Input low voltage	V _{IL}	-0.3*	—	0.8	V

* V_{IL} = -3.0V Min. for pulse width less than 50ns.

SONY

SONY CORP/COMPONENT PRODS

CXK59257ATM/AYM

T-46-23-13

Electrical Characteristics

• DC and operating characteristics

(V_{CC} = 5V ± 10%, GND = 0V, T_a = 0 to +70°C)

Item	Symbol	Test conditions		- 70L/85L/10L/12L			- 70LL/85LL/10LL/12LL			Unit
				Min.	Typ.*	Max.	Min.	Typ.*	Max.	
Input leakage current	I _{LI}	V _{IN} = GND to V _{CC}		- 0.5	—	0.5	- 0.5	—	0.5	μA
Output leakage current	I _{LO}	$\overline{CE} = V_{IH}$ or $\overline{OE} = V_{IH}$ V _{I/O} = GND to V _{CC}		- 0.5	—	0.5	- 0.5	—	0.5	μA
Operating power supply current	I _{CC1}	$\overline{CE} = V_{IL}$, V _{IN} = V _{IH} or V _{IL} , I _{OUT} = 0mA		—	3	10	—	3	10	mA
		$\overline{CE} \leq 0.2V$ V _{IN} $\leq 0.2V$ or $\geq V_{CC} - 0.2V$		—	1	5	—	1	5	
Average operating current	I _{CC2}	Cycle = Min, Duty = 100 %, I _{OUT} = 0mA	70L/70LL	—	30	50	—	30	50	mA
			85L/85LL	—	25	50	—	25	50	
			10L/10LL	—	23	50	—	23	50	
			12L/12LL	—	20	50	—	20	50	
Standby current	I _{SB1}	$\overline{CE} \geq V_{CC} - 0.2V$	0 to 70°C	—	—	25	—	—	5	μA
			0 to 40°C	—	—	5	—	—	1	
			25°C	—	0.5	2	—	0.2	0.5	
	I _{SB2}	$\overline{CE} = V_{IH}$	—	0.4	2	—	0.4	2	mA	
Output high voltage	V _{OH}	I _{OH} = - 1.0mA		2.4	—	—	2.4	—	—	V
Output low voltage	V _{OL}	I _{OL} = 2.1mA		—	—	0.4	—	—	0.4	V

* V_{CC} = 5V, T_a = 25°C

I/O capacitance

(T_a = 25°C, f = 1MHz)

Item	Symbol	Test conditions	Min.	Max.	Unit
Input capacitance	C _{IN}	V _{IN} = 0V	—	6	pF
I/O capacitance	C _{I/O}	V _{I/O} = 0V	—	8	pF

Note) This parameter is sampled and is not 100% tested.


SONY

SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM

AC characteristics● **AC test conditions**(V_{CC} = 5V ± 10%, T_a = 0 to +70°C)

Item	Conditions	
Input pulse high level	V _{IH} = 2.2V	
Input pulse low level	V _{IL} = 0.8V	
Input rise time	tr = 5ns	
Input fall time	tf = 5ns	
Input and output reference level	1.5V	
Output load conditions	85L/85LL/10L/10LL/12L/12LL	C _L * = 100pF, 1TTL
	70L/70LL	C _L * = 30pF, 1TTL

* C_L includes scope and jig capacitances.

SONY®

SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM

T-46-23-13

• Read cycle

Item	Symbol	-70L/70LL		-85L/85LL		-10L/10LL		-12L/12LL		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Read cycle time	t _{RC}	70	—	85	—	100	—	120	—	ns
Address access time	t _{AA}	—	70	—	85	—	100	—	120	ns
Chip enable access time	t _{CO}	—	70	—	85	—	100	—	120	ns
Output enable to output valid	t _{OE}	—	35	—	45	—	50	—	60	ns
Output hold from address change	t _{OH}	20	—	20	—	20	—	20	—	ns
Chip enable to output in low Z (CE)	t _{LZ}	10	—	10	—	10	—	10	—	ns
Output enable to output in low Z (OE)	t _{OLZ}	5	—	5	—	5	—	5	—	ns
Chip disable to output in high Z (CE)	t _{HZ} *	0	30	0	30	0	30	0	30	ns
Chip disable to output in high Z (OE)	t _{OHZ} *	0	30	0	30	0	35	0	40	ns

* t_{HZ} and t_{OHZ} are defined as the time required for outputs to turn to high impedance state and are not referred to as output voltage levels.

• Write cycle

Item	Symbol	-70L/70LL		-85L/85LL		-10L/10LL		-12L/12LL		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Write cycle time	t _{WC}	70	—	85	—	100	—	120	—	ns
Address valid to end of write	t _{AW}	65	—	75	—	80	—	100	—	ns
Chip enable to end of write	t _{CW}	65	—	75	—	80	—	100	—	ns
Data to write time overlap	t _{DW}	30	—	30	—	35	—	40	—	ns
Data hold from write time	t _{DH}	0	—	0	—	0	—	0	—	ns
Write pulse width	t _{WP}	50	—	50	—	60	—	70	—	ns
Address setup time	t _{AS}	0	—	0	—	0	—	0	—	ns
Write recovery time (WE)	t _{WR}	0	—	0	—	0	—	0	—	ns
Write recovery time (CE)	t _{WR1}	0	—	0	—	0	—	0	—	ns
Output active from end of write	t _{OW}	10	—	10	—	10	—	10	—	ns
Write to output in high Z	t _{WHZ} *	0	25	0	25	0	25	0	25	ns

* t_{WHZ} is defined as the time required for outputs to turn to high impedance state and is not referred to as output voltage level.

SONY


SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM


Timing Waveform

- Read cycle (1) : $\overline{CE} = \overline{OE} = V_{IL}$, $\overline{WE} = V_{IH}$


T-46-23-13



- Read cycle (2) : $\overline{WE} = V_{IH}$



- Write cycle (1) : $\overline{WE}$ control




SONY

SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM

T-46-23-13

- Write cycle (2) : $\overline{CE}$ control



During I/O pins are in the output state, the data input signals of opposite phase to the output must not be applied.


Data Retention Characteristics

(Ta = 0 to 70°C)

Item	Symbol	Test conditions	-70L/85L/10L/12L			-70LL/85LL/10LL/12LL			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Data retention voltage	V _{DR}	$\overline{CE} \geq V_{CC} - 0.2V$	2.0	—	5.5	2.0	—	5.5	V
Data retention current	I _{CCDR1}	V _{CC} = 3.0V	—	—	10	—	—	3	μA
		$\overline{CE} \geq 2.8V$	—	—	2	—	—	0.6	
		25°C	—	0.25	1	—	0.1	0.3	
	I _{CCDR2}	V _{CC} = 2.0 to 5.5V $\overline{CE} \geq V_{CC} - 0.2V$	—	0.5	25	—	0.2	5	μA
Data retention setup time	t _{CDRS}	Chip disable to data retention mode	0	—	—	0	—	—	ns
Recovery time	t _r		t _{rc} *	—	—	t _{rc} *	—	—	ns

* t_{rc}: Read cycle time

Data retention waveform



SONY


SONY CORP/COMPONENT PRODS

CXK58257ATM/AYM


T-46-23-13

Example of Representative Characteristics


Supply current vs. Supply voltage




Supply current vs. Ambient temperature




Supply current vs. Frequency




Access time vs. Load capacitance



Access time vs. Supply voltage



Access time vs. Ambient temperature




SONY

SONY CORP/COMPONENT PRODS


CXK58257ATM/AYM

T-46-23-13


Standby current vs. Supply voltage




Standby current vs. Ambient temperature




Input voltage level vs. Supply voltage




Standby current vs. Ambient temperature



Output high current vs. Output high voltage



Output low current vs. Output low voltage



SONY

SONY CORP/COMPONENT PRODS


CXK58257ATM/AYM

Package Outline Unit: mm


T-46-23-13

CXK58257ATM

28pin TSOP (Plastic)



SONY NAME TSOP-28P-L01




Detailed diagram of A

SONY NAME	TSOP-28P-L01
ETAJ NAME	TSOP28-P-0000-A
JEDEC CODE	


Note: Dimensions marked with *
do not include trim residue.

CXK58257AYM

28pin TSOP (Plastic)



SONY NAME TSOP-28P-L01R



Detailed diagram of A

SONY NAME	TSOP-28P-L01R
ETAJ NAME	TSOP28-P-0000-B
JEDEC CODE	

Note: Dimensions marked with *
do not include trim residue.