


“Marshal Bean” Protective Rubber Covers with Tether Rope 780-555



*Fits Metal Shell
M83513 Type
Connectors*

Rubber Covers for Tactical Equipment and Field Instruments

– These friction-fit covers provide dust and splash protection.

Two Tether Styles – Choose ring terminals for attachment to a panel, or choose slip knots for cable attachment.



-55° to +125° Temperature Range

MATERIALS & FINISHES

Cover	SBR Rubber Per ASTM D2000 Type C
Cord	Nylon Per MIL-C-43307
Ring Terminal	Stainless Steel
Slip Collar	Kynar
Crimp Ring	Copper, Black Oxide Finish

HOW TO ORDER 780-555 RUBBER PROTECTIVE COVERS

Series	Connector Layout		Nylon Cord Option	Nylon Cord Length	Attachment Option		Rubber Type
780-555	9P	9S	Omit — (leave blank) Cover only, no cord	Length in One Inch Increments	Ring Terminal		Omit Standard Rubber
	15P	15S			06 — .125 (3.2) I.D.		
	21P	21S	G — Nylon Cord	Example: “6” equals six inches.	01 — .140 (3.6) I.D.		C Conductive Rubber
	25P	25S			05 — .167 (4.2) I.D.		
	31P	31S			04 — .197 (5.0) I.D.		
	37P	37S					
	51P	51S					
	51-2P	51-2S					
	67P	67S					
	69P	69S					
	100P	100S					
Sample Part Number							
780-555	37P	G	4	— SK			



Layout	A Max.		B Max.	
	In.	mm.	In.	mm.
9P, 9S	.830	21.08	.370	9.40
15P, 15S	.980	24.89	.370	9.40
21P, 21S	1.130	28.70	.370	9.40
25P, 25S	1.230	31.24	.370	9.40
31P, 31S	1.380	35.05	.370	9.40
37P, 37S	1.530	38.86	.370	9.40

Layout	A Max.		B Max.	
	In.	mm.	In.	mm.
51P, 51S	1.480	37.59	.410	10.41
51-2P, 51-2S	1.880	47.75	.370	9.40
67P, 67S	2.770	70.36	.370	9.40
69P, 69S	1.780	45.21	.410	10.41
100P, 100S	2.215	56.26	.460	11.68