

DC/DC CONVERTERS**SMALL PACKAGE, WIDE INPUT RANGE****FEATURES**

- SMALL PACKAGE SIZE: 1" x 2"
- INDUSTRY STANDARD PINOUT
- SURFACE MOUNT DEVICES (SMD)
- LOW-COST ALTERNATE SOURCE
- CONTINUOUS SHORT CIRCUIT PROTECTION
- UL1950 RECOGNITION (SOME MODELS PENDING)
- MEETS FCC CLASS B

DESCRIPTION

The WP05R Series is a family of high performance DC/DC converters that offer high efficiency and regulated outputs over a 2:1 input voltage range of either 18-36VDC or 36-72 VDC.

Surface mount devices and manufacturing technology make it possible to offer performance equivalent to competition at a lower cost.

A self oscillating flyback topology coupled with a rugged MOSPOWER transistor are used to produce a highly reliable product with a minimum parts count. The internal body diodes of these FETS protect the unit against input voltage reversal. An external fuse is required to limit the body diode current to 2 amps.

The WP05R Series offers low noise (approximately

APPLICATIONS

- TELECOMMUNICATION EQUIPMENT
- BATTERY POWERED SYSTEMS
- PORTABLE INSTRUMENTS
- PROCESS CONTROL EQUIPMENT
- TRANSPORTATION EQUIPMENT
- DISTRIBUTED POWER SYSTEMS
- SPACE-CRITICAL APPLICATIONS

50 to 75mVp-p) without the addition of an external capacitor. The series is also 6-sided shielded, further reducing system noise. This shield is connected to -VIN.

No external heatsink is required for the WP05R Series to supply its rated 5 watts. With a minimum amount of airflow, the temperature range may be extended from 70°C to 85°C. (See derating curve.)

The package of the WP05R Series is plastic. This eliminates the layout precautions required by metal enclosed devices. The encapsulant material is rated UL94V-0 for flammability and offers excellent heat transfer characteristics.

Internal circuitry provides continuous short-circuit protection and automatic restart after the short is removed.

ELECTRICAL SPECIFICATIONS

Specifications typical at $T_A = +25^{\circ}\text{C}$, nominal input voltage, rated output current unless otherwise specified.

MODEL	NOMINAL INPUT VOLTAGE (VDC)	RATED OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT		INPUT CURRENT		EFFICIENCY (%)
			MIN LOAD (mA)	RATED LOAD (mA)	MIN LOAD (mA)	RATED LOAD (mA)	
WP05R24S03	24	3.3	25	1500	20	300	70
WP05R24S05	24	5	50	1000	20	265	78
WP05R24S12	24	12	21	417	20	255	82
WP05R24S15	24	15	17	333	20	250	83
WP05R24D05	24	± 5	± 25	± 500	20	265	78
WP05R24D12	24	± 12	± 10	± 208	20	255	82
WP05R24D15	24	± 15	± 8	± 167	20	250	83
WP05R48S03	48	3.3	25	1500	13	150	70
WP05R48S05	48	5	50	1000	13	135	78
WP05R48S12	48	12	21	417	13	127	82
WP05R48S15	48	15	17	333	13	125	83
WP05R48D05	48	± 5	± 25	± 500	13	135	78
WP05R48D12	48	± 12	± 10	± 208	13	127	82
WP05R48D15	48	± 15	± 8	± 167	13	125	83

NOTE: Other input and output voltages may be available. Please consult factory.

COMMON SPECIFICATIONS

Specifications typical at $T_A = +25^{\circ}\text{C}$, nominal input voltage, rated output current unless otherwise specified.

Parameter	Conditions	Min	Typ	Max	Units
INPUT					
Voltage Range		18	24	36	VDC
Reflected Ripple Current		36	48	72	VDC
			20	35	mAp-p
ISOLATION					
Rated Voltage		500		VDC	
Test Voltage	60 Hz, 10 Seconds	500		Vpk	
Resistance		10			GΩ
Capacitance			470		pF
Leakage Current	$V_{iso} = 240\text{VAC}, 60\text{Hz}$		50		μArms
OUTPUT					
Rated Power			5.0		W
Voltage Setpoint Accuracy					
Singles			± 1	± 2	%
Duals			± 2	± 4	%
Temperature Coefficient			± 0.02		%/°C
Line Regulation	Low Line to High Line				
Singles				5	mV
Duals				1	%
Load Regulation	Min Load to Rated Load				
Singles				25	mV
Duals				1	%
Ripple and Noise					
24VIN Models	BW = 20Hz to 10MHz			100	mVp-p
48VIN Models	BW = 20Hz to 10MHz			50	mVp-p
5V Output Models	BW = 20Hz to 2MHz			5	mVrms
Other Models	BW = 20Hz to 2MHz			10	mVrms
Transient Response	Rated Load to Min Load	10			mS
	Min Load to Rated Load	10			mS
Overvoltage Protection Threshold	3.3V Output		3.9		VDC
	5V Output		6.8		VDC
	12V Output		15		VDC
	15V Output		18		VDC
GENERAL					
Switching Frequency			140		kHz
Package Weight			30		g
MTTF per MIL-HDBK-217	Ground Benign, Circuit Stress Method				
Revision F	$T_A = +25^{\circ}\text{C}$		636,843		Hr
	$T_A = +70^{\circ}\text{C}$		199,000		Hr
	$T_A = +85^{\circ}\text{C}$		122,009		Hr
MTTF per Bellcore TR-NWT-000322	Environmental Stress = 1.0				
Issue 4, September, 1992	$T_A = +25^{\circ}\text{C}$		1,079,617		Hr
	$T_A = +70^{\circ}\text{C}$		205,055		Hr
	$T_A = +85^{\circ}\text{C}$		98,839		Hr
TEMPERATURE					
Specification	No Power Derating	-40	+85	°C	
Operation		-40	+100	°C	
Storage		-55	+110	°C	



ABSOLUTE MAXIMUM RATINGS

Output Short-Circuit Duration.....	Continuous
Case Temperature	100°C
Lead Temperature (soldering, 10 seconds max).....	+300°C

ORDERING INFORMATION

Device Family	WP05R	xyzz	N	/H
Indicates Wide Input Power 5 Watt Regulated Unit				
Model Number	Selected From Table of Electrical Characteristics			
Where:				
xx = Input Voltage				
y = Number of Outputs (Single "S", Dual "D")				
zz = Output Voltage				
Package Option				
Screening Option				

MECHANICAL



NOTES: All dimensions are in inches (millimeters).

GRID: 0.100 inches (2.54 millimeters)


Common pins are not present on single output models.

Product marked with specific model ordered, date code, job code.

PIN PLACEMENT TOLERANCE: ±0.015

MATERIAL: Units are encapsulated in Iso-ThermoFlex™, a low thermal resistance molding compound which has excellent chemical resistance, wide operating temperature range, and good electrical properties under high humidity environments. The encapsulant and the outer shell of the unit have UL94V-0 ratings. Lead material is brass with a solder plated surface to allow ease of solderability.

APPLICATION NOTES




FUSING

For maximum safety and system protection, a Buss PC-TRON, PCB 2A fuse or equivalent should be used in series with the input.


TYPICAL PERFORMANCE CURVES

$T_A = +25^\circ\text{C}$, nominal input voltage, rated load, recommended external components applied, unless otherwise specified.


EFFICIENCY vs INPUT VOLTAGE




EFFICIENCY vs OUTPUT LOAD




EFFICIENCY vs TEMPERATURE




OUTPUT NOISE vs INPUT VOLTAGE




OUTPUT NOISE vs OUTPUT LOAD




OUTPUT NOISE vs TEMPERATURE



REFLECTED RIPPLE CURRENT vs INPUT VOLTAGE



REFLECTED RIPPLE CURRENT vs OUTPUT LOAD



REFLECTED RIPPLE CURRENT vs TEMPERATURE

