

3

DIGIT HEIGHT	CSC PART NO.				DISPLAY FONT	DRIVING MODE	COMMON MODE	SUGGESTED IC'S IN APPLICATION			
	RED	HI-RED	GREEN	ORANGE					1	2	3
INCH (mm) .7" (17.78)	742	742H	742G	742E	:88:88:	DIRECT	C.A.	NS.MM5387 T11951 EA7316 SANYO8361 NS.MM5455/5456/5457	+COM	-PM	-AM
	743	743H	743G	743E	:88:88:	DIRECT	C.C.		-COM	+PM	+AM
	754	754H	754G	754E	:28:88:	DUPLEX	C.A.		+COM1	+COM2	+AM
	755	755H	755G	755E	:28:88:	DUPLEX	C.C.		-COM1	-COM2	-AM
.8" (20.32)	832	832H	832G	832E	888	MPX	C.A.		-A	+COM2	+COM1
	842	842H	842G	842E	8888	MPX	C.A.		-A	+COM2	+COM1
	844	844H	844G	844E	1888	MPX	C.A.		-A	+COM2	+COM1
.9" (22.86)	944	944H	944G	944E	:88:88:	DIRECT	C.A.	NS.MM5402 NS.MM5387 T11951 EA7316 SANYO8361 NS.MM5455/5456/5457	-AM	+COM1	-1J
	945	945H	945G	945E	:88:88:	DIRECT	C.C.		+AM	-COM1	+1J
	947	947H	947G	947E	18:88	MPX	C.C.		+AL	-AL2	N.C
	954	954H	954G	954E	:28:88:	DUPLEX	C.A.		+COM1	+COM2	N.C
	955	955H	955G	955E	:28:88:	DUPLEX	C.C.		-COM1	-COM2	N.C
1.8" (45.7)	1845H	1845G	1845E		:28:88:	DIRECT	C.C.	NS5387 SANYO8361	+PM	-COM	+1E
	1847H	1847G	1847E		:28:88:	DUPLEX	C.C.		-COM1	-COM2	-AM
2.5" (63.5)	2544H	2544G	2544E		:88:88:	DIRECT	C.A.	NS.MM5402 NS5387 SANYO8361	-PM	N.C	-AM
	2545H	2545G	2545E		:88:88:	DIRECT	C.C.		+PM	N.C	+AM
4.0" (101.6)	4044H	4044G	4044E		:88:88:	DIRECT	C.A.	NS.MM5402 NS5387 SANYO8361	-PM	+COM	-1E
	4045H	4045G	4045E		:88:88:	DIRECT	C.C.		+PM	-COM	+1E
1.5x5.0 (m/m)	V1052	V1052H	V1052G	V1052E	1 x 5 SEG.	DIRECT	C.A.	M51903L-TI:SN16889 NS.LM3916 TITL490C TA7612AP UAA180	+COM	-D1	-D2
	V1102	V1102H	V1102G	V1102E	1 x 10 SEG.	DIRECT	C.A.		+COM	-D1	-D2
	V1103	V1103H	V1103G	V1103E	1 x 10 SEG.	DIRECT	C.C.		-COM	+D1	+D2
2.0x5.0 (m/m)	V10101	V10101H	V10101G	V10101E	10 x 10 SEG.	MPX	C.C.		+C1	+C2	+C3

TE: PIN CONNECTION CODES.

(+)=ANODE

(-)=CATHODE

C.A=COMMON ANODE

C.C=COMMON CATHODE

N.C=NO CONNECTION

DP=DECIMAL POINT

SW=SWITCH

A=Segment A

B=Segment B

C=Segment C

E=Segment E

F=Segment F

G=Segment G