


Digital Transistor (Dual Digital Transistors for Power Management)

UMC1N / FMC1A

●Features

- 1) DTA143T and DTC143T transistors are housed in a UMT or SMT package.

●Circuit schematics



●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CB0}	50	V
Collector-emitter voltage	V_{CE0}	50	V
Emitter-base voltage	V_{EB0}	5	V
Collector current	I_C	100	mA
Collector power dissipation	UMC1N FMC1A	150 (TOTAL) 300 (TOTAL)	mW *1 *2
Junction temperature	T_J	150	°C
Storage temperature	T_{stg}	-55~150	°C

*1 120mW per element must not be exceeded. *2 200mW per element must not be exceeded. PNP type negative symbols have been omitted.

●Package, marking, and packaging specifications

Type	UMC1N	FMC1A
Package	UMT5	SMT5
Marking	C1	C1
Code	TR	T148
Basic ordering unit (pieces)	3000	3000

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	50	—	—	V	$I_C=50/-50 \mu A$
Collector-emitter breakdown voltage	BV_{CEO}	50	—	—	V	$I_C=1/-1mA$
Emitter-base breakdown voltage	BV_{EBO}	5	—	—	V	$I_E=50/-50 \mu A$
Collector cutoff current	I_{CBO}	—	—	0.5	μA	$V_{CB}=50/-50V$
Emitter cutoff current	I_{EBO}	—	—	0.5	μA	$V_{EB}=4/-4V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	—	0.3	V	$I_C=5/-5mA, I_E=0.25/-0.25mA$
DC current transfer ratio	h_{FE}	100	250	600	—	$V_{CE}=5/-5V, I_C=1/-1mA$
Transition frequency	f_T	—	250	—	MHz	$V_{CE}=10V, I_E=-5mA, f=100MHz$ *
Input resistance	R_i	3.29	4.7	6.11	k Ω	—

* Transition frequency of mounted transistor. PNP type negative symbols have been omitted.

(94S-815-AC143T)


Digital Transistor (Dual Digital Transistors for Power Management)

UMD12N / FMC7A

●Features

- 1) DTA144E and DTC144E transistors are housed in a UMT or SMT package.

●Circuit schematics



●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Supply voltage	V_{CC}	50	V
Input voltage	V_{IN}	40 -10	V
Output current	I_C I_O	100 30	mA
Power dissipation	UMD12N FMC7A	150 (TOTAL) 300 (TOTAL)	mW *1 *2
Junction temperature	T_J	150	°C
Storage temperature	T_{stg}	-55~150	°C

*1 120mW per element must not be exceeded. *2 200mW per element must not be exceeded. PNP type negative symbols have been omitted.

●Package, marking, and packaging specifications

Type	UMD12N	FMC7A
Package	UMT6	SMT5
Marking	D12	C7
Code	TR	T148
Basic ordering unit (pieces)	3000	3000

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Input voltage	V_i (off)	—	—	0.5	V	$V_{CC}=5/-5V, I_O=100/-100 \mu A$
	V_i (on)	3	—	—	V	$V_O=0.3/-0.3V, I_O=2/-2mA$
Output voltage	V_O (on)	—	—	0.3	V	$I_O=10/-10mA, I_E=0.5/-0.5mA$
Input current	I_i	—	—	0.18	mA	$V_i=5/-5V$
Output current	I_O (on)	—	—	0.5	μA	$V_{CC}=50/-50V, V_i=0V$
DC current gain	G_i	68	—	—	—	$I_O=5/-5mA, V_O=5/-5V$
Transition frequency	f_T	—	250	—	MHz	$V_{CC}=10/-10V, I_E=-5/5mA, f=100MHz$ *
Input resistance	R_i	32.9	47	61.1	k Ω	—
Resistance ratio	R_2/R_1	0.8	1	1.2	—	—

* Transition frequency of mounted transistor. PNP type negative symbols have been omitted.

Packages

ROHM has been manufacturing transistors since 1975. In the development of products, we constantly strive to anticipate the needs of our customers. Regarding packages, the demands of the market for compactness, low power consumption, low power dissipation and automatic mounting support are becoming ever greater, and we are strengthening our product development system to meet these needs.

●Types and features of surface-mount packages

Type	External dimensions (Units : mm)	Features
EMT3 SC-75A type		A more compact version of the UMT3 (SC-70), the EMT3 is the world's smallest transistor with a mold size of 1.6×0.8 mm. The mounting area is approximately 60% of the UMT3 and 30% of the SMT3, making it ideal for ultra-high density mounting. Mounting is possible with the same type of automatic mounting machine as the UMT3.
UMT3 SC-70 type		The UMT3 is a smaller version of the SMT3 (SC-59). The mounting area is approximately 60% of the SMT3, making it optimum for high density mounting. The taping size is the same as the SMT3, allowing use of conventional automatic mounting machines. Electrical characteristics and reliability are the same as the SMT3.
SMT3 SC-59 type		The SMT3 is a compact package suitable for small electronic devices and hybrid IC applications. With proven performance, this is one of the most basic small packages. With the exception of P_c (collector power dissipation), electrical characteristics are similar to leaded packages. Reliability is on the same level as the TO-92.
MPT3 SC-62 type		By itself the MPT3 has a P_c of 0.5 W ($T_a = 25^\circ\text{C}$), but when used on a $40 \times 40 \times 0.7$ mm ceramic board, $P_c = 2$ W ($T_c = 25^\circ\text{C}$), allowing high power to be obtained with a small package. The flat package makes it suitable for applications requiring compactness such as hybrid ICs. Available on tape for automatic mounting.

Type	External dimensions (Units : mm)	Features
CPT 3 SC-63 type		By itself the CPT3 has a P_c of 1 W ($T_a = 25^\circ\text{C}$), but a large P_c of several watts can be obtained with an appropriate mounting surface. At the same time the CPT3 is compact, making it suitable for high density mounting and hybrid ICs. Available on tape for automatic mounting. For vertical high density mounting, the leaded CPT (SC-64) type with the same mold size is also available.
PSD3		The PSD3 is a TO-220 class surface-mount package. A high P_c can be obtained with an appropriate mounting surface. Surface mounting allows a high vertical density, enabling the design of slim and compact devices. The PSD3 is available on tape for automatic mounting, and it helps improve mounting efficiency and reduce mounting cost.
SMT5 SC-74A type		The SMT5 consists of two connected transistors or digital transistors in an SMT3 (SC-59) package. The mounting area can be reduced by 50% compared to the SMT3 and the internal circuitry is complete, making this package ideal for high density mounting at half the assembly cost.
SMT6 SC-74 type		The SMT6 consists of two independent transistors or two independent digital transistors in an SMT3 (SC-59) package. The mounting area and mounting cost can be reduced by 50% compared to the SMT3, and the two transistors are independent to allow free configuration of a high density circuit.


Type	External dimensions (Units : mm)	Features
UMT5 SC-88A type	2.0±0.2 1.3±0.1 0.65 0.65 1.25±0.1 2.1±0.1 0.2+0.1 -0.05 0.15±0.05 0.9±0.1 0.7 0~0.1 0.1Min. All terminals have same dimensions	The UMT5 consists of two connected transistors or digital transistors in a UMT3 (SC-70) package. The mounting area can be reduced by 50% compared to the UMT3 and the internal circuitry is completed, making this package ideal for high density mounting at half the assembly cost.
UMT6 SC-88 type	2.0±0.2 1.3±0.1 0.65 0.65 1.25±0.1 2.1±0.1 0.2+0.1 -0.05 0.15±0.05 0.9±0.1 0.7 0~0.1 0.1Min. All terminals have same dimensions	The UMT6 consists of two independent transistors or two independent digital transistors in a UMT (SC-70) package. The mounting area and mounting cost can be reduced by 50% compared to the UMT3, and the two transistors are independent to allow free configuration of a high density circuit.

●Types and features of leaded packages

Type	External dimensions (Units : mm)	Features
SPT (SC-72 type)		The SPT is a smaller version of the conventional TO-92 type. The body size (3×4×2 mm³) has been reduced to 1/4 that of the TO-92 (5×5×4 mm³). The SPT is available on tape for automatic insertion, and less space is occupied on the printed circuit board than the TO-92. Reliability is the same as the TO-92.
FTR		SIL type with a height of 3.4 mm and a lead pitch of 2.54 mm.
FTL		The FTL is a radial taping version of the highly popular FTR. This enables automatic high-density mounting with a radial insertion machine.
ATR (SC-71 type)		SC-71type with a height of 4.4 mm and a P_c=1W type.

EXPLANATION

Type	External dimensions (Units : mm)	Features
ATV		The ATV is a radial taping version of the highly popular ATR. This enables automatic high-density mounting with a radial insertion machine.
TO-92 (SC-43 type)		The SC-43 is for general purpose small signals.
TO-126FP		The TO-126FP is an isolation type package based on a TO-126 full mold. In addition to the features of the TO-126, molded heat sink fins allow easy isolation of the heat sink.
TO-220FP (SC-67 type)		The TO-220FP is an isolation type package based on a TO-220 full mold. In addition to the features of the TO-126 and TO-220, molded heat sink fins allow easy isolation of the heat sink.

Type	External dimensions (Units : mm)	Features
TO-220FN	 Technical drawing of the TO-220FN package showing top and side views with dimensions in mm: - Top view dimensions: 10.0^{+0.3}/_{-0.1} (width), 15.0^{+0.4}/_{-0.2} (height), 12.0^{+0.2}/_{-0.2} (height), 8.0^{+0.2}/_{-0.2} (height), 5.0^{+0.2}/_{-0.2} (height), 2.54^{+0.5}/_{-0.5} (width), 2.54^{+0.5}/_{-0.5} (width), 0.75^{+0.1}/_{-0.05} (width), 2.6^{+0.5}/_{-0.5} (width), 1.2 (width), 1.3 (width), 0.8 (width), $\phi 3.2 \pm 0.2$ (hole diameter). - Side view dimensions: 4.5^{+0.3}/_{-0.1} (height), 2.8^{+0.2}/_{-0.1} (height), 2.6^{+0.5}/_{-0.5} (width).	The TO-220FN features the same performance as the TO-220FP with approximately 2 mm less height, allowing the design of slimmer devices. Furthermore, the elimination of support pins in the fin (collector electrode) solves short-circuiting problems with neighboring components and the chassis. To make the height to the installation hole the same as the TO-220FP, it can be replaced as is from the TO-220FP.

EXPLANATION