


UM9151 Pulse Dialer

FEATURES

- Direct Telephone Line Operation
- 4 x 3 Matrix Single Contact Keyboard
- Supply Voltage Range 2.5V to 5V
- Inexpensive RC Oscillator
- Low Power Standby Mode for Redial
- 22 Digit Capacity for Redial
- 18 Lead Dual-in-Line Package
- Redial with Either * or # Key
- Dialer Reset for Line Power Break > 200 msec
- Pin Selectable Inter-Digital Pause (IDP)
- Pin Selectable Make/Break (M/B)
- High Speed Test Capability

PIN CONFIGURATION



UM9151-3 Pulse Dialer

FEATURES

- Direct Telephone Line Operation
- 4 x 3 Matrix Keyboard Interface
- Supply Voltage Range 2.0V to 5.5V
- Inexpensive RC Oscillator
- Low Power Standby Mode for Redial
- 22 Digit Capacity for Redial
- Redial with Either * or # Key
- Dialer Reset for Line Power Break > 200 msec.
- Inter-Digit Pause 800ms (1000ms Mask Option)
- Selectable Make/Break Ratio
- Provision for Rapid Testing (High Speed Test Capacity)
- 16 Lead Dual-in-Line Package

PIN CONFIGURATION

