

Standard Range — Weather Resistant Nylon 6/6

This range of non-releasable TY-RAP® cable ties offers the user a wide range of cable tie sizes and tensile strengths to choose from.

The range features the exclusive steel barb locking device for superior tie performance.

This range is recommended for general wiring use in all outdoor applications and in ultra-violet environments.

For material performance details please consult page 5.

TECHNICAL DETAILS

* Preferred Stock Items

Catalogue Numbers		Bundle Diameter	Tie Length (mm)	Tie Width (mm)	Minimum Tensile Unlocking Force (N)	Installing Tools
						
* TY23MX		2-16	92	2.4	80	WT1 WT193A
TY232MX		2-50	200	2.4	80	WT1 WT193A
TY234MX		2-102	356	2.4	80	WT1 WT193A
						
* TY24MX		2-29	140	3.6	135	WT1 WT193A
TY242MX		2-50	208	3.6	180	WT1 WT193A
* TY26MX		2-76	281	3.6	180	WT1 WT193A
TY244MX		2-103	368	3.6	180	WT1 WT193A
						
* TY25MX		3.5-45	186	4.8	220	WT1 WT193A
TY253MX		3.5-78	293	4.8	220	WT1 WT193A
* TY28MX		3.5-102	360	4.8	220	WT1 WT193A
						
TY272MX		6-50	223	7.6	540	WT2 WT197
* TY27MX		6-90	338	7.6	540	WT2 WT197
* TY29MX		6-229	762	6.9	540	WT2 WT197

Material: Weather Resistant Nylon 6/6