




XFEB201209 SERIES CHIP BEADS

- * TAPE AND REEL PACKAGING FOR HIGH VOLUME MANUFACTURING
4000 PCS PER 7" REEL
- * FOR DC/DC CONVERTERS, DC/AC INVERTERS, VRM APPLICATIONS
- * TEMP. RISE; 15°C TYPICAL ABOVE 50°C AMBIENT
- * OPERATING TEMP.: -40°C TO +125°C
- * RoHS Compliant

Mechanical Dimensions:



Schematic:



Part Number	IMPEDANCE (Ohms)	Test Frequency (MHz)	RDC Max (Ohms)	IDC Max (mA)
XFEB201209-070	7±25%	100	0.10	600
XFEB201209-090	9±25%	100	0.10	600
XFEB201209-100	10±25%	100	0.20	500
XFEB201209-110	11±25%	100	0.10	600
XFEB201209-170	17±25%	100	0.10	500
XFEB201209-320	32±25%	100	0.20	500
XFEB201209-600	60±25%	100	0.30	400
XFEB201209-700	70±25%	100	0.30	400
XFEB201209-800	80±25%	100	0.40	400
XFEB201209-121	120±25%	100	0.40	200
XFEB201209-151	150±25%	100	0.50	200
XFEB201209-221	220±25%	100	0.60	200
XFEB201209-301	300±25%	100	0.90	200
XFEB201209-401	400±25%	100	0.90	200
XFEB201209-501	500±25%	100	1.00	200
XFEB201209-601	600±25%	100	1.00	200
XFEB201209-102	1000±25%	100	1.00	100
XFEB201209-152	1500±25%	50	1.00	100

Graphs

