

XFMRs, Inc.

SPECIFICATION FOR APPROVAL

XFMRs P/N : XFEB453215-800-6A				Rev: A	
DIMENSION : (m/m)				A	$\phi 4.5 \pm 0.2$ m/m
				B	3.2 ± 0.2 m/m
				C	1.5 ± 0.2 m/m
				D	0.5 ± 0.3 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
				K	m/m
				L	m/m
				M	m/m
				N	m/m
				O	m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS	
Z	$80 \pm 25\%$ Ohms	TEST FREQ.	100 MHz	○ HP 34401A MULTIMETER ○ HP 4195 NETWORKS/SPECTRUM ANALYZER ○ HP 42841 BIAS CURRENT SOURCE ○ HP 4285A LCR METER ○ HP 4286A RF LCR METER ● HP 4291A RF IMPEDANCE / MATERIAL ANALYZER ○ HP 4338A MILLION OHM METER ○ HP 6632A DC POWER SUPPLY ○ HP4284A PRECISION LCR METER	
Q		TEST FREQ.	MHz		
SRF		TEST FREQ.	MHz		
Rdc	0.01 Ohms Max	TEST FREQ.	MHz		
Idc	6000mA _{dc} Max	TEST FREQ.	MHz		
		TEST FREQ.			
DRAWN BY :		CHECKED BY :		APPROVED BY :	
BUDDY WOODS		JOE HUFF		TONY IMBURGIA	