



Z SERIES DC-DC CONVERTER


ZW3 3W Dual output

SUPERTEK


Z series DC-DC converter is designed for Small size, high reliability and high quality use.

- Isolated output.
- Over current protection.
- Small and compact size.


NAMING

ZW30512






SPECIFICATIONS

	MODEL	ZW30512	ZW30515	ZW31212	ZW31215	ZW32412	ZW32415
INPUT	VOLTAGE (V)	5(4.5~6.0)		12(10~15)		24(20~30)	
	EFFICIENCY (%)	65typ		70typ		74typ	
OUTPUT	VOLTAGE (V)	±12	±15	±12	±15	±12	±15
	CURRENT (A)	0.12	0.1	0.12	0.1	0.12	0.1
	REGULATION, LINE (mV)	60max	75max	60max	75max	60max	75max
	REGULATION, LOAD (mV)	600max	750max	600max	750max	600max	750max
	RIPPLE (mVp-p)	120max	120max	120max	120max	120max	120max
	NOISE (mVp-p)	120max	120max	120max	120max	120max	120max
	TEMPERATURE DRIFTING (mV) 0~+50°C	120max	150max	120max	150max	120max	150max
	OUTPUT VOLTAGE SETTING (%)	±5 max of nominal Voltage					
PROTECTION CIRCUIT		Works over 105% of rating and recovers automatically					
ELECTRICALLY ISOLATED	HIGH POT.	Input-Output, Input-Case, Output-Case AC500V 1minute (At room Temp. and Humid.)					
	ISOLATION	Input-Output, Input-Case, Output-Case DC500V 50M ohm (At room Temp. and Humid.)					
ENVIRONMENT	OPERATING TEMP. AND HUMID.	0~+50°C, 20~90%RH (Non condensing)					
	STORAGE TEMP. AND HUMID.	-20~+75°C, 20~90%RH (Non condensing)					
	VIBRATION	10~55Hz and 2G 3minutes periods. 30 minutes along X, Y and Z directions.					
	IMPACT	20G 11ms, once each X, Y, Z directions.					

* No parallel operation is permitted.

ZW3**SUPERTEK****EXTERNAL VIEW**

(mm)
* Weight : 35g or less.

STATIC CHARACTERISTICS (ZW30515)**RISE TIME & FALL TIME (ZW30515)****OUTPUT CURRENT V.S. OUTPUT VOLTAGE (ZW30515)****BLOCK DIAGRAM**

* Z series switching power supply is warranted for one year period.

* Above all specifications are subject to change for improvement without notice.