

VACUUM SWITCH SERIES ZS

VACUUM SWITCH SERIES ZSE1

✓ Solid state


Quick response - 10 ms

Compact size

Semiconductor type pressure sensor


NPN and PNP versions







DIMENSIONS

VACUUM SWITCH SERIES ZSE1










TOCKED PRODUCTS FOR A LIST OF STOCKED PRODUCTS, PLEASE SEE THE CURRENT SMC PRICE LIST

SPECIFICATIONS

TECHNICAL

Fluid	Air	
Setting pressure range	0~760mmHg	
Hysteresis	Adjustable 1~10% of range	
Accuracy	±3% F.S. (5-40°C) ±5% F.S. (0-60°C)	
Supply voltage	12-24VDC (Ripple ±10% or less)	
Output	Open collector (NPN/PNP) 30V Max. 80mA	
Trimmer adjustment	200°	
Indicator light	Lighting under ON condition	
Power consumption	17mA 24VDC (under ON condition)	
Max. pressure	2 Bar	
Temperature range	0 ~ 60°C	


CIRCUIT ZSE1



ZSE1-•--55

Switch Type 55L

Switch Type 15L



VACUUM SWITCH SERIES ZS

Interface plate for ZM Ejector P31806-01.....(blank) P31806-02 (use with switch)

STOCKED PRODUCTS FOR A LIST OF STOCKED PRODUCTS, PLEASE SEE THE CURRENT SMC PRICE LIST







VACUUM SWITCH SERIES ZS





ZM VACUUM EJECTOR TYPE

VACUUM SWITCH SERIES ZSM1 DIAPHRAGM TYPE

✓ 100 ms response time ✓ Compact size

TECHNICAL **SPECIFICATIONS**

Model	ZSM1-115	ZSM1-121
Electrical switch type	Solid state NPN	Contact (reed switch)
Fluid	Air, Inert gases	
Max. pressure	0.5MPa	
Setting pressure range	- 200 ~ - 600mmHg	
Adustment screw	Range = 18 turns	
Max. hysteresis	110mmHg	150mmHg
Temperature range	5 ~ 60°C	
Supply voltage	10 ~ 26VDC	100VAC
Indicator light	Lighting under ON condition (LED)	
Wire	3wire	2wire
Port size	⅓ (Male)	

CIRCUIT ZSM1-115





ZSM1-121




DIMENSIONS


VACUUM SWITCH SERIES ZSM1 (THREADED TYPE)







21L ... Contact reed



How To VACUUM SWITCH SERIES ZSM1

 $ZSM1 - \bigcirc \bigcirc - \bigcirc$ CONNECTION -SWITCH TYPE 15L ... Solid state (NPN) 0ZM Ejector mounting

STOCKED PRODUCTS FOR A LIST OF STOCKED PRODUCTS, PLEASE SEE THE CURRENT SMC PRICE LIST

CONTACT PROTECTION BOX

Diaphragm type switches have no built-in contact protection circuit. Use this box for induction load, 5m or more lead wire length and 100V AC.



CONTACT PROTECTION BOX/INTERNAL CIRCUIT

	CD-P11	
o Surge	Choke'	—o Red lead wire
suppressor	Coil	—o Black lead wire
0		O Diack lead wife

VACUUM SWITCH SERIES ZSE1

Interface plate for ZM Ejector P31806-01.....(blank)
P31806-02.....(use with switch) CD-P11Contact protection box

STOCKED PRODUCTS FOR A LIST OF STOCKED PRODUCTS, PLEASE SEE THE CURRENT SMC PRICE LIST



