



ANZAC RF & CELLULAR COMPONENTS

RF Control Devices (continued)

SP3T Switches									
MODEL NO.	FREQUENCY RANGE (MHz)	Si/GaAs	INSERTION LOSS (dB) TYP	ISOLATION (dB) TYP	VSWR TYP	Term	Drive	Case Style	PRICE \$ (5 - 9)
SW-123	10-1000	Si	0.6	60	1.1:1	OPEN	TTL	DI-2	317.
SW-163	20-1500	Si	0.5	45	1.2:1	50 OHM	TTL	DI-2	354.
SW-241	5-2000	GaAs	1.7	60	1.2:1	50 OHM	TTL	DI-5	393.
SW-242	5-2000	GaAs	1.0	60	1.2:1	OPEN	TTL	DI-5	352.
SW-244	5-2000	GaAs	1.7	60	1.2:1	50 OHM	CMOS	DI-5	393.
SW-245	5-2000	GaAs	1.1	60	1.2:1	OPEN	CMOS	DI-5	352.
SW-247	5-2000	GaAs	1.0	55	1.2:1	50 OHM	TTL	FP-17	418.
SW-248	5-2000	GaAs	1.0	55	1.2:1	OPEN	TTL	FP-17	375.
SW-251	5-2000	GaAs	1.0	55	1.2:1	50 OHM	CMOS	FP-17	418.
SW-252	5-2000	GaAs	1.0	55	1.2:1	OPEN	CMOS	FP-17	375.
SW-113	10-2000	Si	1.3	60	1.1:1	OPEN	TTL	DI-2	333.
SW-133	200-2000	Si	0.6	45	1.2:1	OPEN	TTL	DI-2	319.
SP4T Switches									
SW-124	10-1000	Si	0.6	60	1.1:1	OPEN	TTL	DI-2	356.
SW-164	20-1500	Si	0.9	60	1.1:1	50 OHM	TTL	DI-2	392.
SW-415	DC-2000	GaAs	1.0	45	1.4:1	50 OHM	CMOS	FP-25	265.
SW-254	5-2000	GaAs	1.0	55	1.2:1	50 OHM	TTL	DI-5	435.
SW-255	5-2000	GaAs	1.0	55	1.2:1	OPEN	TTL	DI-5	395.
SW-257	5-2000	GaAs	1.0	55	1.2:1	50 OHM	CMOS	DI-5	435.
SW-258	5-2000	GaAs	1.0	55	1.2:1	OPEN	CMOS	DI-5	395.
SW-261	5-2000	GaAs	1.0	55	1.2:1	50 OHM	TTL	FP-17	462.
SW-262	5-2000	GaAs	1.0	55	1.2:1	OPEN	TTL	FP-17	420.
SW-264	5-2000	GaAs	1.0	55	1.2:1	50 OHM	CMOS	FP-17	462.
SW-265	5-2000	GaAs	1.0	55	1.2:1	OPEN	CMOS	FP-17	420.
SW-114	10-2000	Si	1.2	80	1.1:1	OPEN	TTL	DI-2	375.
SW-369	20-2000	GaAs	1.8	50	1.4:1	50 OHM	CMOS	FP-26	248.
SW-134	200-2000	Si	0.6	45	1.2:1	OPEN	TTL	DI-2	356.
SW-243	DC-4000	GaAs	0.7	40	1.2:1	OPEN	0/-5V	CR-4	113.
SP6T Switches Selection Guide									
SW-284	DC-2000	GaAs	1.5	35	1.2:1	50 OHM	TTL	FP-27	550.
DPDT Switches Selection Guide									
SW-355	DC-2000	GaAs	0.5	30	1.3:1	OPEN	0/-5V	TO-5-3	81.
SW-281	DC-4000	GaAs	0.5	50	1.15:1	OPEN	0/-5V	CR-4	90.
Transfer Switches Selection Guide									
SW-362	DC-2000	GaAs	1.1	35	1.3:1	OPEN	0/-5V	TO-5-4	75.
SW-119	10-2000	Si	0.9	50	1.1:1	OPEN	TTL	DI-4	314.
SW-283	DC-3000	GaAs	0.8	55	1.15:1	OPEN	0/5V	CR-4	158.
Solid State Relay Switch Selection Guide									
SW-368	DC-2000	GaAs	0.5	30	1.2:1	OPEN	+5/-5V	TO-5-4	58.

*CASE STYLE: FP = FLATPACK; DI = DUAL INLINE; TO = TO-5/8; CR = CERAMIC

**DENOTES SURFACE MOUNT

PRICE AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

BOLD TYPE = NEW PRODUCTS