

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Pilot lights, with double insulated bezel
Sub-assemblies, ZB5-A : bodies

References

To combine with heads : see page 2/31

Complete bodies (fixing collar + light block with integral LED)

Light source	Supply voltage	Colour of light source	Reference	Weight
	V			kg

Screw clamp terminal connections

Integral LED Protected LED	≈ 24	White	ZB5-AVB1	0.022
		Green	ZB5-AVB3	0.022
		Red	ZB5-AVB4	0.022
		Yellow	ZB5-AVB5	0.022
		Blue	ZB5-AVB6	0.022
	~ 110...120	White	ZB5-AVG1	0.022
		Green	ZB5-AVG3	0.022
		Red	ZB5-AVG4	0.022
		Yellow	ZB5-AVG5	0.022
		Blue	ZB5-AVG6	0.022
	~ 230...240	White	ZB5-AVM1	0.022
		Green	ZB5-AVM3	0.022
		Red	ZB5-AVM4	0.022
		Yellow	ZB5-AVM5	0.022
		Blue	ZB5-AVM6	0.022

Plug-in connector (1)

Integral LED Protected LED	≈ 24	White	ZB5-AVB14	0.021
		Green	ZB5-AVB34	0.021
		Red	ZB5-AVB44	0.021
		Yellow	ZB5-AVB54	0.021
		Blue	ZB5-AVB64	0.021
	~ 110...120	White	ZB5-AVG14	0.021
		Green	ZB5-AVG34	0.021
		Red	ZB5-AVG44	0.021
		Yellow	ZB5-AVG54	0.021
		Blue	ZB5-AVG64	0.021
	~ 230...240	White	ZB5-AVM14	0.021
		Green	ZB5-AVM34	0.021
		Red	ZB5-AVM44	0.021
		Yellow	ZB5-AVM54	0.021
		Blue	ZB5-AVM64	0.021

(1) Connecting cable for plug-in connector light blocks : see page 2/42.

2



ZB5-AV000



ZB5-AV004

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Pilot lights, with double insulated bezel
Sub-assemblies, ZB5-A : bodies + heads

References

Complete bodies (fixing collar + light block for BA 9s incandescent bulb, neon or LED)

Supply	Light source	Supply voltage	Colour of light source	Reference	Weight
V					kg
Screw clamp terminal connections					
Direct supply	BA 9s bulb 2.4 W max. Not included (1)	≤ 250	–	ZB5-AV6	0.022
Via integral transformer 1.2 VA, 6 V secondary	BA 9s incandescent bulb included	~ 110...120 50/60 Hz	–	ZB5-AV3	0.099
		~ 230...240 50/60 Hz	–	ZB5-AV4	0.099
		~ 400 50 Hz	–	ZB5-AV5	0.099
		~ 440...480 60 Hz	–	ZB5-AV8	0.099
		~ 550...600 60 Hz	–	ZB5-AV9	0.099
	BA 9s base fitting LED included	~ 110...120 50/60 Hz	White	ZB5-AV3D1	0.102
			Green	ZB5-AV3D3	0.102
			Red	ZB5-AV3D4	0.102
			Yellow	ZB5-AV3D5	0.102
			Blue	ZB5-AV3D6	0.102
		~ 400 50 Hz	White	ZB5-AV5D1	0.102
			Green	ZB5-AV5D3	0.102
			Red	ZB5-AV5D4	0.102
			Yellow	ZB5-AV5D5	0.102
			Blue	ZB5-AV5D6	0.102



ZB5-AV6



ZB5-AV3

Heads

Shape of head	For use with body comprising light source type	Colour of lens	Reference	Weight
kg				
	Integral LED only	White	ZB5-AV013	0.017
		Green	ZB5-AV033	0.017
		Red	ZB5-AV043	0.017
		Yellow	ZB5-AV053	0.017
		Blue	ZB5-AV063	0.017
		5 colours (2)	ZB5-AV003	0.023
		5 colours (3)	ZB5-AV003S	0.023
	For BA 9s incandescent bulb, neon or LED only	White	ZB5-AV01	0.018
		Green	ZB5-AV03	0.018
		Red	ZB5-AV04	0.018
		Yellow	ZB5-AV05	0.018
		Blue	ZB5-AV06	0.018
		Clear	ZB5-AV07	0.018
	Integral LED only	White	ZB5-CV013	0.020
		Green	ZB5-CV033	0.020
		Red	ZB5-CV043	0.020
		Yellow	ZB5-CV053	0.020
		Blue	ZB5-CV063	0.020
		5 colours (2)	ZB5-CV003	0.028



ZB5-AV053



ZB5-AV01



ZB5-CV063

(1) Bulb to be ordered separately.

(2) 5 different colour lenses included with head (white, green, red, yellow, blue) for insertion of legend.

For legend ordering information see page 2/50.

(3) 5 different colour grooved lenses included with head (white, green, red, yellow, blue) for use in bright ambient light conditions (outdoors with sun for example).

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : bodies

References

To combine with heads : see pages 2/37 to 2/39

Complete bodies (fixing collar + single contact block + light block with integral LED)

Light source	Supply voltage	Type of contact (1)		Colour of light source	Reference	Weight
						
	V	N/O	N/C			kg

Screw clamp terminal connections


Integral LED 	~ 24	1	–	White	<u>ZB5-AW0B11</u>	0.032
				Green	<u>ZB5-AW0B31</u>	0.032
				Red	<u>ZB5-AW0B41</u>	0.032
				Yellow	<u>ZB5-AW0B51</u>	0.032
				Blue	<u>ZB5-AW0B61</u>	0.032
		–	1	White	<u>ZB5-AW0B12</u>	0.032
				Green	<u>ZB5-AW0B32</u>	0.032
				Red	<u>ZB5-AW0B42</u>	0.032
				Yellow	<u>ZB5-AW0B52</u>	0.032
				Blue	<u>ZB5-AW0B62</u>	0.032
		2	–	White	<u>ZB5-AW0B13</u>	0.042
				Green	<u>ZB5-AW0B33</u>	0.042
				Red	<u>ZB5-AW0B43</u>	0.042
				Yellow	<u>ZB5-AW0B53</u>	0.042
				Blue	<u>ZB5-AW0B63</u>	0.042
		1	1	White	<u>ZB5-AW0B15</u>	0.042
				Green	<u>ZB5-AW0B35</u>	0.042
				Red	<u>ZB5-AW0B45</u>	0.042
				Yellow	<u>ZB5-AW0B55</u>	0.042
				Blue	<u>ZB5-AW0B65</u>	0.042
	~ 110...120	1	–	White	<u>ZB5-AW0G11</u>	0.032
				Green	<u>ZB5-AW0G31</u>	0.032
				Red	<u>ZB5-AW0G41</u>	0.032
				Yellow	<u>ZB5-AW0G51</u>	0.032
				Blue	<u>ZB5-AW0G61</u>	0.032
		–	1	White	<u>ZB5-AW0G12</u>	0.032
				Green	<u>ZB5-AW0G32</u>	0.032
				Red	<u>ZB5-AW0G42</u>	0.032
				Yellow	<u>ZB5-AW0G52</u>	0.032
				Blue	<u>ZB5-AW0G62</u>	0.032

(1) Can be fitted with additional contact blocks : see page 2/40.

2



ZB5-AW0B01



ZB5-AW0B03

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : bodies


References (continued)

To combine with heads : see pages 2/37 to 2/39

Complete bodies (Fixing collar + single contact block + light block with integral LED) (continued)

Light source	Supply voltage	Type of contact (1)		Colour of light source	Reference	Weight
						
	V	N/O	N/C			kg
Screw clamp terminal connections (continued)						
Integral LED 	~ 110...120	2	–	White	<u>ZB5-AW0G13</u>	0.042
				Green	<u>ZB5-AW0G33</u>	0.042
				Red	<u>ZB5-AW0G43</u>	0.042
				Yellow	<u>ZB5-AW0G53</u>	0.042
				Blue	<u>ZB5-AW0G63</u>	0.042
		1	1	White	<u>ZB5-AW0G15</u>	0.042
				Green	<u>ZB5-AW0G35</u>	0.042
				Red	<u>ZB5-AW0G45</u>	0.042
				Yellow	<u>ZB5-AW0G55</u>	0.042
				Blue	<u>ZB5-AW0G65</u>	0.042
	~ 230...240	1	–	White	<u>ZB5-AW0M11</u>	0.032
				Green	<u>ZB5-AW0M31</u>	0.032
				Red	<u>ZB5-AW0M41</u>	0.032
				Yellow	<u>ZB5-AW0M51</u>	0.032
				Blue	<u>ZB5-AW0M61</u>	0.032
		–	1	White	<u>ZB5-AW0M12</u>	0.032
				Green	<u>ZB5-AW0M32</u>	0.032
				Red	<u>ZB5-AW0M42</u>	0.032
				Yellow	<u>ZB5-AW0M52</u>	0.032
				Blue	<u>ZB5-AW0M62</u>	0.032
		2	–	White	<u>ZB5-AW0M13</u>	0.042
				Green	<u>ZB5-AW0M33</u>	0.042
				Red	<u>ZB5-AW0M43</u>	0.042
				Yellow	<u>ZB5-AW0M53</u>	0.042
				Blue	<u>ZB5-AW0M63</u>	0.042
		1	1	White	<u>ZB5-AW0M15</u>	0.042
				Green	<u>ZB5-AW0M35</u>	0.042
				Red	<u>ZB5-AW0M45</u>	0.042
				Yellow	<u>ZB5-AW0M55</u>	0.042
				Blue	<u>ZB5-AW0M65</u>	0.042

(1) Can be fitted with additional contact blocks : see page 2/40.



ZB5-AW0...3



ZB5-AW0...1

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : bodies

References (continued)

To combine with heads : see pages 2/37 to 2/39

Complete bodies (fixing collar + single contact block + light block with integral LED) (continued)

Light source	Supply voltage	Type of contact (1)		Colour of light source	Reference	Weight
						
	V	N/O	N/C			kg
Plug-in connector (2)						
Integral LED 	≈ 24	1	–	White	ZB5-AW0B114	0.028
				Green	ZB5-AW0B314	0.028
				Red	ZB5-AW0B414	0.028
				Yellow	ZB5-AW0B514	0.028
				Blue	ZB5-AW0B614	0.028
		–	1	White	ZB5-AW0B124	0.028
				Green	ZB5-AW0B324	0.028
				Red	ZB5-AW0B424	0.028
				Yellow	ZB5-AW0B524	0.028
				Blue	ZB5-AW0B624	0.028
		2	–	White	ZB5-AW0B134	0.035
				Green	ZB5-AW0B334	0.035
				Red	ZB5-AW0B434	0.035
				Yellow	ZB5-AW0B534	0.035
				Blue	ZB5-AW0B634	0.035
		1	1	White	ZB5-AW0B154	0.035
				Green	ZB5-AW0B354	0.035
				Red	ZB5-AW0B454	0.035
				Yellow	ZB5-AW0B554	0.035
				Blue	ZB5-AW0B654	0.035
	~ 110...120	1	–	White	ZB5-AW0G114	0.028
				Green	ZB5-AW0G314	0.028
				Red	ZB5-AW0G414	0.028
				Yellow	ZB5-AW0G514	0.028
				Blue	ZB5-AW0G614	0.028
		–	1	White	ZB5-AW0G124	0.028
				Green	ZB5-AW0G324	0.028
				Red	ZB5-AW0G424	0.028
				Yellow	ZB5-AW0G524	0.028
				Blue	ZB5-AW0G624	0.028

(1) Can be fitted with additional contact blocks : see page 2/42.

(2) Connecting cables and connector for plug-in connector electrical blocks : see page 2/42.



ZB5-AW0●●24



ZB5-AW0●●34

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : bodies

References (continued)

To combine with heads : see pages 2/37 to 2/39

Complete bodies (fixing collar + single contact block + light block with integral LED) (continued)

Light source	Supply voltage	Type of contact (1)		Colour of light source	Reference	Weight
						
	V	N/O	N/C			kg
Plug-in connector (2) (continued)						
Integral LED 	~ 110...120	2	–	White	<u>ZB5-AW0G134</u>	0.035
				Green	<u>ZB5-AW0G334</u>	0.035
				Red	<u>ZB5-AW0G434</u>	0.035
				Yellow	<u>ZB5-AW0G534</u>	0.035
				Blue	<u>ZB5-AW0G634</u>	0.035
		1	1	White	<u>ZB5-AW0G154</u>	0.035
				Green	<u>ZB5-AW0G354</u>	0.035
				Red	<u>ZB5-AW0G454</u>	0.035
				Yellow	<u>ZB5-AW0G554</u>	0.035
				Blue	<u>ZB5-AW0G654</u>	0.035
	~ 230...240	1	–	White	<u>ZB5-AW0M114</u>	0.028
				Green	<u>ZB5-AW0M314</u>	0.028
				Red	<u>ZB5-AW0M414</u>	0.028
				Yellow	<u>ZB5-AW0M514</u>	0.028
				Blue	<u>ZB5-AW0M614</u>	0.028
		–	1	White	<u>ZB5-AW0M124</u>	0.028
				Green	<u>ZB5-AW0M324</u>	0.028
				Red	<u>ZB5-AW0M424</u>	0.028
				Yellow	<u>ZB5-AW0M524</u>	0.028
				Blue	<u>ZB5-AW0M624</u>	0.028
		2	–	White	<u>ZB5-AW0M134</u>	0.035
				Green	<u>ZB5-AW0M334</u>	0.035
				Red	<u>ZB5-AW0M434</u>	0.035
				Yellow	<u>ZB5-AW0M534</u>	0.035
				Blue	<u>ZB5-AW0M634</u>	0.035
		1	1	White	<u>ZB5-AW0M154</u>	0.035
				Green	<u>ZB5-AW0M354</u>	0.035
				Red	<u>ZB5-AW0M454</u>	0.035
				Yellow	<u>ZB5-AW0M554</u>	0.035
				Blue	<u>ZB5-AW0M654</u>	0.035

(1) Can be fitted with additional contact blocks : see page 2/42.

(2) Connecting cables and connector for plug-in connector electrical blocks : page 2/42.



ZB5-AW0G34



ZB5-AW0G24

Control and signalling units Ø 22

Harmony style 5

Illuminated pushbuttons and switches, with double insulated bezel

Sub-assemblies, ZB5-A : bodies

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

References (continued)

To combine with heads : see pages 2/37 to 2/39

Complete bodies (fixing collar + single contact block + light block for BA 9s incandescent bulb, neon or LED)

Supply	Light source	Supply voltage	Type of contact (1)		Colour of light source	Reference	Weight
		V	N/O	N/C			kg
Screw clamp terminal connections							
Direct supply	BA 9s 2.4 W max. bulb Not included (2)	≤ 250	1	–	–	<u>ZB5-AW061</u>	0.031
			–	1	–	<u>ZB5-AW062</u>	0.031
			2	–	–	<u>ZB5-AW063</u>	0.041
			1	1	–	<u>ZB5-AW065</u>	0.041
	BA 9s 2.4 W max. incandescent bulb included	≤ 120	1	–	–	<u>ZB5-AW061120</u>	0.034
			–	1	–	<u>ZB5-AW062120</u>	0.034
			2	–	–	<u>ZB5-AW063120</u>	0.043
			1	1	–	<u>ZB5-AW065120</u>	0.043
Via integral transformer 1.2 VA, 6V secondary	BA 9s incandescent bulb included	~ 110...120 50/60 Hz	1	–	–	<u>ZB5-AW031</u>	0.110
			1	1	–	<u>ZB5-AW035</u>	0.119
		~ 230...240 50/60 Hz	1	–	–	<u>ZB5-AW041</u>	0.110
			1	1	–	<u>ZB5-AW045</u>	0.119
		~ 400 - 50 Hz	1	–	–	<u>ZB5-AW051</u>	0.110
			1	1	–	<u>ZB5-AW055</u>	0.119
	BA 9s base fitting LED included	~ 110...120 50/60 Hz	1	1	White	<u>ZB5-AW03D15</u>	0.119
					Green	<u>ZB5-AW03D35</u>	0.119
					Red	<u>ZB5-AW03D45</u>	0.119
					Yellow	<u>ZB5-AW03D55</u>	0.119
					Blue	<u>ZB5-AW03D65</u>	0.119
		~ 400 - 50 Hz	1	1	White	<u>ZB5-AW05D15</u>	0.120
					Green	<u>ZB5-AW05D35</u>	0.120
					Red	<u>ZB5-AW05D45</u>	0.120
					Yellow	<u>ZB5-AW05D55</u>	0.120
					Blue	<u>ZB5-AW05D65</u>	0.120


(1) Can be fitted with additional contact blocks : see page 2/40.

(2) Bulb to be ordered separately : see page 2/52.

2



ZB5-AW065



ZB5-AW035

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : heads

References (continued)

To combine with bodies : see pages 2/32 to 2/36

Heads for spring return illuminated pushbuttons

Shape of head	Type of push	Colour	Reference	Weight kg
---------------	--------------	--------	-----------	-----------

Only for use with bodies comprising a light block with integral LED. Can be used with XAL control station, see page 3/10.



ZB5-AW313

	Flush	White	ZB5-AW313	0.017
		Green	ZB5-AW333	0.017
		Red	ZB5-AW343	0.017
		Yellow	ZB5-AW353	0.017
		Blue	ZB5-AW363	0.017



ZB5-AW363

	Flush with illuminated ring	White	ZB5-AW913	0.016
		Green	ZB5-AW933	0.016
		Red	ZB5-AW943	0.016
		Yellow	ZB5-AW953	0.016
		Blue	ZB5-AW963	0.016

	Flush with clear boot	White	ZB5-AW513	0.019
		Green	ZB5-AW533	0.019
		Red	ZB5-AW543	0.019
		Yellow	ZB5-AW553	0.019
		Blue	ZB5-AW563	0.019

	Flush for insertion of legend	White	ZB5-AA18	0.018
		Green	ZB5-AA38	0.018
		Red	ZB5-AA48	0.018
		Yellow	ZB5-AA58	0.018
		Blue	ZB5-AA68	0.018



ZB5-AW143

	Projecting	White	ZB5-AW113	0.018
		Green	ZB5-AW133	0.018
		Red	ZB5-AW143	0.018
		Yellow	ZB5-AW153	0.018
		Blue	ZB5-AW163	0.018

	Flush for insertion of legend	White	ZB5-CW313	0.023
		Green	ZB5-CW333	0.023
		Red	ZB5-CW343	0.023
		Yellow	ZB5-CW353	0.023
		Blue	ZB5-CW363	0.023



ZB5-CW113

	Projecting for insertion of legend	White	ZB5-CW113	0.024
		Green	ZB5-CW133	0.024
		Red	ZB5-CW143	0.024
		Yellow	ZB5-CW153	0.024
		Blue	ZB5-CW163	0.024

Only for use with bodies comprising a light block for a BA 9s incandescent bulb, neon or LED



ZB5-AW33

	Flush	White	ZB5-AW31	0.018
		Green	ZB5-AW33	0.018
		Red	ZB5-AW34	0.018
		Yellow	ZB5-AW35	0.018
		Blue	ZB5-AW36	0.018
		Clear	ZB5-AW37	0.018

	Projecting	White	ZB5-AW11	0.017
		Green	ZB5-AW13	0.017
		Red	ZB5-AW14	0.017
		Yellow	ZB5-AW15	0.017
		Blue	ZB5-AW16	0.017
		Clear	ZB5-AW17	0.017

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : heads

References (continued)

To combine with bodies : see pages 2/32 to 2/36

Heads with pilot light for double-headed spring return pushbuttons (IP 40) (1)

Shape of head	Description	Colour of pushes	Colour of pilot light	Reference	Weight kg
---------------	-------------	------------------	-----------------------	-----------	-----------

Only for use with bodies comprising a light block with integral LED (without function marking on push)

	1 flush push 1 central pilot light 1 flush push	Black Red	Clear (2)	ZB5-AW812743	0.022
		Green Red	Clear (2)	ZB5-AW813743	0.022
		White Black	Clear (2)	ZB5-AW811723	0.022

	1 flush push 1 central pilot light 1 projecting push	Black Red	Clear (2)	ZB5-AW832743	0.021
		Green Red	Clear (2)	ZB5-AW833743	0.021
		White Black	Clear (2)	ZB5-AW831723	0.021

Only for use with bodies comprising a light block with integral LED (with function marking on push)

	1 flush push (marked "I") 1 central pilot light 1 flush push (marked "O")	Black Red	Clear (2)	ZB5-AW822743	0.022
		Green Red	Clear (2)	ZB5-AW823743	0.022
		White Black	Clear (2)	ZB5-AW821723	0.022

	1 flush push (marked "I") 1 central pilot light 1 projecting push (marked "O")	Black Red	Clear (2)	ZB5-AW842743	0.021
		Green Red	Clear (2)	ZB5-AW843743	0.021
		White Black	Clear (2)	ZB5-AW841723	0.021

Heads for illuminated "push-push to release" pushbuttons (3)

Shape of head	Type of push	Colour of lens	Reference	Weight kg
---------------	--------------	----------------	-----------	-----------

Only for use with bodies comprising a light block with integral LED

	Flush	White	ZB5-AH013	0.017
		Green	ZB5-AH033	0.017
		Red	ZB5-AH043	0.017
		Yellow	ZB5-AH053	0.017
		Blue	ZB5-AH063	0.017
	Projecting	White	ZB5-AH13	0.017
		Green	ZB5-AH33	0.017
		Red	ZB5-AH43	0.017
		Yellow	ZB5-AH53	0.017
		Blue	ZB5-AH63	0.017

(1) For IP 65 degree of protection, fit clear sealing boot **ZBW-008** : see page 2/40.

(2) Colour of centrally positioned pilot light determined by the colour of the LED incorporated in the body sub-assembly.

(3) Maximum of 1 row of 2 contact blocks on associated body/fixing collar sub-assembly.

Control and signalling units Ø 22

General :
pages 2/2 to 2/9
Characteristics :
pages 2/10 to 2/13
Dimensions :
pages 2/56 to 2/63

Harmony style 5
Illuminated pushbuttons and switches, with double insulated bezel
Sub-assemblies, ZB5-A : heads

References (continued)

To combine with bodies : see pages 2/32 to 2/36. Can be used with XAL control station, see page 3/10.

Heads for illuminated selector switches, standard handle

Shape of head	Number and type of positions	Colour of handle	Reference	Weight kg
Only for use with bodies comprising a light block with integral LED				
	2 - stay put 	White	ZB5-AK1213	0.021
		Green	ZB5-AK1233	0.021
		Red	ZB5-AK1243	0.021
		Yellow	ZB5-AK1253	0.021
		Blue	ZB5-AK1263	0.021
	2 - spring return from right to left 	White	ZB5-AK1413	0.021
		Green	ZB5-AK1433	0.021
		Red	ZB5-AK1443	0.021
		Yellow	ZB5-AK1453	0.021
		Blue	ZB5-AK1463	0.021
	3 - stay put 	White	ZB5-AK1313	0.021
		Green	ZB5-AK1333	0.021
		Red	ZB5-AK1343	0.021
		Yellow	ZB5-AK1353	0.021
		Blue	ZB5-AK1363	0.021
	3 - spring return to centre 	White	ZB5-AK1513	0.021
		Green	ZB5-AK1533	0.021
		Red	ZB5-AK1543	0.021
		Yellow	ZB5-AK1553	0.021
		Blue	ZB5-AK1563	0.021
	3 - spring return from right to centre 	White	ZB5-AK1813	0.021
		Green	ZB5-AK1833	0.021
		Red	ZB5-AK1843	0.021
		Yellow	ZB5-AK1853	0.021
		Blue	ZB5-AK1863	0.021
	3 - spring return from left to centre 	White	ZB5-AK1713	0.021
		Green	ZB5-AK1733	0.021
		Red	ZB5-AK1743	0.021
		Yellow	ZB5-AK1753	0.021
		Blue	ZB5-AK1763	0.021

ZB5-AK1213

ZB5-AK1463