

Low saturation voltage type regulator with ON/OFF switch

BA○○ST Series

The BA○○ST Series are variable, fixed output low drop-out type voltage regulators with an ON/OFF switch. These regulators are used to provide a stabilized output voltage from a fluctuating DC input voltage. Fixed output voltages are 3V*, 3.3V, 5V, 6V* 7V, 8V, 9V, 10V, 12V, and 15V*. The maximum current capacity is 1A for each of the above voltages. (Items marked with an asterisk are under development.)

●Applications

Constant voltage power supply

●Features

- 1) Built-in overvoltage protection circuit, overcurrent protection circuit and thermal shutdown circuit.
- 2) TO220FP-5 package can be used in wide range of applications.
- 3) 0 μ A (design value) circuit current when switch is off.
- 4) Richly diverse lineup of products.
- 5) Low dropout voltage.

●Product codes

Output Voltage (V)	Product No.	Output Voltage (V)	Product No.
Variable	BA00ST *	8.0	BA08ST
3.0	BA03ST *	9.0	BA09ST
3.3	BA033ST	10.0	BA10ST
5.0	BA05ST	12.0	BA12ST
6.0	BA06ST *	15.0	BA15ST *
7.0	BA07ST		

* : Under development.

●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Power supply voltage	V _{cc}	35	V
Power dissipation	P _d	2000*1	mW
Operating temperature	T _{opr}	-40~85	°C
Storage temperature	T _{stg}	-55~150	°C
Applied surge voltage	V _{surge}	50*2	V

*1 Reduce 16 mW for each 1°C when using the regulator at Ta=25°C or higher.


*2 Voltage application time : 200 msec. or less

7828999 0021824 805


ROHM

573

●Block diagram



Variable output type (BA○○ST)



Fixed output type

7828999 0021825 741

●Pin descriptions

Pin No.	Pin Name	Function
1	ON / OFF	Output ON/OFF pin
2	V _{cc}	Power supply input pin
3	GND	Ground pin
4	OUT	Output pin
5	NF	Reference power supply pin for setting voltage with the BA00ST.
	NC	In the BA00ST Series, these are NC pins, except for the BA○○ST.

●Recommended operating conditions

BA00ST (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	4	—	33	V
Output current	I _o	—	—	1	A

BA03ST (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	4	—	25	V
Output current	I _o	—	—	1	A

BA033ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	4.3	—	25	V
Output current	I _o	—	—	1	A

BA05ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	6	—	25	V
Output current	I _o	—	—	1	A

BA06ST (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	7	—	25	V
Output current	I _o	—	—	1	A

BA07ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	8	—	25	V
Output current	I _o	—	—	1	A

BA08ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	9	—	25	V
Output current	I _o	—	—	1	A

BA09ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	10	—	25	V
Output current	I _o	—	—	1	A

BA10ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	11	—	25	V
Output current	I _o	—	—	1	A

BA12ST

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	13	—	27	V
Output current	I _o	—	—	1	A

BA15ST (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Input voltage	V _{cc}	16	—	30	V
Output current	I _o	—	—	1	A

●Electrical characteristics

BA00ST (unless otherwise noted, Ta=25°C, Vcc=10V, Vo=5V, Io=500mA) (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Reference voltage	Vref	1.21	1.27	1.33	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=6→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V		Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when"H"	IIN	—	150	—	μA	CTL=5V	Fig.6

BA03ST (unless otherwise noted, Ta=25°C, Vcc=8V, Io=500mA) (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	Vo1	2.85	3.0	3.15	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=4→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V	Vcc=2.85V	Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when"H"	IIN	—	150	—	μA	CTL=5V	Fig.6

BA033ST (unless otherwise noted, Ta=25°C, Vcc=8V, Io=500mA)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	Vo1	3.15	3.3	3.45	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=4.3→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V	Vcc=3.15V	Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when"H"	IIN	—	150	—	μA	CTL=5V	Fig.6

BA05ST (unless otherwise noted, $T_a=25^{\circ}\text{C}$, $V_{CC}=10\text{V}$, $I_o=500\text{mA}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	V_{O1}	4.75	5.0	5.25	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	$V_{CC}=6\rightarrow 25\text{V}$	Fig.1
Ripple rejection	R.R.	45	55	—	dB	$e_{IN}=1\text{V}_{rms}$, $f=120\text{Hz}$, $I_o=100\text{mA}$	Fig.2
Load regulation	Reg.L	—	50	150	mV	$I_o=5\text{mA}\rightarrow 1\text{A}$	Fig.1
Temperature coefficient of output voltage	T_{CVO}	—	± 0.02	—	% / $^{\circ}\text{C}$	$I_o=5\text{mA}$, $T_j=0\rightarrow 125^{\circ}\text{C}$	Fig.1
Dropout voltage	V_d	—	0.3	0.5	V	$V_{CC}=4.75\text{V}$	Fig.3
Bias current	I_b	—	2.5	5.0	mA	$I_o=0\text{mA}$	Fig.4
Peak output current	I_{o-p}	1.0	1.5	—	A	$T_j=25^{\circ}\text{C}$	Fig.1
Short-circuit output current	I_{os}	—	0.3	1.0	A	$V_{CC}=25\text{V}$	Fig.5
ON mode voltage	V_{th1}	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	V_{th2}	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	I_{IN}	—	150	—	μA	CTL=5V	Fig.6

BA06ST (unless otherwise noted, $T_a=25^{\circ}\text{C}$, $V_{CC}=11\text{V}$, $I_o=500\text{mA}$) (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	V_{O1}	5.7	6.0	6.3	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	$V_{CC}=7\rightarrow 25\text{V}$	Fig.1
Ripple rejection	R.R.	45	55	—	dB	$e_{IN}=1\text{V}_{rms}$, $f=120\text{Hz}$, $I_o=100\text{mA}$	Fig.2
Load regulation	Reg.L	—	50	150	mV	$I_o=5\text{mA}\rightarrow 1\text{A}$	Fig.1
Temperature coefficient of output voltage	T_{CVO}	—	± 0.02	—	% / $^{\circ}\text{C}$	$I_o=5\text{mA}$, $T_j=0\rightarrow 125^{\circ}\text{C}$	Fig.1
Dropout voltage	V_d	—	0.3	0.5	V	$V_{CC}=5.7\text{V}$	Fig.3
Bias current	I_b	—	2.5	5.0	mA	$I_o=0\text{mA}$	Fig.4
Peak output current	I_{o-p}	1.0	1.5	—	A	$T_j=25^{\circ}\text{C}$	Fig.1
Short-circuit output current	I_{os}	—	0.3	1.0	A	$V_{CC}=25\text{V}$	Fig.5
ON mode voltage	V_{th1}	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	V_{th2}	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	I_{IN}	—	150	—	μA	CTL=5V	Fig.6

BA07ST (unless otherwise noted, $T_a=25^{\circ}\text{C}$, $V_{CC}=12\text{V}$, $I_o=500\text{mA}$) (under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	V_{O1}	6.65	7.0	7.35	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	$V_{CC}=8\rightarrow 25\text{V}$	Fig.1
Ripple rejection	R.R.	45	55	—	dB	$e_{IN}=1\text{V}_{rms}$, $f=120\text{Hz}$, $I_o=100\text{mA}$	Fig.2
Load regulation	Reg.L	—	50	150	mV	$I_o=5\text{mA}\rightarrow 1\text{A}$	Fig.1
Temperature coefficient of output voltage	T_{CVO}	—	± 0.02	—	% / $^{\circ}\text{C}$	$I_o=5\text{mA}$, $T_j=0\rightarrow 125^{\circ}\text{C}$	Fig.1
Dropout voltage	V_d	—	0.3	0.5	V	$V_{CC}=6.65\text{V}$	Fig.3
Bias current	I_b	—	2.5	5.0	mA	$I_o=0\text{mA}$	Fig.4
Peak output current	I_{o-p}	1.0	1.5	—	A	$T_j=25^{\circ}\text{C}$	Fig.1
Short-circuit output current	I_{os}	—	0.3	1.0	A	$V_{CC}=25\text{V}$	Fig.5
ON mode voltage	V_{th1}	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	V_{th2}	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	I_{IN}	—	150	—	μA	CTL=5V	Fig.6

7828999 0021828 450

ROHM

577

●Electrical characteristics

BA08ST (unless otherwise noted, Ta=25°C, Vcc=13V, Io=500mA)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	Vo1	7.6	8.0	8.4	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=9→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V	Vcc=7.6V	Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	IIN	—	150	—	μA	CTL=5V	Fig.6

BA09ST (unless otherwise noted, Ta=25°C, Vcc=14V, Io=500mA)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	Vo1	8.45	9.0	9.55	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=10→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V	Vcc=8.45V	Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	IIN	—	150	—	μA	CTL=5V	Fig.6

BA10ST (unless otherwise noted, Ta=25°C, Vcc=15V, Io=500mA)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	Vo1	9.5	10	10.5	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	Vcc=11→25V	Fig.1
Ripple rejection	R.R.	45	55	—	dB	eIN=1Vrms, f=120Hz, Io=100mA	Fig.2
Load regulation	Reg.L	—	50	150	mV	Io=5mA→1A	Fig.1
Temperature coefficient of output voltage	Tcvo	—	±0.02	—	% / °C	Io=5mA, Tj=0→125°C	Fig.1
Dropout voltage	Vd	—	0.3	0.5	V	Vcc=9.5V	Fig.3
Bias current	Ib	—	2.5	5.0	mA	Io=0mA	Fig.4
Peak output current	Io-p	1.0	1.5	—	A	Tj=25°C	Fig.1
Short-circuit output current	Ios	—	0.3	1.0	A	Vcc=25V	Fig.5
ON mode voltage	Vth1	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	Vth2	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	IIN	—	150	—	μA	CTL=5V	Fig.6

7828999 0021829 397

BA12ST (unless otherwise noted, $T_a=25^{\circ}\text{C}$, $V_{\text{CC}}=17\text{V}$, $I_o=500\text{mA}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	V_{O1}	11.4	12	12.6	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	$V_{\text{CC}}=13.5\rightarrow 27\text{V}$	Fig.1
Ripple rejection	R.R.	45	55	—	dB	$e_{\text{IN}}=1\text{Vrms}$, $f=120\text{Hz}$, $I_o=100\text{mA}$	Fig.2
Load regulation	Reg.L	—	50	150	mV	$I_o=5\text{mA}\rightarrow 1\text{A}$	Fig.1
Temperature coefficient of output voltage	T_{CVO}	—	± 0.02	—	% / $^{\circ}\text{C}$	$I_o=5\text{mA}$, $T_j=0\rightarrow 125^{\circ}\text{C}$	Fig.1
Dropout voltage	V_d	—	0.3	0.5	V	$V_{\text{CC}}=11.4\text{V}$	Fig.3
Bias current	I_b	—	2.5	5.0	mA	$I_o=0\text{mA}$	Fig.4
Peak output current	I_{o-p}	1.0	1.5	—	A	$T_j=25^{\circ}\text{C}$	Fig.1
Short-circuit output current	I_{os}	—	0.3	1.0	A	$V_{\text{CC}}=27\text{V}$	Fig.5
ON mode voltage	V_{th1}	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	V_{th2}	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	I_{IN}	—	150	—	μA	CTL=5V	Fig.6

BA15ST (unless otherwise noted, $T_a=25^{\circ}\text{C}$, $V_{\text{CC}}=20\text{V}$, $I_o=500\text{mA}$) (Under development)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions	Measurement Circuit
Output voltage	V_{O1}	14.25	15	15.75	V		Fig.1
Input regulation	Reg.I	—	20	100	mV	$V_{\text{CC}}=17\rightarrow 30\text{V}$	Fig.1
Ripple rejection	R.R.	45	55	—	dB	$e_{\text{IN}}=1\text{Vrms}$, $f=120\text{Hz}$, $I_o=100\text{mA}$	Fig.2
Load regulation	Reg.L	—	50	150	mV	$I_o=5\text{mA}\rightarrow 1\text{A}$	Fig.1
Temperature coefficient of output voltage	T_{CVO}	—	± 0.02	—	% / $^{\circ}\text{C}$	$I_o=5\text{mA}$, $T_j=0\rightarrow 125^{\circ}\text{C}$	Fig.1
Dropout voltage	V_d	—	0.3	0.5	V	$V_{\text{CC}}=14.25\text{V}$	Fig.3
Bias current	I_b	—	2.5	5.0	mA	$I_o=0\text{mA}$	Fig.4
Peak output current	I_{o-p}	1.0	1.5	—	A	$T_j=25^{\circ}\text{C}$	Fig.1
Short-circuit output current	I_{os}	—	0.3	1.0	A	$V_{\text{CC}}=30\text{V}$	Fig.5
ON mode voltage	V_{th1}	2.0	—	—	V	Output Active mode	Fig.6
OFF mode voltage	V_{th2}	—	—	0.8	V	Output OFF mode	Fig.6
Input current when "H"	I_{IN}	—	150	—	μA	CTL=5V	Fig.6

7828999 0021830 009

ROHM

579

● Measurement circuits





Fig.1 Measurement circuit for output voltage, input regulation, load regulation, and temperature coefficient of output voltage



$$\text{Ripple rejection ratio R.R.} = 20 \log \left(\frac{|θ_{IN}|}{|θ_{OUT}|} \right)$$

Fig.2 Measurement circuit for ripple rejection ratio




Fig.3 Measurement circuit for dropout voltage




Fig.4 Measurement circuit for bias current




Fig.5 Measurement circuit for short-circuit output current




Fig.6 Measurement circuit for ON/OFF mode voltage, input current when "H"

7828999 0021831 T45

● Operation notes

1. Although the circuit examples included in this handbook are highly recommendable for general use, you should be thoroughly familiar with circuit characteristics as they relate to your own use conditions. If you intend to change the number of external circuits, leave an ample margin, taking into account discrepancies in both static and dynamic characteristics of external parts and Rohm ICs. In addition, please be advised that Rohm cannot provide complete assurance regarding patent rights.
2. Operating power supply voltage
When operating within the normal voltage range and within the ambient operating temperature range, most circuit functions are guaranteed. The rated values cannot be guaranteed for the electrical characteristics, but there are no sudden changes of the characteristics within these ranges.
3. Power dissipation P_d
Heat attenuation characteristics are noted on a separate page and can be used as a guide in judging power dissipation.
If these ICs are used in such a way that the allowable power dissipation level is exceeded, an increase in the chip temperature could cause a reduction in the current capability or could otherwise adversely affect the performance of the IC. Make sure a sufficient margin is allowed so that the allowable power dissipation value is not exceeded.
4. Preventing oscillation in output and using bias capacitors
Always use a capacitor between the output pins and the GND to prevent fluctuation in the output and to prevent oscillation between the output pins and the GND. (A capacitor greater than $10\ \mu\text{F}$ for all temperature ranges should be used.)
Changes in the temperature and other factors can cause the capacitance of the capacitor to change, and this can cause oscillation. To prevent this, we recommend using a tantalum capacitor which has minimal changes in nominal capacitance. Also, we recommend adding a bypass capacitor of about $0.33\ \mu\text{F}$ between the input pin and the GND, as close to the pin as possible.
5. Current overload protection circuit
A current overload protection circuit is built into the outputs, to prevent IC destruction if the load is shorted.
This protection circuit limits the current in the shape of a '7'. It is designed with a high margin, so that even if a large current suddenly flows through the large capacitor in the IC, the current is restricted and latching is prevented.
However, these protection circuits are only good for preventing damage from sudden accidents. The design should take this into consideration, so that the protection circuit is not made to operate continuously (for instance, clamping at an output of $1V_f$ or greater; below $1V_f$, the short mode circuit operates). Note that the capacitor has negative temperature characteristics, and the design should take this into consideration.
6. Thermal overload circuit
A built-in thermal overload circuit prevents damage from overheating. When the thermal circuit is activated, the various outputs are in the OFF state. When the temperature drops back to a constant level, the circuit is restored.
7. Internal circuits could be damaged if there are modes in which the electric potential of the application's input (V_{cc}) and GND are the opposite of the electric potential of the various outputs. Use of a diode or other such bypass path is recommended.
8. Although the manufacture of this product includes rigorous quality assurance procedures, it may be damaged if absolute maximum ratings for voltage or operating temperature are exceeded. When damage has occurred, special modes (such as short circuit mode or open circuit mode) cannot be specified. If it is possible that such special modes may be needed, please consider using a fuse or some other mechanical safety measure.
9. When used within a strong magnetic field, be aware that there is a slight possibility of malfunction.

7828999 0021832 981

ROHM

581

●Electrical characteristic curves




Fig. 7 Ambient temperature - power dissipation characteristic




Fig. 8 Thermal cutoff circuit characteristic




Fig. 9 Current limit characteristic





Fig. 10 Over voltage protection characteristic

●External dimensions (Units: mm)



7828999 0021833 818

ROHM