

T-11-25

Part Number	Maximum Ratings (85°C)					Characteristics (25°C)			Typical Capacitance 1kHz
	Continuous			Transient		Varistor Voltage 1mA DC + 10%	Maximum Clamping Voltage		
	AC Voltage (RMS)	DC Voltage	Average Power Dissipation	Energy ⁽¹⁾ 2 ms	Peak Current 8/20µs				
	Volts	Volts	Watts	Joules	Amps	Volts	Volts	Amps	Picofarads
B32K75 B40K75 B60K75	75	100	1.2 1.4 1.6	120 190 320	25000 40000 70000	120	200	200 300 500	8000 11000 26000
B32K130 B40K130 B60K130 B80K130	130	170	1.2 1.4 1.6 2.0	210 310 490 660	25000 40000 70000 100000	205	340	200 300 500 800	4400 5600 15000 28000
B32K150 B40K150 B60K150 B80K150	150	200	1.2 1.4 1.6 2.0	240 360 570 800	25000 40000 70000 100000	240	395	200 300 500 800	3700 4800 12000 23000
B32K230 B40K230 B60K230 B80K230	230	300	1.2 1.4 1.6 2.0	300 460 730 1200	25000 40000 70000 100000	360	595	200 300 500 800	2500 3200 7900 16000
B32K250 B40K250 B60K250 B80K250	250	320	1.2 1.4 1.6 2.0	330 490 800 1300	25000 40000 70000 100000	390	650	200 300 500 800	2200 2900 7100 14000
B32K275 B40K275 B60K275 B80K275	275	350	1.2 1.4 1.6 2.0	360 550 860 1400	25000 40000 70000 100000	430	710	200 300 500 800	2000 2700 6600 13000
B32K320 B40K320 B60K320 B80K320	320	420	1.2 1.4 1.6 2.0	430 640 1000 1600	25000 40000 70000 100000	510	840	200 300 500 800	1700 2300 5600 11000
B32K385 B40K385 B60K385 B80K385	385	505	1.2 1.4 1.6 2.0	550 800 1200 2000	25000 40000 70000 100000	620	1025	200 300 500 800	1400 1900 4600 9000
B32K420 B40K420 B60K420 B80K420	420	560	1.2 1.4 1.6 2.0	600 910 1500 2200	25000 40000 70000 100000	680	1120	200 300 500 800	1300 1800 4300 8500
B32K460 B40K460 B60K460 B80K460	460	615	1.2 1.4 1.6 2.0	520 780 1200 2500	25000 40000 70000 100000	750	1240	200 300 500 800	1200 1600 3900 7700
B32K550 B40K550 B60K550 B80K550	550	745	1.2 1.4 1.6 2.0	620 960 1500 3100	25000 40000 70000 100000	910	1500	200 300 500 800	1000 1400 3300 6500
B32K680 B40K680 B60K680 B80K680	680	895	1.2 1.4 1.6 2.0	760 1100 1800 3600	25000 40000 70000 100000	1100	1815	200 300 500 800	830 1100 2600 5200
B32K750 B40K750 B60K750 B80K750	750	1060	1.2 1.4 1.6 2.0	800 1200 2000 4000	25000 40000 70000 100000	1200	2000	200 300 500 800	800 1000 2400 4800
B60K1000 ⁽²⁾ B80K1100	1100	1465	1.6 2.0	3000 6000	70000 100000	1800	2970	500 800	1600 3200

¹Previous catalog specified at 20 microseconds

²Part number differs from AC (RMS) voltage