

FEATURES

- Monolithic DBS Tuner IC
- On Chip Oscillator
- 6 dB Noise Figure
- 11 dB Conversion Gain
- Single + 5V Supply
- Small Size
- Low Cost
- High Reliability
- Surface Mount Package



PRODUCT DESCRIPTION

The ANADIGICS DBS (Direct Broadcast Satellite) Tuner IC is intended for use in high volume, low cost manufacturing of compact DBS tuners for satellite receivers and integrated satellite ready TV/VTR receivers.

manufacturers the ability to produce, in high volumes, tuners with low component count, minimal tuning, small size, high reliability and exceptional price-performance ratios. The ADC20013 offers a high degree of functionality in a very small and user friendly configuration.

The ADC20013 Tuner IC provides DBS tuner




Figure 1: Functional Block Diagram

ELECTRICAL CHARACTERISTICS

Table 1: Absolute Minimum and Maximum Ratings

PARAMETER	MIN	MAX	UNIT
V_{DD}/V_{IF}	0	+7	VDC
V_{LO}	-5	+0.5	VDC
V_{RF}	-10	+0.5	VDC
V_{OSC}	-5	+0.5	VDC
Storage Temperature	-55	+100	°C
Input Power RF		+10	dBm
Input Power LO		+17	dBm

Stresses in excess of the absolute ratings may cause permanent damage. Functional operation is not implied under these conditions. Exposure to absolute ratings for extended periods of time may adversely affect reliability.

Table 2: Operating Ranges

PARAMETER	MIN	TYP	MAX	UNIT
Frequency				
RF	950	-	2050	MHz
LO	1430	-	2530	MHz
IF	-	480	-	MHz
V_{DD}	-	+5	-	VDC
Case Temperature	-55	-	+85	°C

The device may be operated safely over these conditions; however, parametric performance is guaranteed only over the conditions defined in the electrical specifications.

Table 3: Electrical Specifications
($T_A = 25\text{ }^\circ\text{C}$; $V_{DD} = +5\text{V}$)

PARAMETER	MIN	TYP	MAX	UNIT
Conversion Gain ⁽⁶⁾	6	11	-	dB
SSB Noise Figure ⁽⁶⁾	-	6.5	11	dB
Third Order IMD ⁽⁴⁾ (-20 dBm Tones, 5 MHz Apart)	-	- 40	-35	dBc
Second Order IMD (-20 dBm Input Level)	-	- 25	- 20	dBc
LO Leakage ^{(1),(2)} RF Port	-	- 30	- 25	dBm
IF Port	-	0	3	dBm
LO Output Level for PLL ⁽³⁾	-8	- 4	-	dBm
Tuning Voltage ⁽¹⁾ (VT)	1	-	20	Volts
VCO Phase Noise ⁽⁵⁾ 10 kHz Offset	-	- 70	- 65	dBc/Hz
100 kHz Offset	-	- 100	- 95	dBc/Hz
Input Impedance ⁽⁷⁾	-	-	-	-
Output Impedance ⁽⁷⁾	-	-	-	-
Power Supply Current	-	60	85	mA

Notes:

(1) Measured in ANADIGICS test fixture with Toshiba 1SV186 off-chip-varactor.

(2) Includes external coupling through test fixture.

(3) Oscillator output for external PLL. (Pin 14)

(4) Measured at 1450 & 1750 MHz.

(5) Measured using PLL (LBW =1KHz, Reference = 1.25 MHz, Step Size = 10 MHz).

(6) Measured in ANADIGICS test setup.

(7) See Smith charts.




Figure 2: Test Circuit

PERFORMANCE DATA

Figure 3: Conversion Gain and Noise Figure vs Frequency




Figure 4: Oscillator Tuning Curve



Figure 5: Third Order IMD
RF Input Power Level -20dBm/Tone

Figure 6: VCO Phase Noise





Figure 7: Input Impedance Data (RF)


1. IMPEDANCE REFERENCE AT PIN 6
2. VCO ON $V_t = 3.20$ VOLTS
3. $V_{dd} = +5$ VOLTS
4. USE EXTERNAL BIAS TEE FOR IF

MEASURED IN 50 Ω SYSTEM

1.	0.950 GHz
	8.40 Ω
	- 61.53 j Ω
2.	1.250 GHz
	8.12 Ω
	-34.53 j Ω
3.	1.550 GHz
	10.13 Ω
	- 19.90 j Ω
4.	1.750 GHz
	12.75 Ω
	- 8.70 j Ω
5.	1.900 GHz
	15.23 Ω
	- 3.03 j Ω
6.	2.050 GHz
	16.33 Ω
	- 0.27 j Ω

Figure 8: Output Impedance Data (IF)


1. IMPEDANCE REFERENCE AT PIN 2
2. VCO ON $V_t = 3.20$ VOLTS
3. $V_{dd} = +5$ VOLTS
4. USE EXTERNAL BIAS TEE FOR IF

MEASURED IN 50 Ω SYSTEM

1.	0.40 GHz
	26.8 Ω
	- 82.8 j Ω
2.	0.48 GHz
	22.2 Ω
	- 70.0 j Ω
3.	0.50 GHz
	21.4 Ω
	- 67.5 j Ω
4.	0.60 GHz
	18.1 Ω
	- 56.2 j Ω
5.	0.70 GHz
	15.9 Ω
	- 48.7 j Ω
6.	0.80 GHz
	14 Ω
	- 41.2 j Ω


Figure 9: LO Impedance Data

1. IMPEDANCE REFERENCE AT PIN 11
 2. Vdd = + 5 VOLTS




MEASURED IN 50 Ω SYSTEM

- 1 500.0 MHz
 - 60.83 Ω
 - 169.80 j Ω
- 2 1000.0 MHz
 - 15.15 Ω
 - 54.41 j Ω
- 3 1430.0 MHz
 - 5.71 Ω
 - 24.62 j Ω
- 4 1700.0 MHz
 - 2.80 Ω
 - 12.02 j Ω
5. 1922.0 MHz
 - 2.83 Ω
 - 4.25 j Ω
6. 2768.0 MHz
 0.54 Ω
 - 11.31 j Ω

Figure 10: MTF vs. Tcase

PACKAGE OUTLINE



	INCHES		MILLIMETERS		NOTE
	MIN.	MAX.	MIN.	MAX.	
A	0.058	0.068	1.47	1.73	
A ₁	0.004	0.010	0.10	0.25	
A ₂	0.055	0.065	1.40	1.65	
B	0.013	0.020	0.33	0.50	
B ₁	0.062	0.070	1.58	1.78	
C	0.008	0.010	0.20	0.25	4
D	0.380	0.400	9.66	10.16	2
E	0.150	0.160	3.81	4.06	3
e	0.050	BSC	1.27	BSC	
H	0.226	0.244	5.74	6.20	
L	0.016	0.040	0.41	1.02	
LE	0.030	—	0.76	—	
α	0°	8°	0°	8°	

NOTES:

1. CONTROLLING DIMENSION: INCHES
2. DIMENSION "D" DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS AND GATE BURRS SHALL NOT EXCEED 0.006 [0.15mm] PER SIDE.
3. DIMENSION "E" DOES NOT INCLUDE INTER-LEAD FLASH OR PROTRUSIONS. INTER-LEAD FLASH AND PROTRUSIONS SHALL NOT EXCEED 0.010 [0.25mm] PER SIDE.
4. MAXIMUM LEAD TWIST/SKEW TO BE ± 0.005 [0.13mm].
5. LEAD THICKNESS AFTER PLATING TO BE 0.013 [0.33mm] MAXIMUM.

Figure 11: S3 Package Outline - Modified 16 Pin SOIC

NOTES

NOTES

ORDERING INFORMATION

ORDER NUMBER	TEMPERATURE RANGE	PACKAGE DESCRIPTION	COMPONENT PACKAGING
ADC20013S3CTR	-55 to +85°C	Modified 16 Pin SOIC	3500 Piece Tape and Reel
ADC20013S3C	-55 to +85°C	Modified 16 Pin SOIC	Plastic Tubes (50 pcs. per tube)

ANADIGICS, Inc.
35 Technology Drive
Warren, New Jersey 07059
Tel: (908) 668-5000 / Fax: (908) 668-5132
Email: Mkg@anadigics.com
www.anadigics.com

IMPORTANT NOTICE

ANADIGICS, Inc. reserves the right to make changes to its products or discontinue any product at any time without notice. The Advanced Product data sheets and product specifications contained in this data sheet are subject to change prior to a products formal introduction. The information in this data sheet has been carefully checked and is assumed to be reliable. However, ANADIGICS assumes no responsibility for inaccuracies. ANADIGICS strongly urges customers to verify that the information they are using is current before placing orders.

WARNING

ANADIGICS products are not intended for use in life support appliances, device, or systems. Use of an ANADIGICS product in any such application without written consent is prohibited.