

AZ970/AZ971

40 AMP MINIATURE POWER RELAY FOR AUTOMOTIVE USE

FEATURES

- Low cost
- Up to 40 Amp switching capability in a compact size
- Open, covered or sealed
- Coils to 24 VDC
- Small footprint
- 1 Form A, B and C contacts available
- Vibration and shock resistant
- Designed for high in-rush applications

CONTACTS

Arrangement	SPST (1 Form A) SPST (1 Form B) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: Form A: 560 W Form B: 420 W Form C: 420 W Max. switched current: Form A: 40 A Form B: 30 A Form C: 30 A Max. switched voltage: 150* VDC Max. carry current: 60 A * If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Minimum Load	5 VDC, 0.1 A
Material	Silver alloy
Resistance	< 100 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power	
At Pickup Voltage (typical)	514 mW (12 and 24 VDC Coil) 573 mW (6 VDC Coil)
Max. Continuous Dissipation	4.8 W 20°C (68°F) ambient (AZ970) 3.8 W 20°C (68°F) ambient (AZ971)
Temperature Rise	60°C (108°F) nominal coil VDC (AZ970) 75°C (135°F) nominal coil VDC (AZ971)
Max. Temperature	200°C (392°F)



GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 5 x 10 ⁶ operations 1 x 10 ⁵ operations at rated load
Operate Time (typical)	3 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	500 VDC coil to contact 500 VDC between open contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 6% of nominal coil voltage
Ambient Temperature AZ970 Operating AZ970 Storage AZ971 Operating AZ971 Storage	At nominal coil voltage -40°C (-40°F) to 140°C (284°F) -40°C (-40°F) to 200°C (392°F) -40°C (-40°F) to 125°C (257°F) -40°C (-40°F) to 175°C (347°F)
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	20 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.



AMERICAN ZETTLER, INC.

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

8/17/98W

AZ970/AZ971

RELAY ORDERING DATA — AZ970 — OPEN STYLE

COIL SPECIFICATIONS				ORDER NUMBER		
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Form A (SPST)	Form B (SPST)	Form C (SPDT)
6	3.3	9.0	19.0	AZ970-1A-6D	AZ970-1B-6D	AZ970-1C-6D
9	5.1	14.7	50.0	AZ970-1A-9D	AZ970-1B-9D	AZ970-1C-9D
12	6.8	19.6	90.0	AZ970-1A-12D	AZ970-1B-12D	AZ970-1C-12D
24	13.9	39.3	362.0	AZ970-1A-24D	AZ970-1B-24D	AZ970-1C-24D

RELAY ORDERING DATA — AZ971 — With Dust Cover

COIL SPECIFICATIONS				ORDER NUMBER*		
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Form A (SPST)	Form B (SPST)	Form C (SPDT)
6	3.3	8.1	19.0	AZ971-1A-6D	AZ971-1B-6D	AZ971-1C-6D
9	5.1	14.7	50.0	AZ971-1A-9D	AZ971-1B-9D	AZ971-1C-9D
12	6.8	17.6	90.0	AZ971-1A-12D	AZ971-1B-12D	AZ971-1C-12D
24	13.9	35.4	362.0	AZ971-1A-24D	AZ971-1B-24D	AZ971-1C-24D

*Add suffix "E" for epoxy sealed version.

MECHANICAL DATA

AZ970 Outline Dimensions and PCB Layout

Top View: .760 [19.3] x .945 [24]
Side View: .715 [18.2]
Terminal View: .170 [4.3]
Terminal View (Viewed towards terminals): 3x $\phi .081$ [$\phi 2.1$], .559 [14.2], .102 [2.6], .148 [3.8], .211 [5.4], .134 [3.4], .066 [1.7], .147 [3.7], .467 [11.9], .161 [4.1], .322 [8.2], 4x $\phi .055$ [$\phi 1.4$]

Terminal Dimensions

Term.	Dimensions
3,5	.041 [1.02] x .03 [0.76]
1,2	.041 [1.02] x .018 [0.46]
4	.041 [1.02] x .062 [1.57]

AZ971 Outline Dimensions and PCB Layout

Top View: .866 [22] x 1.040 [26.4]
Side View: .878 [22.3]
Terminal View: .020 [.5], .126 [3.2]
Terminal View (Viewed towards terminals): 3x $\phi .081$ [$\phi 2.1$], .559 [14.2], .102 [2.6], .148 [3.8], .211 [5.4], .170 [4.3], .134 [3.4], .147 [3.7], .467 [11.9], .161 [4.1], .322 [8.2], 4x $\phi .055$ [$\phi 1.4$]

Wiring Diagrams

FORM C: SPDT wiring diagram showing terminals 1, 2, 3, 4, 5.

FORM B: SPST wiring diagram showing terminals 1, 2, 3, 4.

FORM A: SPST wiring diagram showing terminals 1, 2, 3, 4.

Viewed towards terminals

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "



AMERICAN ZETTLER, INC.

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

8/17/98W