

ZXM62N03G


30V N-CHANNEL ENHANCEMENT MODE MOSFET

SUMMARY

$V_{(BR)DSS} = 30V$; $R_{DS(on)} = 0.11\Omega$; $I_D = 4.7A$

DESCRIPTION

This new generation of High Density MOSFETs from Zetex utilises a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




SOT223

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- SOT223 package


APPLICATIONS

- DC-DC Converters
- Audio Output Stage
- Relay and Solenoid driving
- Motor Control



ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXM62N03GTA	7"	12mm	1000 units
ZXM62N03GTC	13"	12mm	4000 units



Top View

DEVICE MARKING

- ZXM6
2N03

ZXM62N03G

ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($V_{GS}=10V$; $T_A=25^\circ C$)(b) ($V_{GS}=10V$; $T_A=70^\circ C$)(b) ($V_{GS}=10V$; $T_A=25^\circ C$)(a)	I_D	4.7 3.8 3.4	A
Pulsed Drain Current (c)	I_{DM}	16	A
Continuous Source Current (Body Diode) (b)	I_S	2.6	A
Pulsed Source Current (Body Diode)(c)	I_{SM}	16	A
Power Dissipation at $T_A=25^\circ C$ (a) Linear Derating Factor	P_D	2.0 16	W mW/ $^\circ C$
Power Dissipation at $T_A=25^\circ C$ (b) Linear Derating Factor	P_D	3.9 31	W mW/ $^\circ C$
Operating and Storage Temperature Range	T_j, T_{stg}	-55 to +150	$^\circ C$

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)	$R_{\theta JA}$	62.5	$^\circ C/W$
Junction to Ambient (b)	$R_{\theta JA}$	32	$^\circ C/W$


NOTES

(a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions

(b) For a device surface mounted on FR4 PCB measured at $t \leq 10$ secs.

(c) Repetitive rating 25mm x 25mm FR4 PCB, $D=0.05$ pulse width limited by maximum junction temperature.

ZXM62N03G



ZXM62N03G

ELECTRICAL CHARACTERISTICS (at $T_A = 25^\circ\text{C}$ unless otherwise stated).


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	30			V	I _D =250μA, V _{GS} =0V
Zero Gate Voltage Drain Current	I _{DSS}			1	μA	V _{DS} =30V, V _{GS} =0V
Gate-Body Leakage	I _{GSS}			100	nA	V _{GS} =± 20V, V _{DS} =0V
Gate-Source Threshold Voltage	V _{GS(th)}	1.0			V	I _D =250μA, V _{DS} = V _{GS}
Static Drain-Source On-State Resistance (1)	R _{DS(on)}			0.11 0.15	Ω Ω	V _{GS} =10V, I _D =2.2A V _{GS} =4.5V, I _D =1.1A
Forward Transconductance (1)(3)	g _{fs}	1.1			S	V _{DS} =15V,I _D =1.1A
DYNAMIC (3)						
Input Capacitance	C _{iss}		380		pF	V _{DS} =25V, V _{GS} =0V, f=1MHz
Output Capacitance	C _{oss}		90		pF	
Reverse Transfer Capacitance	C _{rss}		30		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	t _{d(on)}		2.9		ns	V _{DD} =15V, I _D =2.2A R _G =6.0Ω, V _{GS} =10V
Rise Time	t _r		5.6		ns	
Turn-Off Delay Time	t _{d(off)}		11.7		ns	
Fall Time	t _f		6.4		ns	
Total Gate Charge	Q _g			9.6	nC	V _{DS} =24V,V _{GS} =10V, I _D =2.2A
Gate-Source Charge	Q _{gs}			1.7	nC	
Gate-Drain Charge	Q _{gd}			2.8	nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V _{SD}			0.95	V	T _J =25°C, I _S =2.2A, V _{GS} =0V
Reverse Recovery Time (3)	t _{rr}		18.8		ns	T _J =25°C, I _F =2.2A, di/dt= 100A/μs
Reverse Recovery Charge (3)	Q _{rr}		11.4		nC	

NOTES

- (1) Measured under pulsed conditions. Width=300 μs . Duty cycle $\leq 2\%$.
 (2) Switching characteristics are independent of operating junction temperature.
 (3) For design aid only, not subject to production testing.


ZXM62N03G

TYPICAL CHARACTERISTICS




ZXM62N03G

TYPICAL CHARACTERISTICS



ZXM62N03G


PACKAGE OUTLINE



PACKAGE DIMENSIONS

DIM	Millimetres		Inches	
	Min	Max	Min	Max
A	6.3	6.7	0.248	0.264
B	3.3	3.7	0.130	0.146
C	-	1.7	-	0.067
D	0.6	0.8	0.024	0.031
E	2.9	3.1	0.114	0.122
F	0.24	0.32	0.009	0.13
G	NOM 4.6		NOM 0.181	
H	0.85	1.05	0.033	0.041
K	0.02	0.10	0.0008	0.004
L	6.7	7.3	0.264	0.287
M	NOM 2.3		NOM 0.0905	

PAD LAYOUT DETAILS



© Zetex plc 2002

Europe

Zetex plc
Fields New Road
Chadderton
Oldham, OL9 8NP
United Kingdom
Telephone (44) 161 622 4422
Fax: (44) 161 622 4420
uk.sales@zetex.com

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49
europe.sales@zetex.com

Americas

Zetex Inc
700 Veterans Memorial Hwy
Hauppauge, NY11788
USA
Telephone: (631) 360 2222
Fax: (631) 360 8222
usa.sales@zetex.com

Asia Pacific

Zetex (Asia) Ltd
3701-04 Metroplaza, Tower 1
Hing Fong Road
Kwai Fong
Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494
asia.sales@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to **www.zetex.com**

ISSUE 1 - OCTOBER 2002

