



SAFETY DATA SHEET

FAST-TAK CONTACT ADHESIVE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME: FAST-TAK CONTACT ADHESIVE

PART No.: 91770

SUPPLIER: Bostik (UK) Limited,
Ulverscroft Road,
Leicester. LE4 6BW

TEL: 0116-2510015

FAX: 0116-2531943

2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	CONTENTS	HEALTH (class)	RISK (R No.)
ACETONE	67-64-1	10-30 %		
SOLVENT NAPHTHA (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC; LOW BOI	92062-15-2	10-30 %	T	45, 65

3 HAZARDS IDENTIFICATION

Extremely flammable.

4 FIRST AID MEASURES

GENERAL: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention immediately!

SKIN: Remove affected person from source of contamination. Remove contaminated clothing. Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use extinguishing media appropriate for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES: Use pressurized air mask if substance is involved in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS: Wear necessary protective equipment. Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Runoff or release to sewer, waterway or ground is forbidden. Absorb in vermiculite, dry sand or earth and place into

FAST-TAK CONTACT ADHESIVE

containers. Do not let washing down water contaminate ponds or waterways. Flush area with plenty of water. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS:	Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Keep in cool, dry, ventilated storage and closed containers. Keep in original container.
STORAGE CRITERIA:	Toxic storage.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME	CAS No	STD	LT EXP (8 hrs) 750 ppm	ST EXP (15 min) 1500 ppm
ACETONE	67-64-1	OES.		

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:



VENTILATION: Provide adequate general and local exhaust ventilation.
RESPIRATORS: If ventilation is insufficient, suitable respiratory protection must be provided.
PROTECTIVE GLOVES: Use protective gloves.
EYE PROTECTION: Wear approved safety goggles.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENIC WORK ROUTINES: DO NOT SMOKE IN WORK AREA! Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. No eating or drinking while working with this material.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol.	COLOUR:	Colourless.
ODOUR/TASTE:	Organic solvents.		
SOLUBILITY DESCRIPTION:	Miscible with water.	VAPOUR PRESSURE:	>1.8 (AIR=1)
FLASH POINT (°C):	- 40		
FLASH POINT METHOD:	CC (Closed cup).		

10 STABILITY AND REACTIVITY

STABILITY: Normally stable.
CONDITIONS TO AVOID: Avoid heat. Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS: Because of limited volume in an aerosol, and that the contents can hardly be swallowed, risk of poisoning is regarded to be small.
MEDICAL SYMPTOMS: EYES AND MUCOUS MEMBRANES. Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS: No data on possible environmental effects have been found.

FAST-TAK CONTACT ADHESIVE

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14 TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



ROAD:

UN No: 1950
ADR ITEM No: 5°F
PROPER SHIPPING NAME I: AEROSOL

ADR CLASS No: 2
ADR LABEL No: 3

RAIL:

SEA:

SEA TRANSPORT CLASS No: 9
EmS No.: 2-13
MARINE POLLUTANT: No.

IMDG Page No: 9022
MFAG Table No: 340

AIR:

15 REGULATORY INFORMATION

LABEL FOR SUPPLY:



EXTREMELY FLAMMABLE

RISK PHRASES: R-12 Extremely flammable.

SAFETY PHRASES: S-9 Keep container in a well ventilated place.
S-16 Keep away from sources of ignition - No Smoking.
S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S-38 In case of insufficient ventilation, wear suitable respiratory equipment.
S-45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

EC DIRECTIVES: System of specific information relating to Dangerous Preparations. 91\155.
APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES: Occupational Exposure Limits EH40.

CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES: Dangerous Properties of Industrial Materials Report, N.Sax et.al.
REVISION COMMENTS: This MSDS has been revised in Section(s) : 14
REVISION DATE: 05/99
REVISION No. /REPLACES SDS ISSUED: 4 - 02/98