

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

85505	01	R	X
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

<u>Device type</u>	<u>Generic number</u>	<u>Circuit</u>
01	54HCT240	Octal 3-state inverting buffer/line receiver/line driver

<u>Outline letter</u>	<u>Case outline</u>
R	D-8 (20-lead, 1/4" x 1-1/16"), dual-in-line package
2	C-2 (20-terminal, .350" x .350"), square chip carrier package

Supply voltage range	- - - - -	-0.5 V dc to +7.0 V dc
DC input voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
DC output voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
Clamp diode current	- - - - -	± 20 mA
DC output current (per pin)	- - - - -	± 35 mA
DC V_{CC} or GND current (per pin)	- - - - -	± 70 mA
Storage temperature range	- - - - -	-65°C to +150°C
Maximum power dissipation (P_D)	- - - - -	500 mW <u>2/</u>
Lead temperature (soldering 10 seconds)	- - - - -	+260°C
Thermal resistance, junction to case (θ_{JC}):		
Case R	- - - - -	See MIL-M-38510, appendix C
Case 2	- - - - -	60°C/W <u>3/</u>
Junction temperature (T_J)	- - - - -	+175°C

- 1/ Unless otherwise specified, all voltages are referenced to ground.
- 2/ For $T_C = +100^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, derate linearly at $12\text{ mW}/^{\circ}\text{C}$.
- 3/ When a thermal resistance for this case is specified in MIL-M-38510, appendix C, that value shall supersede the value specified herein.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505	
		REV A	PAGE 2	

Powered by ICminer.com Electronic-Library Service Copyright 2003

1.4 Recommended operating conditions.

Supply voltage (V_{CC}) - - - - - +4.5 V dc to +5.5 V dc
Case operating temperature range (T_C) - - - - - -55°C to +125°C
Input rise or fall time:
 $V_{CC} = 4.5$ V - - - - - 0 to 500 ns

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Logic diagram. The logic diagram shall be as specified on figure 3.

3.2.4 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full recommended case operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
		REV A	PAGE 3

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 1/ -55°C < T _C < +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
High level output voltage	V _{OH}	V _{IN} = V _{IH} or V _{IL} I _O ≤ 20 μA	V _{CC} = 4.5 V	1, 2, 3	4.4	V
		V _{IN} = V _{IH} or V _{IL} I _O ≤ 6.0 mA	V _{CC} = 4.5 V	1, 2, 3	3.7	V
Low level output voltage	V _{OL}	V _{IN} = V _{IH} or V _{IL} I _O ≤ 20 μA	V _{CC} = 4.5 V	1, 2, 3	0.1	V
		V _{IN} = V _{IH} or V _{IL} I _O ≤ 6.0 mA	V _{CC} = 4.5 V	1, 2, 3	0.4	V
High level input voltage	V _{IH}	2/	V _{CC} = 4.5 V	1, 2, 3	2.0	V
Low level input voltage	V _{IL}	2/	V _{CC} = 4.5 V	1, 2, 3	0.8	V
Input capacitance	C _{IN}	V _{IN} = 0 V See 4.3.1c	T _C = +25°C	4	10	pF
Quiescent current	I _{CC}	V _{CC} = 5.5 V; V _{IN} = V _{CC} or GND		1, 2, 3	160	μA
Input leakage current	I _{IN}	V _{CC} = 5.5 V; V _{IN} = V _{CC} or GND		1, 2, 3	±1	μA
Functional tests		See 4.3.1d		7		
Three state output current	I _{OZ}	V _{IN} = V _{IH} or V _{IL} ; V _O = V _{CC} or GND		1, 2, 3	±10	μA

See footnotes at end of table.

MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO

SIZE
A

CODE IDENT. NO.
14933

DWG NO.

85505

REV A

PAGE 4

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C < T _C < +125°C unless otherwise specified	Group A subgroups	Limits		Unit	
				Min	Max		
Additional quiescent supply current	ΔI _{CC}	V _{IN} = 2.4 V or 0.5 V, any 1 input V _{IN} = V _{CC} or GND, other inputs V _{CC} = 5.5 V I _{OUT} = 0 μA	1, 2, 3		3	mA	
Propagation delay time, A to YA or B to YB	t _{PHL} t _{PLH}	V _{CC} = 5.0 V ±10% C _L = 50 pF ±10% See figure 4	9		25	ns	
			10, 11		38	ns	
Propagation delay time, output enable to YA or YB	t _{PLZ} t _{PHZ}		9		35	ns	
			10, 11		53	ns	
Propagation delay time, output enable to YA or YB	t _{PZL} t _{PZH}		9		35	ns	
			10, 11		53	ns	
Transition time <u>3/</u>	t _{TLH} t _{THL}		9		12	ns	
			10, 11		18	ns	

^{1/} For a power supply of 5 V $\pm 10\%$ the worst case output voltages (V_{OH} and V_{OL}) occur for HCT at 4.5 V. Thus the 4.5 V values should be used when designing with this supply. Worse case V_{IH} and V_{IL} occur at V_{CC} = 5.5 V and 4.5 V respectively.

^{2/} Test not required if applied as a forcing function for V_{OH} or V_{IL}.

^{3/} Transition time, (t_{TLH}, t_{THL}), if not tested, shall be guaranteed to the specified parameters.

MILITARY DRAWING

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO

SIZE

A

CODE IDENT. NO.

14933


DWG NO.

85505

REV A

PAGE 5

DESC FORM 193A
FEB 86



DESC FORM 193A
FEB 86

Inputs		Outputs
Enable A	Enable B	YA,YB
L	L	H
L	H	L
H	X	Z

Z = High Impedance

X = Don't Care

FIGURE 2. Truth table.







FIGURE 3. Logic diagram.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
	REV A		PAGE 7

DESC FORM 193A
FEB 86



*INCLUDES ALL PROBE AND JIG CAPACITANCE

FIGURE 4. Switching waveforms and test circuits.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
		REV A	PAGE 8

DESC FORM 193A
FEB 86

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test (method 1015 of MIL-STD-883).

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 5, 6, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

c. Subgroup 4 (C_{IN} measurement) shall be measured only for the initial test and after process or design changes which may affect input capacitance.

d. Subgroup 7 tests shall verify the truth table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
	REV A		PAGE 9

DESC FORM 193A
FEB 86

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test (method 1005 of MIL-STD-883) conditions:
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*,2,9
Group A test requirements (method 5005)	1,2,3,7,9, 10,11**
Groups C and D end-point electrical parameters (method 5005)	1,2,3
Additional electrical subgroups for group C periodic inspections	---

* PDA applies to subgroup 1.

** Subgroup 10 and 11, if not tested, shall be guaranteed to the specified limits in table I.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Replaceability is determined as follows:

- a. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.
- b. When a QPL source is established, the part numbered device specified in this drawing will be replaced by the microcircuit identified as part number M38510/65753B---.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
		REV A	PAGE 10

DESC FORM 193A
FEB 86

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

6.4 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed herein have agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>	Replacement military specification part number
8550501RX	01295 04713 18714	SNJ54HCT240J 54HCT240/BRAJC CD54HCT240F/3A	M38510/65753BRX
85505012X	04713 01295	54HCT240M/B2CJC SNJ54HCT240FK	M38510/65753B2X

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

04713

18714

01295

Vendor name
and address

Motorola, Inc .
7402 S. Price Road
Tempe, AZ 85283

RCA Corporation
Route 202
Somerville, NJ 08876

Texas Instrument, Inc.
P.O. Box 6448
Midland, TX 79701

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 85505
		REV A	PAGE 11

DESC FORM 193A
FEB 86