

| REVISIONS | | | | | | | | | | | | | | | | | | | |
|-----------|--|-----------------|------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| LTR | DESCRIPTION | DATE (YR-MO-DA) | APPROVED | | | | | | | | | | | | | | | | |
| A | Change to military drawing format. Page 1, change title. Page 2, change generic number and circuit function. Page 6, correct switching test circuit. Page 9, correct vendor similar part number. | 86 Oct 20 | <i>M.A. Lyle</i> | | | | | | | | | | | | | | | | |
| B | Add vendor CAGE 34333. Editorial changes throughout. Change current CAGE code to 67268. | 88 JULY 26 | <i>M.A. Lyle</i> | | | | | | | | | | | | | | | | |

CURRENT CAGE CODE 67268


| | | | | | | | | | | | | | | | | | | | | |
|-------------------------|-------|---|---|---|---|---|---|---|---|---|--|--|--|--|--|--|--|--|--|--|
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV STATUS OF SHEETS | REV | B | B | B | B | A | B | B | B | | | | | | | | | | | |
| | SHEET | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | | | | | | | | | | |

| | | | | | |
|---|--|--|------------------|---------------------------|-------|
| <p>PMIC N/A</p> <p style="text-align: center; font-weight: bold;">STANDARDIZED MILITARY DRAWING</p> <p style="font-size: 0.8em;">THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE</p> <p>AMSC N/A</p> | <p>PREPARED BY <i>Joseph A. Herby</i></p> <p>CHECKED BY <i>Ray Monnin</i></p> <p>APPROVED BY <i>M.A. Lyle</i></p> <p>DRAWING APPROVAL DATE 28 March 86</p> <p>REVISION LEVEL B</p> | <p style="text-align: center;">DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444</p> <hr/> <p style="text-align: center;">MICROCIRCUIT, LINEAR, QUAD 2-INPUT AND DRIVER, MONOLITHIC SILICON</p> <table style="width: 100%;"> <tr> <td style="width: 15%;">SIZE A</td> <td style="width: 35%;">CAGE CODE 14933</td> <td style="width: 50%; text-align: right;">85500</td> </tr> </table> <p style="text-align: center;">SHEET 1 OF 9</p> | SIZE A | CAGE CODE 14933 | 85500 |
| SIZE A | CAGE CODE 14933 | 85500 | | | |

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:



1.2.1 Device type. The device type shall identify the circuit function as follows:

| <u>Device type</u> | <u>Generic number</u> | <u>Circuit</u> |
|--------------------|-----------------------|---|
| 01 | UH -508 | Quad 2-Input AND driver high-output voltage and current |

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

| <u>Outline letter</u> | <u>Case outline</u> |
|-----------------------|--|
| C | D-1 (14-lead, .785" x .310" x .200"), dual-in-line package |
| D | F-2 (14-lead, .390" x .260" x .085"), flat package |

1.3 Absolute maximum ratings.

| | | |
|--|-----------|-----------------------------|
| Supply voltage (V_{CC}) | - - - - - | 7.0 V dc |
| Input voltage (V_{IN}) | - - - - - | 5.5 V dc |
| Output off-state voltage | - - - - - | 100 V dc |
| Output on-state sink current | - - - - - | 500 mA |
| Storage temperature | - - - - - | -65°C to +150°C |
| Lead temperature (soldering, 10 seconds) | - - - - - | +300°C |
| Junction temperature (T_J) | - - - - - | +150°C |
| Thermal resistance, junction to case (θ_{JC}): | | |
| Cases C and D | - - - - - | See MIL-M-38510, appendix C |
| Thermal resistance, junction to ambient (θ_{JA}): | | |
| Case C | - - - - - | 90°C/watt |
| Case D | - - - - - | 140°C/watt |

1.4 Recommended operating conditions.

| | |
|---|-----------------|
| Supply voltage (V_{CC}) | 4.5 V to 5.5 V |
| Current into any output (on-state) | 250 mA maximum |
| Ambient operating temperature (T_A) | -55°C to +125°C |
| Minimum high level input voltage (V_{IH}) | 2.0 V |
| Maximum low level input voltage (V_{IL}) | 0.8 V |

| | | | |
|---|-------------------------|----------------------------|-------------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 85500 |
| | | REVISION LEVEL B | SHEET 2 |

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Logic diagram and terminal connections. The logic diagram and terminal connections shall be as specified on figure 1.

3.2.2 Switching circuit and waveforms. The switching circuit and waveforms shall be as specified on figure 2.

3.2.3 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

| | | | |
|---|-------------------------|----------------------------|-------------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 85500 |
| | | REVISION LEVEL B | SHEET 3 |

TABLE I. Electrical performance characteristics.

| Test | Symbol | Conditions $-55^{\circ}\text{C} < T_A < +125^{\circ}\text{C}$ unless otherwise specified | Group A subgroups | Limits | | Unit |
|---------------------------------------|-------------|---|----------------------|--------|-------------|---------------|
| | | | | Min | Max | |
| Input current High | $I_{IN(1)}$ | Other input = 0 V Driven input: 2.4 V 5.5 V | 1,2,3 1,2,3 | --- | 40 1,000 | μA |
| Input current Low | $I_{IN(0)}$ | Other input = 4.5 V, Driven input: 0.4 V $V_{CC} = 5.5\text{ V}$, $V_{OUT} = 100\text{ V}$ | 1,2,3 | --- | -800 | μA |
| Output reverse current | I_{OFF} | Other input = V_{CC} , Driven input: 0.8 V $V_{CC} = 4.5\text{ V}$ | 1,2,3 | --- | 100 | μA |
| Output voltage Low | V_{OH} | $-55^{\circ}\text{C} < T_A < 25^{\circ}\text{C}$, $V_{CC} = 4.5\text{ V}$ All inputs = 2.0 V | 1,3 1,3 | --- | 0.5 0.7 | V |
| | | $T_A = +125^{\circ}\text{C}$, $V_{CC} = 4.5\text{ V}$ All inputs = 2.0 V | 2 2 | --- | 0.6 0.8 | |
| | | | | | | |
| | | | | | | |
| Level supply current, High | $I_{CC(1)}$ | $T_A = +25^{\circ}\text{C}$ $V_{CC} = 5.5\text{ V}$ All inputs = 0 V | 1 | --- | 30 | mA |
| Level supply current, Low | $I_{CC(0)}$ | $T_A = +25^{\circ}\text{C}$ $V_{CC} = 5.5\text{ V}$ All inputs = 5.0 V | 1 | --- | 106 | |
| Propagation delay time, "Turn-on" | t_{pdON} | $V_S = 100\text{ V}$, $C_L = 15\text{ pF}$ | 9,10,11 | --- | 500 | ns |
| Propagation delay time, "Turn-off" | t_{pdOFF} | $V_{CC} = 5.0\text{ V}$, $R_L = 670\text{ ohm}$ | 9,10,11 | --- | 750 | |

**STANDARDIZED
MILITARY DRAWING**


DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


85500

REVISION LEVEL
B

SHEET
4




Case C




Case D

FIGURE 1. Logic diagram and terminal connections.

| | | | |
|---|-----------|---------------------------------|------------------|
| DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO | SIZE A | CODE IDENT. NO. 14933 | DWG NO. 85500 |
| | | REV A | PAGE 5 |



Waveforms



Input pulse:

$V_{IN(0)} = 0\text{ V}$
 $V_{IN(1)} = 3.5\text{ V}$
 $t_f = 7\text{ ns}$
 $t_r = 14\text{ ns}$
 $t_p = 1\text{ us}$
 $PLR = 500\text{ KHZ}$
 $V_S = 100\text{ V}$

*Includes probe and test fixture capacitance

Test circuit

FIGURE 2. Switching circuit and waveforms.

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO

SIZE
A

CODE IDENT. NO.
14933

DWG NO.

85500

REV B

PAGE 6

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test, method 1015 of MIL-STD-883.
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

TABLE II. Electrical test requirements.

| MIL-STD-883 test requirements | Subgroups (per method 5005, table I) |
|--|--|
| Interim electrical parameters (method 5004) | --- |
| Final electrical test parameters (method 5004) | 1*, 2, 3, 9 |
| Group A test requirements (method 5005) | 1, 2, 3, 9, 10**, 11** |
| Groups C and D end-point electrical parameters (method 5005) | 1, 2, 3 |

* PDA applies to subgroup 1.

** Subgroups 10 and 11, if not tested, shall be guaranteed to the specified limits in table I.

STANDARDIZED MILITARY DRAWING

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

85500

REVISION LEVEL
B

SHEET
7

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, 7, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

| | | | |
|---|------------------|----------------------------|-------------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 85500 |
| | | REVISION LEVEL B | SHEET 8 |

6.4 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed herein have agreed to this drawing and a certificate of compliance (see 3.8) has been submitted to DESC-ECS.

| Military drawing part number | Vendor CAGE number | Vendor similar part number <u>1/</u> |
|------------------------------|--------------------|--------------------------------------|
| 8550001CX | 56289 | UHD508H/883C |
| 8550001CX | 34333 | SG508H/883B |
| 8550001DX | 56289 | UHC508J/883C |

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

Vendor name and address

56289

Sprague Electric Company
115 Northeast Cutoff
Worcester, MA 01607

34333

Silicon General Incorporated
11861 Western Avenue
Garden Grove, CA 92641

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

85500

REVISION LEVEL
B

SHEET

9