

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
C	Delete Vendor, CAGE 18324 Revise to military drawing format.	9 APRIL 1987	<i>M. A. Hancock</i>
D	Add vendor CAGE 18324. Change drawing code ident. no. to 67268. Editorial changes throughout.	6 OCT 1987	<i>R. P. Evans</i>

DEVICE 01 INACTIVE FOR NEW
DESIGN AS OF 9 APRIL 1987
USE M38510/32803B - -.

CURRENT CAGE CODE 67268

[illegible]

5962-E602

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


DESC FORM 193

MAY 86

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:



1.2.1 Device type. The device type shall identify the circuit function as follows:

Device type	Generic number	Circuit
01	54LS245	Octal bus transceivers with three-state outputs

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
2	C-2 (20-terminal, .350" x .350"), square chip carrier package
S	F-9 (20-lead, 1/4" x 1/2"), flat package

1.3 Absolute maximum ratings.

Supply voltage range - - - - -	-0.5 V dc to +7.0 V dc
DC input voltage - - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
Storage temperature - - - - -	-65°C to +150°C
Maximum power dissipation (P_D) per device 1/ - - -	522.5 mW
Lead temperature (soldering, 10 seconds) - - - - -	+300°C
Thermal resistance, junction-to-case (θ_{JC}):	
Cases S and 2 - - - - -	See MIL-M-38510, appendix C
Junction temperature (T_J) - - - - -	+175°C

1.4 Recommended operating conditions.

Supply voltage (V_{CC}) - - - - -	4.5 V dc minimum to 5.5 V dc maximum
Minimum high level input voltage (V_{IH}) - - - - -	2.0 V dc
Case operating temperature range (T_C) - - - - -	-55°C to +125°C
High level output current (I_{OH}) - - - - -	-12 mA maximum
Low level output current (I_{OL}) - - - - -	12 mA maximum

1/ Must withstand the added P_D due to short circuit test (e.g., I_{OS}).

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	DWG NO. 80021
	REV D	PAGE 2

DESC FORM 193A
FEB 86

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2. Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections and logic diagram. The terminal connections and logic diagram shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full recommended case operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE		DWG NO.	
	A		80021	
		REV	C	PAGE 3

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C < T _C < +125°C, unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
High level input voltage	V _{IH}		1, 2, 3	2.0		V
Low level input voltage	V _{IL}		1, 2, 3		0.7	V
Input clamp voltage	V _{IC}	V _{CC} = 4.5 V, T _C = +25°C	1		-1.5	V
High level output voltage	V _{OH}	V _{CC} = 4.5 V, V _{IL} = 0.7 V,	1, 2, 3	2.4		V
Low level output voltage	V _{OL}	V _{CC} = 4.5 V, V _{IH} = 2.0 V,	1, 2, 3		0.4	V
Off-state output current, high level voltage applied	I _{OZH}	V _{CC} = 5.5 V, V _{IH} = 2.0 V, V _{IL} = 0.7 V	1, 2, 3		20	μA
Off-state output current, low level voltage applied	I _{OZL}		1, 2, 3		-200	μA
High level input current	I _{IH1}	V _{CC} = 5.5 V,	1, 2, 3		0.1	mA
High level input current, any input	I _{IH2}	V _{CC} = 5.5 V,	1, 2, 3		20	μA
Low level input current	I _{IL}	V _{CC} = 5.5 V,	1, 2, 3		-200	μA
Output short circuit current	I _{OS}	V _{CC} = 5.5 V V _{OUT} = 0.0 V <u>1/</u>	1, 2, 3	-40	-225	mA
Supply current	I _{CC}	V _{CC} = 5.5 V	Outputs high	1, 2, 3	70	mA
			Outputs low	1, 2, 3	90	mA
			All outputs disabled	1, 2, 3	95	mA
Functional tests		See 4.3.1c	7			

See footnote at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	DWG NO. 80021	
		REV C	PAGE 4

DESC FORM 193A
FEB 86

TABLE 1. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _C < +125°C, unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
Propagation delay time, low-to- high level output	t _{PLH}	V _{CC} = 5.0 V, R _L = 667Ω ±5%, C _L = 50 pF ±10% 2/	9, 10, 11		22	ns
Propagation delay time, high-to- low level output	t _{PHL}		9, 10, 11		22	ns
Disabled time to low level output	t _{PZL}		9, 10, 11		58	ns
Disabled time to high level output	t _{PZH}		9, 10, 11		58	ns
Low level time to disable output	t _{PLZ}		9, 10, 11		39	ns
High level time to disable output	t _{PHZ}		9, 10, 11		53	ns

- 1/ Not more than one output should be shorted at a time, and the duration of the short circuit condition should not exceed one second.
- 2/ Testing may be performed using either C_L = 5 pF, C_L = 45 pF, or C_L = 50 pF; however, the manufacturer shall certify that the microcircuits meet the switching test limits specified for a 50 pF load.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE		DWG NO.	
	A		80021	
		REV	C	PAGE 5

DESC FORM 193A
FEB 86

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test (method 1015 of MIL-STD-883).
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, and 8 of table I of method 5005 of MIL-STD-883 shall be omitted.
- c. Subgroup 7 tests shall verify the truth table.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test (method 1005 of MIL-STD-883) conditions:
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	DWG NO. 80021	
		REV C	PAGE 6

DESC FORM 193A
FEB 86




FIGURE 1. Terminal connections (top views) and logic diagram.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	DWG NO. 80021
	REV C	PAGE 7

DESC FORM 193A
FEB 86

ENABLE G	DIRECTION CONTROL DIR	OPERATION
L	L	B data to A bus
L	H	A data to B bus
H	X	Isolation

H = high level

L = low level

X = irrelevant

FIGURE 2. Truth table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A		DWG NO. 80021
		REV C	PAGE 8

DESC FORM 193A
FEB 86

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3, 9
Group A test requirements (method 5005)	1, 2, 3, 7, 9 10, 11**
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3

* PDA applies to subgroup 1.

** Subgroups 10 and 11, if not tested, shall be
guaranteed to the specified limits in table I.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Replaceability is determined as follows:

- Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.
- When a QPL source is established, the part numbered device specified in this drawing will be replaced by the microcircuit identified as part number M38510/32803B--.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, OH 45444, or telephone 513-296-5375.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A		DWG NO. 80021
		REV C	PAGE 9

DESC FORM 193A
FEB 86

6.4 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed herein have agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number 1/	Replacement military specification part number
80021012X 2/	04713 01295 18324	54LS245M/B2CJC SNJ54LS245FK 54LS245/B2X	M38510/3280382X
8002101SX 2/	04713 01295 18324	54LS245/8SAJC SNJ54LS245W 54LS245/BSA	M38510/328038SX

- 1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.
2/ Inactive for new design, use QPL-38510 device.

Vendor CAGE
number

04713

01295

18324

Vendor name
and address

Motorola, Inc.
7402 South Price Road
Tempe, AZ 85283

Texas Instruments, Inc.
P. O. Box 6448
Midland, TX 79701

Signetics Corp.
4130 South Market Ct.
Sacramento, CA 95834

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A		DWG NO. 80021
		REV D	PAGE 10

DESC FORM 193A
FEB 86

012775 - - -