

434085

Catamount®

Cable Ties



Mounting Head Ties

Cat. No. Std.	Cat. No. Bulk	Material	Color	Bundle Diameter		Length		Width		Minimum Loop Tensile	Mounting Head Screw Size	Std. Pkg.	Bulk Qty.
				Inch	(mm)	Inch	(mm)	Inch	(mm)				
L-5-30MH-0-C	L-5-30MH-0-M	UV Nylon	Black	1/4 - 1 1/4	(2 - 32)	5.0	(127)	.140	(4)	30	(13.6)	No. 8	100
L-5-30MH-0-C	L-5-30MH-0-M	Nylon	Natural	1/4 - 1 1/4	(2 - 32)	5.0	(127)	.140	(4)	30	(13.6)	No. 8	100
L-7-50MH-0-C	L-7-50MH-0-M	UV Nylon	Black	1/4 - 7/8	(2 - 44)	7.5	(191)	.185	(5)	50	(13.6)	No. 10	100
L-7-50MH-0-C	L-7-50MH-0-M	Nylon	Natural	1/4 - 1 1/4	(2 - 44)	7.5	(191)	.185	(5)	50	(13.6)	No. 10	100
L-11-50MH-0-C	L-11-50MH-0-M	UV Nylon	Black	1/4 - 3	(2 - 76)	11.1	(282)	.187	(5)	50	(22.7)	No. 10	100
L-11-50MH-0-C	L-11-50MH-0-M	Nylon	Natural	1/4 - 3	(2 - 76)	11.1	(282)	.187	(5)	50	(22.7)	No. 10	100
L-14-50MH-0-C	L-14-50MH-0-M	UV Nylon	Black	1/4 - 4	(2 - 102)	14.5	(368)	.187	(5)	50	(22.7)	No. 10	100
L-14-50MH-0-C	L-14-50MH-0-M	Nylon	Natural	1/4 - 4	(2 - 102)	14.5	(368)	.187	(5)	50	(22.7)	No. 10	100
L-14-120MH-0-C		UV Nylon	Black	1/4 - 4	(2 - 102)	14.5	(368)	.300	(8)	120	(54.4)	1/4 inch	100
L-14-120MH-0-C		Nylon	Natural	1/4 - 4	(2 - 102)	14.5	(368)	.300	(8)	120	(54.4)	1/4 inch	100

* Use QC-100, L-200, L-400, L-400C, ERG-297, or ERG-299 Installation Tool.



Restricted Bundle

Cat. No. Std.	Cat. No. Bulk	Material	Color	Bundle Diameter		Length		Width		Minimum Loop Tensile	Tab Height	Std. Pkg.	Bulk Qty.
				Inch	(mm)	Inch	(mm)	Inch	(mm)		Inch (mm)		
L-5-30TB-3-M		Nylon	Dark Blue	1/4 - 1 1/4	(2 - 32)	5.0	(127)	.130	(3)	30	(13.6)	100	1000

* Recommended for tote-box, security and temporary applications.
* Use QC-100, L-200, L-400, L-400C, or ERG-299 Installation Tools on Low pulling.



Releasable Ties

Cat. No. Std.	Cat. No. Bulk	Material	Color	Bundle Diameter		Length		Width		Minimum Loop Tensile	Std. Pkg.	Bulk Qty.
				Inch	(mm)	Inch	(mm)	Inch	(mm)			
L-5-50R-0-C	L-5-50R-0-D	Nylon	Black	1/4 - 1 1/4	(2 - 32)	5.0	(127)	.298	(7.5)	50	(22.7)	100
L-5-50R-0-C	L-5-50R-0-D	Nylon	Natural	1/4 - 1 1/4	(2 - 32)	5.0	(127)	.298	(7.5)	50	(22.7)	100
L-5-50R-0-C	L-5-50R-0-D	Nylon	Black	1/4 - 2	(2 - 51)	7.8	(198)	.298	(7.5)	50	(22.7)	100
L-5-50R-0-C	L-5-50R-0-D	Nylon	Natural	1/4 - 2	(2 - 51)	7.8	(198)	.298	(7.5)	50	(22.7)	100
L-10-50R-0-C	L-10-50R-0-D	Nylon	Black	1/4 - 3	(2 - 76)	11.1	(282)	.298	(7.5)	50	(22.7)	100
L-10-50R-0-C	L-10-50R-0-D	Nylon	Natural	1/4 - 3	(2 - 76)	11.1	(282)	.298	(7.5)	50	(22.7)	100

* Push Button Release.
* Use QC-100, L-200, L-400, L-400C, ERG-297, ERG-299 Installation Tool.



L = labelled
P = Plain

* Suffix MC multi-comp.

Thomas & Betts

© 2001 Thomas & Betts Corporation. Specifications are subject to change without notice. www.tnb.com