

54F/74F02 Quad 2-Input NOR Gate

General Description

This device contains four independent gates, each of which performs the logic NOR function.


Ordering Code: See Section 11

| Commercial | Military | Package Number | Package Description |
|------------------|------------------|----------------|---|
| 74F02PC | | N14A | 14-Lead (0.300" Wide) Molded Dual-In-Line |
| | 54F02DM (Note 2) | J14A | 14-Lead Ceramic Dual-In-Line |
| 74F02SC (Note 1) | | M14A | 14-Lead (0.150" Wide) Molded Small Outline, JEDEC |
| 74F02SJ (Note 1) | | M14D | 14-Lead (0.300" Wide) Molded Small Outline, EIAJ |
| | 54F02FM (Note 2) | W14B | 14-Lead Cerpack |
| | 54F02LM (Note 2) | E20A | 20-Lead Ceramic Leadless Chip Carrier, Type C |

Note 1: Devices also available in 13" reel. Use suffix = SCX and SJX.


Note 2: Military grade device with environmental and burn-in processing. Use suffix = DMQB, FMQB and LMQB.

Logic Symbol




TL/F/9455-3

Pin Assignment for DIP, SOIC and Flatpak



TL/F/9455-2

Pin Assignment for LCC



TL/F/9455-1

Unit Loading/Fan Out: See Section 2 for U.L. definitions

| Pin Names | Description | 54F/74F | |
|--|-------------------|--------------------|---|
| | | U.L. HIGH/LOW | Input I _H /I _L Output I _{OH} /I _{OL} |
| A _n , B _n bar{O} _n | Inputs Outputs | 1.0/1.0 50/33.3 | 20 μA/-0.6 mA -1 mA/20 mA |

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|--|------------------------------------|
| Storage Temperature | −65°C to +150°C |
| Ambient Temperature under Bias | −55°C to +125°C |
| Junction Temperature under Bias Plastic | −55°C to +175°C −55°C to +150°C |
| V _{CC} Pin Potential to Ground Pin | −0.5V to +7.0V |
| Input Voltage (Note 2) | −0.5V to +7.0V |
| Input Current (Note 2) | −30 mA to +5.0 mA |

| | |
|--|--------------------------|
| Voltage Applied to Output in HIGH State (with V _{CC} = 0V) | −0.5V to V _{CC} |
| Standard Output TRI-STATE® Output | −0.5V to +5.5V |

| | |
|---|--------------------------------------|
| Current Applied to Output in LOW State (Max) | twice the rated I _{OL} (mA) |
|---|--------------------------------------|

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

| | |
|------------------------------|-----------------|
| Free Air Ambient Temperature | |
| Military | −55°C to +125°C |
| Commercial | 0°C to +70°C |
| Supply Voltage | |
| Military | +4.5V to +5.5V |
| Commercial | +4.5V to +5.5V |

DC Electrical Characteristics

| Symbol | Parameter | 54F/74F | | | Units | V _{CC} | Conditions |
|------------------|-----------------------------------|-------------------------|------|------|-------|-----------------|--|
| | | Min | Typ | Max | | | |
| V _{IH} | Input HIGH Voltage | 2.0 | | | V | | Recognized as a HIGH Signal |
| V _{IL} | Input LOW Voltage | | 0.8 | | V | | Recognized as a LOW Signal |
| V _{CD} | Input Clamp Diode Voltage | | | −1.2 | V | Min | I _{IN} = −18 mA |
| V _{OH} | Output HIGH Voltage | 54F 10% V _{CC} | 2.5 | | | | I _{OH} = −1 mA |
| | 74F 10% V _{CC} | 2.5 | | | | | I _{OH} = −1 mA |
| | 74F 5% V _{CC} | 2.7 | | | | | I _{OH} = −1 mA |
| V _{OL} | Output LOW Voltage | 54F 10% V _{CC} | 0.5 | | V | Min | I _{OL} = 20 mA |
| | 74F 10% V _{CC} | 0.5 | | | | | I _{OL} = 20 mA |
| I _{IH} | Input HIGH Current | 54F | 20.0 | | μA | Max | V _{IN} = 2.7V |
| | 74F | | 5.0 | | | | |
| I _{BVI} | Input HIGH Current Breakdown Test | 54F | 100 | | μA | Max | V _{IN} = 7.0V |
| | 74F | | 7.0 | | | | |
| I _{CEx} | Output HIGH Leakage Current | 54F | 250 | | μA | Max | V _{OUT} = V _{CC} |
| | 74F | | 50 | | | | |
| V _{ID} | Input Leakage Test | 74F | 4.75 | | V | 0.0 | I _{ID} = 1.9 μA All other pins grounded |
| I _{OD} | Output Leakage Circuit Current | 74F | | 3.75 | μA | 0.0 | V _{IOD} = 150 mV All other pins grounded |
| I _{IL} | Input LOW Current | | | −0.6 | mA | Max | V _{IN} = 0.5V |
| I _{OS} | Output Short-Circuit Current | −60 | −150 | mA | Max | | V _{OUT} = 0V |
| I _{CCH} | Power Supply Current | | 3.7 | 5.6 | mA | Max | V _O = HIGH |
| I _{CLL} | Power Supply Current | | 8.7 | 13.0 | mA | Max | V _O = LOW |

AC Electrical Characteristics: See Section 2 for Waveforms and Load Configurations

| Symbol | Parameter | 74F | | | 54F | | 74F | | Units | Fig. No. | | |
|------------------------|--|---------------------|------------|------------|---------------------|------------|---------------------|------------|-------|-------------|--|--|
| | | $T_A = +25^\circ C$ | | | $T_A, V_{CC} = MII$ | | $T_A, V_{CC} = Com$ | | | | | |
| | | Min | Typ | Max | Min | Max | Min | Max | | | | |
| t_{PLH} t_{PHL} | Propagation Delay A_n, B_n to \bar{O}_n | 2.5 1.5 | 4.4 3.2 | 5.5 4.3 | 2.5 1.5 | 7.5 6.5 | 2.5 1.5 | 6.5 5.3 | ns | 2-3 | | |