

Farnell Code Nos:



HEALTH AND SAFETY DATA SHEET

12 August 1996

KLINGERSIL C-4400

Identification of the substances/preparation and of the company/undertaking 1.

1.1 SUPPLIER:

Klinger Limited

The Klinger Building Wharfedale Road

Euroway Trading Estate

Bradford BD4 6SG

1.2

MATERIAL:

KLINGERSIL C-4400

GENERIC NAME: ASBESTOS FREE

SHEETING AND

GASKETS

FAX NO:

PERSON TO CONTACT: John Middlemiss

TELEPHONE NO:

01274 688222

01274 688549

MSDS REF:

35 30/05/96

ISSUE DATE: STATE OF ISSUE:

2. Composition/information on ingredients

INGREDIENT 1:

Synthetic Rubber

10 - 15 %

INGREDIENT 2:

Aluminium Silicate Clays

40 - 45%

INGREDIENT 3:

Treated Fused Silica

3 - 8%

INGREDIENT 4:

Aramid Fibre

15 - 20%

INGREDIENT 5:

Carbonised Fibre

10 - 5%

3. Hazard Identification

In its form as supplied, has no known hazards. Dust arising from working the product should be regarded as nuisance particulate material - O.E.S. is 10mg/m3.8 hr TWA total inhalable dust. Prolonged exposure to dust concentrations above the O.E.S. can lead to lung and breathing disorders

4. First-Aid Measures

SKIN CONTACT:

Wash with soapy water.

EYE CONTACT:

Remove Solid particle(s) and bathe in cold water for 10 minutes.

INGESTION:

Not Hazardous - Drink plenty of fluid to assist passage through the system.

INHALATION:

Remove to fresh air.

DOCTOR: Klinger Limited

The Klinger Building

Tel (01274) 688222 Fax (01274) 688549

Wharfedale Road **Euroway Trading Estate**

Bradford BD4 6SG

International

Telex 517036

Tel +44 1274 688222 Fax +44 1274 688549





12 August 1996 KLINGERSIL C-4400

5. Fire Fighting Measures

EXTINGUISHING MEDIA: Water, Carbon Dioxide, Dry Powder

SPECIAL FIRE FIGHTING PROCEDURES: Fire Fighters should use breathing apparatus and eye

protection against OS dust and fumes from burning

rubber.

ADDITIONAL ADVICE: Extra cooling may be needed to prevent re-ignition of

rubber

6. Accidental Release Measures

PERSONAL PRECAUTION: See point four. Use personal protection equipment.

ENVIRONMENTAL PRECAUTION: Do not burn.

METHOD FOR CLEANING UP: Use approved vacuum cleaner.

7. Handling and Storage

HANDLING: Keep in dry place away from sources of heat.

STORAGE: Keep in dry place away from sources of heat.

8. Exposure controls/personal protection

OES MEL EH40 93: 10MG/M3 8 HR. TWA total inhalable dust.

RESPIRATORY PROTECTION: None required if LEV is effected.

VENTILATION: Where generation of dust exceeds the O.E.S. effective

local extract ventilation should be used.

HAND PROTECTION:

EYE PROTECTION:

SKIN PROTECTION:

OTHERS: Wear gloves and overalls.

Klinger Limited
The Klinger Building
Wharfedale Road
Euroway Trading Estate
Bradford BD4 6SG

Tel (01274) 688222 Fax (01274) 688549 Telex 517036







13 August 1996 KLINGERSIL C-4400

9. Physical and chemical properties

APPEARANCE AND ODOUR:	Green - No Smell	
BOILING POINT:		
MELTING POINT:	Decomposes	
FLASH POINT:		
FLAMMABILITY:		
AUTOFLAMMABILITY:		
EXPLOSIVE PROPERTIES:	N/A	
OXIDISING PROPERTIES:		
VAPOUR PRESSURE:	N/A	
SPECIFIC GRAVITY:	1.4-1.7	
SOLUBILITY IN WATER:	Insoluble	
PARTITION COEFFICIENT n-Octanol/Water:		
10. Stability and Reactivity		
CONDITIONS TO AVOID:		

CONDITIONS TO AVOID:

MATERIAL TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCT:

11. Toxicological Information

Non Toxic

Klinger Limited
The Klinger Building
Wharfedale Road
Euroway Trading Estate
Bradford BD4 6SG

Tel (01274) 688222 Fax (01274) 688549 Telex 517036







12 August 1996

KLINGERSIL C-4400

12. Ecological Information	12.	Ecol	ogical	Informatio	n
----------------------------	-----	------	--------	------------	---

MOBILITY:	
DEGRADABILITY:	Non-hazardous with normal materials handling care.
ACCUMULATION:	
SHORT AND LONG TERM EFFECTS:	
ECOTOXITY:	
OTHER ADVERSE EFFECTS:	

13. Disposal consideration

Off - Cuts, Centres and pips should be disposed of as normal industrial waste.

14. Transport Information

No special precautions necessary

Klinger Limited
The Klinger Building
Wharfedale Road
Euroway Trading Estate
Bradford BD4 6SG

Tel (01274) 688222 Fax (01274) 688549 Telex 517036



