

SERIES 601 5-TAPS 14 PIN FAST LOGIC DELAY MODULES

T-47-13

- 14 Pin DIL Package • TTL and DTL Compatible
- 5 Equally Spaced Taps • Low Cost Units

Specifications:

- Supply Voltage : 4.75 to 5.25VDC
- Logic 1 Input Current : 100 μ A Max
- Logic 0 Input Current : -1.6mA Max
- Logic 1 Volt Out : 2.5V Min
- Logic 0 Volt Out : 0.5V Max
- Logic 1 Fan-Out : 25 Max
- Logic 0 Fan-Out : 12.5 Max
- Output Rise Time⁽²⁾ : 2NSEC TYP.
- Operating Temp Range : 0°C to 70°C
- Temperature Coefficient : 100 PPM/°C

Input Test Conditions:

- Input Pulse Voltage : 3.2V
- Input Rise Time : ≤ 2 NSEC
- Pulse Width : 40% of Total Delay
- Supply Current ICCL* : 32mA
- ICCH* : 7mA

Electrical Specifications at 25°C (Measured with no Loads on Taps)

Part Number	Total Delay Nanosecond (1)	Tap To Tap Delay NSEC (1)
601-4*	4 $\pm$ 1	1 $\pm$ 0.5
601-5*	5 $\pm$ 1	1.2 $\pm$ 0.5
601-6*	6 $\pm$ 1	1.5 $\pm$ 0.5
601-8*	8 $\pm$ 2	2 $\pm$ 0.5
601-10*	10 $\pm$ 2	2.5 $\pm$ 0.5
601-12*	12 $\pm$ 2	3 $\pm$ 0.5
601-16*	16 $\pm$ 2	4 $\pm$ 0.6
601-25	25 $\pm$ 2	5 $\pm$ 0.8
601-30	30 $\pm$ 2	6 $\pm$ 1
601-35	35 $\pm$ 2	7 $\pm$ 1
601-40	40 $\pm$ 2	8 $\pm$ 1
601-45	45 $\pm$ 2.2	9 $\pm$ 1
601-50	50 $\pm$ 2.5	10 $\pm$ 2
601-60	60 $\pm$ 3	12 $\pm$ 2
601-75	75 $\pm$ 3.5	15 $\pm$ 2
601-100	100 $\pm$ 5.0	20 $\pm$ 2
601-125	125 $\pm$ 5.5	25 $\pm$ 2
601-150	150 $\pm$ 6.0	30 $\pm$ 3
601-175	175 $\pm$ 8.7	35 $\pm$ 3.5
601-200	200 $\pm$ 10	40 $\pm$ 4
601-250	250 $\pm$ 12.5	50 $\pm$ 5
601-300	300 $\pm$ 15	60 $\pm$ 6
601-350	350 $\pm$ 17.5	70 $\pm$ 7
601-400	400 $\pm$ 20	80 $\pm$ 8
601-500	500 $\pm$ 25	100 $\pm$ 10

Note: (1) Measured at 1.5v level leading edge.

(2) Measured from 0.75v to 2.4v.

*Time Delay measured with respect to 1st Tap.

Version A profile 0.250 inch and B profile 0.210 inch are available.
Please add A or B to above part number if lower profile is required.
(i.e. DL601-4A or DL601-4B)

