

3900 Series

Tubeaxial

92x92x25mm



■ AC fans with internal rotor shaded-pole motor. Impedance protected against overloading.

■ Metal fan housing, impeller of mineral-reinforced plastic PA.

■ Air exhaust over struts. Rotational direction CCW looking at rotor.



■ Mounting from either face using four 4.3 mm holes.

■ Electrical connection via 2 flat pins 2.8 x 0.5 mm.

■ Fan housing with ground lug for screw M4.

■ UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	Curve	CFM @ 0	VAC	Hertz	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Speed (RPM)	Features	Wgt. (lbs)
3900L	4	23.0	115	60	5	27	80	Sintec	1850	Terminals	0.62
3906L	4	23.0	115	60	5	27	80	Ball	1850	Terminals	0.62
3900M	5	31.2	115	60	5	34	80	Sintec	2600	Terminals	0.62
3906M	5	31.2	115	60	5	34	80	Ball	2600	Terminals	0.62
3900	6	41.2	115	60	9	40	80	Sintec	3150	Terminals	0.62
3906	6	41.2	115	60	9	40	80	Ball	3150	Terminals	0.62
3950L	1	18.2	230	50	6	24	80	Sintec	1550	Terminals	0.62
3956L	1	18.2	230	50	6	24	80	Ball	1550	Terminals	0.62
3950M	2	26.5	230	50	6	29	80	Sintec	2150	Terminals	0.62
3956M	2	26.5	230	50	6	29	80	Ball	2150	Terminals	0.62
3950	3	34.7	230	50	11	35	80	Sintec	2650	Terminals	0.62
3956	3	34.7	230	50	11	35	80	Ball	2650	Terminals	0.62



ebmpapst

e-mail: sales@us.ebmpapst.com · TEL: 860-674-1515 · FAX: 860-674-8536

ebm-papst Inc., 100 Hyde Road, Farmington, CT 06034 USA

ebm-papst Inc., 2006 © ebm-papst Inc. reserves the right to change any specifications or data without notice