


5962-E1020

## 1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

**1.2 Part number.** The complete part number shall be as shown in the following example:



**1.2.1 Device type.** The device type shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	54HC05	Hex inverters with open-drain outputs

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

<u>Outline letter</u>	<u>Case outline</u>
C	D-1 (14-lead, .785" x .310" x .200"), dual-in-line package
2	C-2 (20-terminal, .358" x .358" x .100"), square chip carrier package

### 1.3 Absolute maximum ratings. 1/

Supply voltage range	- - - - -	-0.5 V dc to +7.0 V dc
DC input voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
DC output voltage	- - - - -	-0.5 V dc to $V_{CC} + 0.5$ V dc
Clamp diode current	- - - - -	$\pm 20$ mA
DC output current (per pin)	- - - - -	$\pm 25$ mA
DC $V_{CC}$ or GND current (per pin)	- - - - -	$\pm 50$ mA
Continuous power dissipation ( $P_D$ ) <sup>2/</sup>	- - - - -	+500 mW
Storage temperature range	- - - - -	-65°C to +150°C
Lead temperature (soldering, 10 seconds)	- - - - -	+300°C
Thermal resistance, junction-to-case ( $\theta_{JC}$ )	- - - - -	See MIL-M-38510, appendix C
Junction temperature ( $T_J$ )	- - - - -	+175°C

#### 1.4 Recommended operating conditions.

Supply voltage range ( $V_{CC}$ )	- - - - -	+2.0 V dc minimum to +6.0 V dc maximum
Input voltage range	- - - - -	0 to $V_{CC}$
Output voltage range	- - - - -	0 to $V_{CC}$
Input rise or fall time:		
$V_{CC} = 2.0$ V dc	- - - - -	0 to 1000 ns
$V_{CC} = 4.5$ V dc	- - - - -	0 to 500 ns
$V_{CC} = 6.0$ V dc	- - - - -	0 to 400 ns
Case operating temperature range ( $T_C$ )	- - - - -	-55°C to +125°C

1/ Unless otherwise specified, all voltages are referenced to ground.

**Z/** For  $T_C = +100^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ , derate linearly at  $12\text{ mW}/^{\circ}\text{C}$ .

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	<b>SIZE A</b>		5962-88718
		<b>REVISION LEVEL</b>	<b>SHEET</b> 2

## 2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

### SPECIFICATION

#### MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

### STANDARD

#### MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

## 3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Test circuit and switching waveforms. The test circuit and switching waveforms shall be as specified on figure 3.

3.2.4 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full case operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	<b>SIZE</b> <b>A</b>		5962-88718
		<b>REVISION LEVEL</b>	<b>SHEET</b> 3

DESC FORM 193A  
SEP 87

☆ U. S. GOVERNMENT PRINTING OFFICE: 1988-550-547

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C < T <sub>C</sub> < +125°C unless otherwise specified <u>1/</u>		Group A subgroups	Limits		Unit
					Min	Max	
High level output current	I <sub>OH</sub>	V <sub>IN</sub> = V <sub>IH</sub> minimum or V <sub>IL</sub> maximum V <sub>OUT</sub> = 6.0 V	V <sub>CC</sub> = 6.0 V	1, 2, 3		10	μA
Low level output voltage	V <sub>OL</sub>	V <sub>IN</sub> = V <sub>IH</sub> minimum or V <sub>IL</sub> maximum I <sub>OL</sub> = 20 μA	V <sub>CC</sub> = 2.0 V	1, 2, 3		0.1	V
			V <sub>CC</sub> = 4.5 V			0.1	
			V <sub>CC</sub> = 6.0 V			0.1	
	V <sub>OL</sub>	V <sub>IN</sub> = V <sub>IH</sub> minimum or V <sub>IL</sub> maximum I <sub>OL</sub> = 4.0 mA	V <sub>CC</sub> = 4.5 V	1, 2, 3		0.4	V
		V <sub>IN</sub> = V <sub>IH</sub> minimum or V <sub>IL</sub> maximum I <sub>OL</sub> = 5.2 mA	V <sub>CC</sub> = 6.0 V	1, 2, 3		0.4	V
High level input voltage	V <sub>IH</sub>	<u>2/</u>	V <sub>CC</sub> = 2.0 V	1, 2, 3	1.5		V
			V <sub>CC</sub> = 4.5 V	1, 2, 3	3.15		
			V <sub>CC</sub> = 6.0 V	1, 2, 3	4.2		
Low level input voltage	V <sub>IL</sub>	<u>2/</u>	V <sub>CC</sub> = 2.0 V	1, 2, 3		0.3	V
			V <sub>CC</sub> = 4.5 V	1, 2, 3		0.9	
			V <sub>CC</sub> = 6.0 V	1, 2, 3		1.2	
Input capacitance	C <sub>IN</sub>	V <sub>CC</sub> = 2.0 V to 6.0 V see 4.3.1c	T <sub>C</sub> = +25°C	4		10	pF
Supply current	I <sub>CC</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND I <sub>OUT</sub> = 0.0	V <sub>CC</sub> = 6.0 V	1, 2, 3		40	μA

See footnotes at end of table.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-88718
		REVISION LEVEL	SHEET 4

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T <sub>C</sub> < +125°C unless otherwise specified <sup>1/</sup>		Group A subgroups	Limits		Unit
					Min	Max	
Input leakage current	I <sub>IN</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND	V <sub>CC</sub> = 6.0 V	1, 2, 3		±1	μA
Functional tests		See 4.3.1d		7, 8			
Propagation delay time, from A to Y	t <sub>PLH</sub>	R <sub>L</sub> = 1 kΩ C <sub>L</sub> = 50 pF See figure 3  <u>3/</u>	V <sub>CC</sub> = 2.0 V	9 10, 11		115 175	ns
			V <sub>CC</sub> = 4.5 V	9 10, 11		23 35	
			V <sub>CC</sub> = 6.0 V	9 10, 11		20 30	
Propagation delay time, from A to Y	t <sub>PHL</sub>	R <sub>L</sub> = 1 kΩ C <sub>L</sub> = 50 pF See figure 3  <u>3/</u>	V <sub>CC</sub> = 2.0 V	9 10, 11		85 130	ns
			V <sub>CC</sub> = 4.5 V	9 10, 11		17 26	
			V <sub>CC</sub> = 6.0 V	9 10, 11		14 22	
Transition time from high to low at Y	t <sub>THL</sub>	R <sub>L</sub> = 1 kΩ C <sub>L</sub> = 50 pF See figure 3  <u>3/</u>	V <sub>CC</sub> = 2.0 V	9 10, 11		75 110	ns
			V <sub>CC</sub> = 4.5 V	9 10, 11		15 22	
			V <sub>CC</sub> = 6.0 V	9 10, 11		13 19	

- <sup>1/</sup> For a power supply of 5.0 V ±10%, the worst case output voltage (V<sub>OL</sub>), for HC occur at 4.5 V. Thus, the 4.5 V values should be used when designing with this supply. Worst case V<sub>IH</sub> and V<sub>IL</sub> occur at V<sub>CC</sub> = 5.5 V and 4.5 V respectively. (The V<sub>IH</sub> value at 5.5 V is 3.85 V.) The worst case leakage currents (I<sub>IN</sub>, I<sub>CC</sub>, and I<sub>OZ</sub>) occur for CMOS at the higher voltage, so the 6.0 V values should be used. Power dissipation capacitance (C<sub>PD</sub>), typically 60 pF, determines the no load dynamic power consumption, P<sub>D</sub> = C<sub>PD</sub>V<sub>CC</sub><sup>2</sup>f + I<sub>CC</sub>V<sub>CC</sub>, and the no load dynamic current consumption, I<sub>S</sub> = C<sub>PD</sub>V<sub>CC</sub>f + I<sub>CC</sub>.
- <sup>2/</sup> V<sub>IH</sub> and V<sub>IL</sub> tests are not required if applied as a forcing function for V<sub>OH</sub> and V<sub>OL</sub>.
- <sup>3/</sup> AC testing at V<sub>CC</sub> = 2.0 V and V<sub>CC</sub> = 6.0 V shall be guaranteed, if not tested to the specified limits in table I.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	<b>SIZE</b> <b>A</b>		5962-88718
		<b>REVISION LEVEL</b>	<b>SHEET</b> 5

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

#### 4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test, method 1015 of MIL-STD-883.
  - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
  - (2)  $T_A = +125^{\circ}\text{C}$ , minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

##### 4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 5 and 6 in table I, method 5005 of MIL-STD-883 shall be omitted.
- c. Subgroup 4 ( $C_{in}$  measurement) shall be measured only for the initial test and after process or design changes which may affect input capacitance. Test all applicable pins on 5 devices with zero failures.
- d. Subgroup 7 and 8 tests shall verify the truth table specified on figure 2.

##### 4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
  - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
  - (2)  $T_A = +125^{\circ}\text{C}$ , minimum.
  - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-88718
		REVISION LEVEL	SHEET 6

Device type	01	
Case outlines	C	2
Terminal number	Terminal symbol	
1	1A	NC
2	1Y	1A
3	2A	1Y
4	2Y	2A
5	3A	NC
6	3Y	2Y
7	GND	NC
8	4Y	3A
9	4A	3Y
10	5Y	GND
11	5A	NC
12	6Y	4Y
13	6A	4A
14	VCC	5Y
15	---	NC
16	---	5A
17	---	NC
18	---	6Y
19	---	6A
20	---	VCC

NC = No connection


FIGURE 1. Terminal connections.

Input A	Output Y
H	L
L	H

H = High voltage level  
L = Low voltage level

FIGURE 2. Truth table.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-88718
		REVISION LEVEL	SHEET 7



NOTES:

1. Input characteristics:  $PRR \leq 1\text{ MHz}$ ,  $Z_{OUT} = 50\Omega$ ,  $t_r = t_f \leq 6\text{ ns}$ .
2.  $C_L$  includes probe and jig capacitance.

FIGURE 3. Test circuit and switching waveforms.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>	5962-88718	
		REVISION LEVEL	SHEET 8



TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3, 7, 8, 9, 10, 11
Group A test requirements (method 5005)	1, 2, 3, 4, 7, 8, 9, 10, 11
Group C and D end-point electrical parameters (method 5005)	1, 2, 3

\* PDA applies to subgroup 1.

## 5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

## 6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

## STANDARDIZED MILITARY DRAWING

DEFENSE ELECTRONICS SUPPLY CENTER  
DAYTON, OHIO 45444

SIZE  
**A**

5962-88718

REVISION LEVEL

SHEET

9

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number 1/
5962-8871801CX	01295	SNJ54HC05J
5962-88718012X	01295	SNJ54HC05FK

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE  
number

01295

Vendor name  
and address

Texas Instruments, Incorporated  
P.O. Box 60448  
Midland, TX 79711-0448

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-88718
		REVISION LEVEL	SHEET 10

DESC FORM 193A  
SEP 87

\* U. S. GOVERNMENT PRINTING OFFICE: 1988-550-547

011086 ✓