

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0039012125](#)
Status: **Active**
Overview: [minifit_jr](#)
Description: 4.20mm (.165") Pitch Mini-Fit Jr.™ Receptacle Housing, Dual Row, UL 94V-0, 12 Circuits

Documents:

3D Model	Product Specification PS-5556-001 (PDF)
Test Summary (PDF)	Product Specification PS-5557-001 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	Crimp Housings
Series	5557
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.. Glow Wire Equivalent Part Number 50361674 . Use with Strain Relief 41995 Series minifit_jr
Overview	Mini-Fit Jr.™
Product Name	

Physical

Breakaway	No
Circuits (maximum)	12
Color - Resin	Ivory
Flammability	94V-0
Gender	Female
Glow-Wire Compliant	No
Material - Resin	Nylon
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.165 In
Pitch - Mating Interface (mm)	4.20 mm
Pitch - Term. Interface (in)	0.165 In
Pitch - Term. Interface (mm)	4.20 mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Electrical

Current - Maximum per Contact	13A
-------------------------------	-----

Material Info

Old Part Number	5557-12R-210
-----------------	--------------

Reference - Drawing Numbers

Packaging Specification	SPK-5557-001
-------------------------	--------------




image - Reference only

Series

EU RoHS

ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free Status

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[5557Series](#)

Mates With

[5559d](#) , [5566vw](#) , [5566vwo](#) , [5569rdf](#) , [5569rdp](#) , [43810a](#) , [43810b](#) , [43810c](#) , [43810d](#) , [44068a](#) , [44068b](#) , [44068c](#) , [44068d](#) , [44281](#) , [44472dw](#) , [44472dwo](#) , [87427](#) , [87427r](#) , [87427rf](#) , [42404](#) , [44474](#) , [42440](#) , [43879](#) , [42475](#)

Use With

[41995](#) Strain Relief



Product Specification

Sales Drawing



PS-5556-001, PS-5557-001, RPS-5557-002,
RPS-5557-004, RPS-5557-024, RPS-5557-031,
RPS-5557-036, RPS-5557-050, RPS-5557-058
SD-5557-003

This document was generated on 05/19/2010


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




4 CKT SHOWN



4-24 CKT



2 CKT ONLY



NOTES:

1) MATERIAL:

*"BLANK" = NYLON 6/6, 94V-2, COLOR: NATURAL.

*"BL" = NYLON 6/6, 94V-2, COLOR: BLACK.

*"RE" = NYLON 6/6, 94V-2, COLOR: RED.

*"YE" = NYLON 6/6, 94V-2, COLOR: YELLOW

*"210" = NYLON 6/6, 94V-0, COLOR: NATURAL.

*"225" = NYLON (PA6), UL94V-0, COLOR: BLACK, IEC 60335-1, 4th EDITION
GLOW WIRE CAPABLE.

*"225N" = NYLON (PA6), UL94V-0, COLOR: WHITE, IEC 60335-1, 4th EDITION
GLOW WIRE CAPABLE.

*"400" = NYLON 6/6, 94V-0, COLOR: BLACK.

2) FINISH: NOT APPLICABLE

3) PRODUCT SPECIFICATION: PS-5556-001

4) PACKAGING: BULK

5) PART MATES WITH MOLEX PLUG #5559 AND HEADERS #5566, #5569.

6) PART TO BE USED WITH MOLEX FEMALE TERMINAL #5556.

7) PART IS NOT DESIGNED FOR CURRENT SHARING.

8) CONNECTORS ARE NOT TO BE MATED OR UNMATED WHILE CIRCUITS ARE LIVE.





9) WIRES ARE TO BE DRESSED IN SUCH A MANNER TO ALLOW THE TERMINALS
TO FLOAT FREELY IN THE POCKET.

10) PART CONFORMS TO CLASS "B" REQUIREMENTS OF COSMETIC SPECIFICATION
PS-45499-002 WITH THE EXCEPTION OF DISCOLORATION, FLASH AND SINK MEET
CLASS "C" REQUIREMENTS.

△ TO BE MEASURED AT SURFACE Z

2.031/(51.6)	1.819/(46.2)		24
1.866/(47.4)	1.654/(42.0)		22
1.701/(43.2)	1.488/(37.8)	.142	20
1.535/(39.0)	1.323/(33.6)	(3.6)	18
1.370/(34.8)	1.157/(29.4)		16
1.205/(30.6)	0.992/(25.2)		14
1.039/(26.4)	0.827/(21.0)		12
0.874/(22.2)	0.661/(16.8)		10
0.709/(18.0)	0.496/(12.6)	.129	8
0.543/(13.8)	0.331/(8.4)	(3.3)	6
0.378/(9.6)	0.165/(4.2)		4
0.213/(5.4)	—		2
A	B	C	NO. OF CKTS.

MODIFIED ISO VIEW EC NO: UCP2010-2566 DRWN: JAGULAR 2010/04/05 CHKD: J.BELL 97/01/08 APPR: F.S.MITH 2010/04/14		QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	TITLE NEW MINI FIT CONN REC. HOUSING				
					IN/MM									
REV J4	DESCRIPTION		mm		INCH		DRAWN BY S. MOCHIZUKI	DATE '90/02/22						
			4 PLACES ± --		± ---									
			3 PLACES ± --		± .010									
			2 PLACES ± .25		± .015									
			1 PLACE ± 0.38		± ---		CHECKED BY M. FUKUSHIMA	DATE '97/01/08						
			ANGULAR ± 3 °											
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS											
			MATERIAL NO.		DOCUMENT NO.		MOLEX INCORPORATED							
			SEE SHEET 2		SD-5557-003									
			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											



CIRCUIT SIZE LAYOUT
(NOT TO SCALE)

LEGEND

5557-**R - *
CIRCUIT SIZE
RECEPTACLE
MATERIAL (SEE NOTE 1)

V-0 GLOW WIRE (BLACK)				V-0 GLOW WIRE (WHITE)			
	50-36-1667	5557-24R-225	24	-	-	-	24
	26-01-3167	5557-22R-225	22	-	-	-	22
*	26-01-3166	5557-20R-225	20	-	-	-	20
	50-36-1668	5557-18R-225	18	-	-	-	18
	50-36-1669	5557-16R-225	16	-	-	-	16
	50-36-2293	5557-14R-225	14	-	-	-	14
	50-36-1674	5557-12R-225	12	-	-	-	12
	50-36-1671	5557-10R-225	10	-	-	-	10
	50-36-1713	5557-08R-225	8	-	-	-	8
	50-36-1672	5557-06R-225	6	-	-	-	6
	50-30-4461	5557-04R-225	4	50-36-2301	5557-04R-225N	4	4
	50-36-1673	5557-02R-225	2	-	-	-	2
	EDP. NO.	ENG. NO.	NO. OF CKTS.	EDP. NO.	ENG. NO.	NO. OF CKTS.	

V-0 (BLACK)				V-0 (NATURAL)			
*	39-03-9242	5557-24R-400	24	39-01-2245	5557-24R-210	24	24
*	39-03-9222	5557-22R-400	22	39-01-2225	5557-22R-210	22	22
*	39-03-9202	5557-20R-400	20	39-01-2205	5557-20R-210	20	20
*	39-03-9182	5557-18R-400	18	39-01-2185	5557-18R-210	18	18
*	39-03-9162	5557-16R-400	16	39-01-2165	5557-16R-210	16	16
*	39-03-9142	5557-14R-400	14	39-01-2145	5557-14R-210	14	14
*	39-03-9122	5557-12R-400	12	39-01-2125	5557-12R-210	12	12
*	39-03-9102	5557-10R-400	10	39-01-2105	5557-10R-210	10	10
*	39-03-9082	5557-08R-400	8	39-01-2085	5557-08R-210	8	8
*	39-03-9062	5557-06R-400	6	39-01-2065	5557-06R-210	6	6
	39-03-9042	5557-04R-400	4	39-01-2045	5557-04R-210	4	4
	39-03-9022	5557-02R-400	2	39-01-2025	5557-02R-210	2	2
	EDP. NO.	ENG. NO.	NO. OF CKTS.	EDP. NO.	ENG. NO.	NO. OF CKTS.	

* = CONSULT FACTORY FOR AVAILABILITY.

V-2 (YELLOW)				V-2 (RED)				V-2 (BLACK)				V-2 (NATURAL)			
			24	-	-	-	24	*	39-01-3245	5557-24R-BL	24	39-01-2240	5557-24R	24	24
			22	-	-	-	22		39-01-3225	5557-22R-BL	22	39-01-2220	5557-22R	22	22
			20	-	-	-	20	*	39-01-3205	5557-20R-BL	20	39-01-2200	5557-20R	20	20
			18	-	-	-	18	*	39-01-3185	5557-18R-BL	18	39-01-2180	5557-18R	18	18
			16	-	-	-	16	*	39-01-3165	5557-16R-BL	16	39-01-2160	5557-16R	16	16
			14	-	-	-	14		39-01-3145	5557-14R-BL	14	39-01-2140	5557-14R	14	14
			12	-	-	-	12		39-01-3125	5557-12R-BL	12	39-01-2120	5557-12R	12	12
			10	-	-	-	10		39-01-3105	5557-10R-BL	10	39-01-2100	5557-10R	10	10
			8	-	-	-	8		39-01-3085	5557-08R-BL	8	39-01-2080	5557-08R	8	8
*	39-02-8061	5557-06R-YE	6	-	-	-	6		39-01-3065	5557-06R-BL	6	39-01-2060	5557-06R	6	6
*	39-02-8041	5557-04R-YE	4	*	39-02-8040	5557-04R-RE	4		39-01-3045	5557-04R-BL	4	39-01-2040	5557-04R	4	4
*	39-02-8021	5557-02R-YE	2	-	-	-	2		39-01-3025	5557-02R-BL	2	39-01-2020	5557-02R	2	2
	EDP. NO.	ENG. NO.	NO. OF CKTS.	EDP. NO.	ENG. NO.	NO. OF CKTS.		EDP. NO.	ENG. NO.	NO. OF CKTS.		EDP. NO.	ENG. NO.	NO. OF CKTS.	

MODIFIED CHARTS
EC NO: UCP2010-2566
DRAWN: JAGUILAR 2010/04/05
CHKD: J.BELL '97/01/08
APPR: F.S.MITH 2010/04/14

REV
J4

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH
4 PLACES ±0.2 ± ---
3 PLACES ±0.3 ± ---
2 PLACES ±0.4 ± ---
1 PLACE ± --- ± ---
ANGULAR ± 3 °
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE
MM ONLY
DRAWN BY DATE
S.MOCHIZUKI '90/02/22
CHECKED BY DATE
M.FUKUSHIMA '97/01/08
APPROVED BY DATE
M.FUKUSHIMA '97/01/08
MATERIAL NO.
SEE CHART
SIZE C

SCALE
1:1
DESIGN UNITS
METRIC
THIRD ANGLE PROJECTION
NEW MINI FIT CONN
REC. HOUSING
MOLEX INCORPORATED
DOCUMENT NO.
SD-5557-003
SHEET NO.
2 OF 2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION