

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0026033031

Status:


Active

Overview:

kk

Description:

3.96mm (.156") Pitch KK® Crimp Terminal Housing - Use With Trifurcon® Terminals, 3 Circuits



Documents:

3D Model

Drawing (PDF)

Product Specification PS-40-02 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Crimp Housings
Series	6442
Overview	kk
Product Name	KK®
Physical	
Circuits (maximum)	3
Color - Resin	Natural
Flammability	94V-2
Gender	Female
Glow-Wire Compliant	No
Material - Resin	Nylon
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.156 In
Pitch - Mating Interface (mm)	3.96 mm
Stackable	No
Temperature Range - Operating	0°C to +75°C
Material Info	
Old Part Number	6442-03-Z
Reference - Drawing Numbers	
Product Specification	PS-40-02
Sales Drawing	SD-6442

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

6442Series

Mates With

Molex 3.96mm (.156") pitch KK® headers

Use With

6838 and 7258 KK® Trifurcon crimp terminals

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1

M

L

K

J

I

H

G

F

E

D

C

B

A

M

L

K

J

I

H

G

F

E



D

C


B

A

NO. OF CKT'S.	DIM. A	DIM. B
1	-----	(4.78+.18)
	-----	.188+.007
2	(3.96+.13)	(8.74+.18)
	.156+.005	.344+.007
3	(7.92+.13)	(12.70+.18)
	.312+.005	.500+.007
4	(11.89+.13)	(16.66+.18)
	.468+.005	.656+.007
5	(15.85+.13)	(20.62+.18)
	.624+.005	.812+.007
6	(19.81+.13)	(24.59+.18)
	.780+.005	.968+.007
7	(23.77+.13)	(28.55+.18)
	.936+.005	1.124+.007
8	(27.74+.25)	(32.51+.30)
	1.092+.010	1.280+.012
9	(31.70+.25)	(36.47+.30)
	1.248+.010	1.436+.012
10	(35.66+.25)	(40.44+.30)
	1.404+.010	1.592+.012
11	(39.62+.25)	(44.40+.30)
	1.560+.010	1.748+.012
12	(43.59+.25)	(48.36+.30)
	1.716+.010	1.904+.012
13	(47.55+.30)	(52.32+.36)
	1.872+.012	2.060+.014
14	(51.51+.36)	(56.29+.41)
	2.028+.014	2.216+.016
15	(55.47+.36)	(60.25+.41)
	2.184+.014	2.372+.016
16	(59.44+.36)	(64.21+.41)
	2.340+.014	2.528+.016
17	(63.40+.36)	(68.17+.41)
	2.496+.014	2.684+.016
18	(67.36+.36)	(72.14+.41)
	2.652+.014	2.840+.016
19	(71.32+.36)	(76.10+.41)
	2.808+.014	2.996+.016
20	(75.29+.46)	(80.06+.51)
	2.964+.018	3.152+.020
21	(79.25+.46)	(84.02+.51)
	3.120+.018	3.308+.020
22	(83.21+.46)	(87.99+.51)
	3.276+.018	3.464+.020
23	(87.17+.46)	(91.95+.51)
	3.432+.018	3.620+.020
24	(91.14+.46)	(95.91+.51)
	3.588+.018	3.776+.020



SECTION "C-C"



- NOTES:
1. MATERIAL A: NYLON 6/6 UL94V-2, COLOR: NATURAL
 2. FINISH: N/A
 3. THIS PART COMPLIES WITH PRODUCT SPECIFICATION PS-40-02.
 4. SEE SHEET 2 FOR OPTIONS.
 5. HOUSING SHOWN ABOVE IS STANDARD HOUSING WITH NO OPTIONS.
 6. THIS HOUSING FOR USE WITH TERMINAL NO.,
6438-N, (18-22 GA) WITH (2.79) .110 MAX. INSULATION DIA.
6838-N, (18-24 GA) WITH (2.79) .110 MAX. INSULATION DIA.
7258-N, (22-26 GA) WITH (1.65) .065 MAX. INSULATION DIA.
 7. CIRCUIT SIZE MOLDED ON 4 THRU 24 CIRCUIT HOUSINGS ONLY.
 8. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

HOUSING OPTIONS

CODE	HOOKS	SIDE HOOKS	RAMP
BLANK	NONE	NONE	NONE
A	NONE	YES	NONE
R	NONE	NONE	FRICTION
B	NONE	NONE	TYPE B
C	NONE	NONE	TYPE C

VOLTAGE RATING OPTION
BLANK=NONE
V= '250 VAC' ON HOUSING

MAT'L. OPTION
BLANK= MATERIAL A (SEE NOTE 1)

MOLDED VOID CODE
Z=NO VOIDS
A=CKT. 1 VOID,
B=CKT. 2 VOID, ETC.
51=1ST MULTIPLE VOID,
52=2ND MULTIPLE VOID, ETC.


6442- * N - * - * - *

NO. OF CKT'S.

REMOVE D OPTION EC NO: UCP2009-3148 DRAWN BY: DRWNK/PPER CHKD BY: CHYKSS/SEK APPR:FSM/TH REV: J	QUALITY SYMBOLS =0 =0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
		mm INCH		DRAWN BY DATE POLGAR 1986/12/03		TITLE KK (3.96) .156 TRIFURCON CRIMP TERMINAL HOUSING 6442 SERIES			
		4 PLACES ± --- ± --- 3 PLACES ± --- ± .010 2 PLACES ± 0.25 ± .014 1 PLACE ± 0.36 ± --- ANGULAR ±1/2°		CHECKED BY DATE PATEL 1986/12/03		APPROVED BY DATE LENZ 1986/12/03		MATERIAL NO. DOCUMENT NO.	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-6442		SHEET NO. 1 OF 4	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION


CONTINUOUS RAMP ON HOUSINGS UP TO 8 CIRCUITS, AND ON 9 THRU 24 CIRCUITS. RAMPS ARE 4 CIRCUITS LONG, LOCATED AT BOTH ENDS.




20° TYP.

(L5)
.020

SECT. "E-E"



SINGLE CKT. VOID CODE



MULTIPLE CKT. VOID CODE

SEE LEGEND ON SHT.

SEE SHEET 1 EC NO: UC72009-3148 DRAWING: UPPER CH3C5030K APPR: F5M 1/1 2009/07/13 2009/07/13 2009/08/05	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±.005 ±.010 3 PLACES ±.005 ±.010 2 PLACES ±.025 ±.014 1 PLACE ±.036 ±.014 ANGULAR ±1/2°	DIMENSION STYLE MM/IN DRAWN BY DATE POLGAR 1986/12/05 CHECKED BY DATE PATEL 1986/12/05 APPROVED BY DATE LENZ 1986/12/05	SCALE --- INCH THIRD ANGLE PROJECTION	DESIGN UNITS (3.96)/156 TRIFURCON CRIMP TERMINAL HOUSING 6442 SERIES	MOLEX MOLEX INCORPORATED	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-6442	SHEET NO. 2 OF 4
	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE D	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
	REV								

lb_frame_D_P_ME_T
Rev. E 2006/04/15