TEMPIL°, INC.

MATERIAL SAFETY DATA SHEET

2901 Hamilton Blvd. South Plainfield, NJ 07080 MSDS NO: TS - 45°C - 70°C

DATE: June 10, 2000

PHONE: 908-757-8300 EMERGENCY NO: 800-424-9300 FAX: 908-757-9273

SECTION 1 MATERIAL IDENTIFICATION

TEMPILSTIK 45°C/113°F, 50°C/122°F, 55°C/131°F, 60°C/140°F, 65°C/149°F, 70°C/158°F PRODUCT NAME:

GENERIC NAME OR FAMILY: Temperature indicating product

SHIPPING NAMES: **DOT**: Non-regulated IATA: Non-regulated

HAZARDOUS COMPONENTS OF MIXTURE	WEIGHT %	OSHA PEL (PPM)	ACGIH TLV (PPM)	CAS Number
Not applicable				

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemical (s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of CFR 372:

Chemical Name	%	CAS Number
Not applicable		

SECTION 2 PHYSICAL DATA

BOILING POINT (°F): N.E.	SPECIFIC GRAVITY (H ₂ O = 1): N.E.
VAPOR PRESSURE (mm Hg.): N.E.	PERCENT VOLATILE BY VOLUME (%): N.A.
VAPOR DENSITY (AIR =1): N.E.	EVAPORATION RATE (N-Butyl Acetate = 1) : N.A.
SOLUBILITY IN WATER: Negligible	VOLATILE ORGANIC COMPOUNDS (VOC) : N.A.
APPEARANCE AND ODOR: Crayon like solid stick	

SECTION 3 FIRE AND EXPLOSION HAZARD DATA

SECTION 4 - REACTIVITY HAZARD DATA				
_				
UNUSUAL FIRE AND EXPLOSION HAZARD	S: None known			
SPECIAL FIRE FIGHTING PROCEDURES:	Wear self contained breathing app	paratus and protect	ive clothing.	
EXTINGUISHING MEDIA: Water, CO ₂ , dry c	chemical, foam			
PLASTIFORNI (and Method). N.E.	PLAWIWABLE LIWITS	N.E.	N.E.	
FLASH POINT (and Method): N.E.	FLAMMABLE LIMITS	LOWER	UPPER	

CONDITIONS TO AVOID: Not applicable

STABILITY: Stable

Incompatibility	(Materia	Is to Avoid): Strong oxid	dizing agent	ts or strong mineral acids	
		tion Products: Carbon r ERIZATION: Will not oc		arbon dioxide CONDITIONS TO AVOID: Not app	licable
	. 02		/001	T CONDITIONS TO ALL OID. NOT UPP	
		SECTION 5 - CON	TROL AN	ID PROTECTIVE MEASURES	
Respiratory Pr	otection	(Specify Type): NIOSH	approved re	espirator if ventilation is insufficient.	
Protective Glo	ves: Rub	ber	Eye Prote	ection: Safety glasses	
VENTILATION BE USED	I TO	□ Local Exhaust	Mecha	nical(general): If local ventilation is in	sufficient.
Other Protectiv		ng & Equipment: Not no se: Wash hands thoroug			
		SECTION	l 6 - HEAI	LTH HAZARD DATA	
PRIMARY RO OF ENTRY	UTES	☐ Inhalation ☐ S	Skin Absorpt	tion	
HEALTH HAZARDS		May cause eye, skin or :: Unknown.	respiratory	tract irritation.	
Target Organ I	Informati	on: Unknown		nay cause headache, dizziness, naus	
	lush with	n water for 15 minutes.		Skin Contact: Wash thoroughly wit	th soap and water.
Inhalation: Remove to fresh air. If breathing is difficult, obtain medical attention.		Ingestion: Obtain immediate medical attention.			
				•	
				OR SAFE HANDLING AND U	
Steps to be tak	ken if Ma	terial Is Spilled or Relea	ısed: Sweep	o up and place in bag for waste dispo	sal.
 Waste Disposa	al Method	ds: Dispose of in accord	dance with a	all Federal, State and local laws.	
Precaution to b	oe taken	in Handling & Storage:	Store in coo	ol, dry area. Avoid skin contact. Avoi	id breathing vapors.
Other Precauti	ions and	or Special Hazards: N	ot applicable	e.	
HMIS rating: 0=	Minimal	hazard 1= Slight haza	ard 2= M	loderate hazard 3= Serious hazard	4= Severe hazard

Health: 1 Flammability: 1 Reactivity: 0

This information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.