


ÖLFLEX-SERVO® 700

ÖLFLEX-SERVO® 700 CY

The combined control and supply cable
for motor connection, also with overall screening



Part Number	No. of cores and mm ² per conductor	Approx. outside diameter in mm	Copper weight kg/km	Approx. weight kg/km
ÖLFLEX-SERVO® 700				
0036 140 R + T	4 G 0,75 + 2 x (2 x 0,34) StD	9,6	91,9	120
0036 145 R + T	4 G 1,5 + 2 x (2 x 0,75) StD	12,1	100,6	185
0036 150 R + T	4 G 2,5 + (2 x 2 x 0,75) StD	13,9	142,1	327
0036 151 R + T	4 G 4 + (2 x 0,75 + 2 x 1,0) StD	15,8	217,8	423
0036 152 T	4 G 6 + (2 x 0,75 + 2 x 1,0) StD	16,7	294,6	544
0036 153 T	4 G 10 + (2 x 0,75 + 2 x 1,0) StD	20,4	448,2	802
0036 154 T	4 G 16 + (2 x 2 x 1,0) StD	23,5	668,8	1168
0036 155 T	4 G 25 + (2 x 2 x 1,5) StD	29,0	1059,2	1625
0036 025 T	4 G 1,5 + (2 x 0,75) FDF	11,7	98,0	149
0036 001 T	5 G 1,5 + (2 x 0,75) FDF	12,7	110,0	160
0036 015 T	7 G 1,5 + (2 x 0,75) FDF	12,4	144,8	210
0036 026 T	4 G 2,5 + (2 x 0,75) FDF	13,1	138,6	227
0036 010 T	5 G 2,5 + (2 x 0,75) FDF	14,4	159,0	246
0036 020 T	7 G 2,5 + (2 x 0,75) FDF	15,2	215,7	334
ÖLFLEX-SERVO® 700 CY				
0036 156 R + T	4 G 0,75 + 2 x (2 x 0,34) StD-CY	10,5	111,1	165
0036 157 R + T	4 G 1,5 + 2 x (2 x 0,75) StD-CY	12,7	147,5	245
0036 158 R + T	4 G 2,5 + (2 x 2 x 0,75) StD-CY	14,9	226,1	385
0036 159 R + T	4 G 4 + (2 x 0,75 + 2 x 1,0) StD-CY	16,6	303,6	482
0036 161 R + T	4 G 6 + (2 x 0,75 + 2 x 1,0) StD-CY	17,7	379,4	609
0036 162 T	4 G 10 + (2 x 0,75 + 2 x 1,0) StD-CY	21,6	591,7	828
0036 163 T	4 G 16 + (2 x 2 x 1,0) StD-CY	24,5	861,3	1150
0036 164 T	4 G 25 + (2 x 2 x 1,5) StD-CY	30,1	1261,8	1671

R = Coils up to 30 kg, T = Drums

No surplus sectioning for the lengths: 50 m, 100 m, 500 m, 1000 m

G = with protective conductor

X = without protective conductor