



Electronic Wire Specialists (Manufacturing) Ltd.,
Unit 24, Forgehammer Industrial Estate,
Cwmbran Gwent NP44 3AA
Telephone 01633 861243
FAX 01633 865600

Lap Screened and Braid Screened Audio Cables

Your Part No.	Description
140-460	1 x 7/0.1 Plain copper insulated in Red PVC, Lap screened and Grey PVC sheathed Nom O.D 2.0 mm Capacitance 360 pF/M Core to Screen
140-461	2 x 7/0.1 Red and Blue PVC insulated Plain copper conductors laid side-by-side, overall Lap screened, and Grey PVC sheathed Nom Dims 2.8 mm x 2.0 mm Capacitance 330 pF/M Core to Screen 180 pF/M Core to Core
140-462	1 x 7/0.2 Plain copper insulated in Blue PVC, Lap screened and Grey PVC sheathed Nom O.D 3.1 mm Capacitance 320 pF/M Core to Screen
140-463	2 x 7/0.2 Red and Blue PVC insulated Plain copper conductors laid side-by-side, overall Lap screened, and Grey PVC sheathed Nom Dims 4.7 mm x 3.1 mm Capacitance 310 pF/M Core to Screen 170 pF/M Core to Core
140-464	2 x 7/0.2 Red and Black PVC insulated Tinned copper conductors twisted together, overall Lap screened, and Grey PVC sheathed Nom O.D. 4.8 mm Capacitance 215 pF/M Core to Screen 120 pF/M Core to Core

- 140-465 2 x 10/0.1 Blue and Red PVC insulated Plain copper conductors, individually lap screened, laid side-by-side and sheathed in Grey PVC to give a flat "figure of 8 " section.
Nom Dims 4.3 mm x 2.1 mm
Capacitance 350 pF/M Core to Screen
- 140-466 2 x 7/0.2 Yellow and Red PVC insulated Tinned copper
sheathed conductors, individually lap screened, laid side-by-side and
 in Grey PVC to give a flat "figure of 8 " section.
Nom Dims 5.9 mm x 2.8 mm
Capacitance 320 pF/M Core to Screen
- 140-467 4 x 7/0.1 Red, Yellow, Blue, White Polyethylene insulated Plain
copper conductors, individually lap screened, Laid together, and
Grey PVC sheathed
Nom O.D 4.7 mm
Capacitance 95 pF/M Core to Screen