

2SK3533-01 (900V/2.0Ω/7A)**1) Package** TO-220**2) Absolute Maximum Ratings (Tc=25 unless otherwise specified)**

Items	Symbols	Ratings	Units
Drain-Source Voltage	V _{DS}	900	V
Continuous Drain Current	I _D	±7	A
Pulsed Drain Current	I _{D(pulse)}	±28	A
Gate-Source Voltage	V _{GS}	±30	V
Repetitive and Non-Repetitive Maximum Avalanche Current	I _{AR}	7	A
Non-Repetitive Maximum Avalanche Energy	E _{AS}	269.5	mJ *1
Maximum Drain-Source dV/dt	dV _{DS} /dt	20	kV/us
Peak Diode recovery dV/dt	dV/dt	5	kV/us *2
Maximum Power Dissipation	P _D @ T _c =25	225	W
	P _D @ T _a =25	2.02	W
Operating and Storage Temperature range	T _{ch}	150	
	T _{stg}	-55 ~ +150	

3) Electrical Characteristics (Tch=25 unless otherwise specified)

Items	Symbols	Test Conditions		min.	typ.	max.	Units
Drain-Source Breakdown Voltage	BV _{DSS}	I _D =250μA	V _{GS} =0V	900	---	---	V
Gate Threshold Voltage	V _{GS(th)}	I _D =250μA	V _{DS} =V _{GS}	3.0	---	5.0	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =900V V _{GS} =0V	T _{ch} =25 T _{ch} =125	---	---	50	μA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±30V	V _{DS} =0V	---	---	100	nA
Drain-Source On-State Resistance	R _{DS(on)}	I _D =3.5A	V _{GS} =10V	---	---	2.0	
Input Capacitance	C _{iss}	V _{DS} =25V		---	980	---	pF
Output Capacitance	C _{oss}	V _{GS} =0V		---	120	---	
Reverse Transfer Capacitance	C _{rss}	f=1MHz		---	6	---	
Total Gate Charge	Q _g	Vcc=450V		---	28	---	nC
Gate to Source Charge	Q _{gs}	I _D =7A		---	9	---	
Gate to Drain (Miller) Charge	Q _{gd}	V _{GS} =10V		---	8	---	
Avalanche Capability	I _{AV}	L=10.1mH Tch=25		7	---	---	A
Diode Forward On-Voltage	V _{SD}	I _F =7A, V _{GS} =0V, Tch=25		---	1.0	1.5	V

4) Thermal Characteristics

Items	Symbols	Test Conditions		min.	typ.	max.	Units
Channel to Case	R _{th(ch-c)}					0.56	W
Channel to Ambient	R _{th(ch-a)}					62.0	W

*1 L=10.1mH, Vcc=90V

*2 I_F≤-I_D, -di/dt=50A/μs, Vcc≤BV_{DSS}, Tch≤150°C

a:Absolute max ratings were revised.

DATE	NAME	APPROVED	Fuji Electric Co.,Ltd.		
DRAWN Sep.-03-'02	T. Kuboyama				
CHECKED Sep.-03-'02	J. Hogen				
REVISIONS			DWG.NO.	MT5F12134 1/1	